



FCC 47 CFR PART 15 SUBPART C TEST REPORT

For

Product Name: Tablet

Brand Name: PCD

Model No.: Q PAD

FCC ID: ZTP-QPAD

Test Report Number:

C141224R01-RPB

Issued for

Technology Brokers, INC

7412 SW 48ST Suite B, Miami, FL, 33133

Issued by

Compliance Certification Services Inc.

Kun shan Laboratory

**No.10 Weiye Rd., Innovation park, Eco&Tec,
Development Zone, Kunshan City, Jiangsu, China**

TEL: 86-512-57355888

FAX: 86-512-57370818



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by A2LA or any government agencies. The test results in the report only apply to the tested sample.



TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION	4
2. EUT DESCRIPTION	5
3. TEST METHODOLOGY	6
3.1 EUT CONFIGURATION	6
3.2 EXERCISEEUT	6
3.3 GENERAL TEST PROCEDURES	6
3.4 TEST MODE	7
3.5 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	8
4. INSTRUMENT CALIBRATION	9
5. FACILITIES AND ACCREDITATIONS	9
5.1 FACILTIES	9
5.2 EQUIPMENT	9
5.3 LABORATORY ACCREDITATIONS AND LISTING	9
5.4 TABLE OF ACCREDITATIONS	10
5.5 LIST OF MEASURING EQUIPMENT	11
5.6 SETUP CONFIGURATION	12
5.7 SUPPORT EQUIPMENT	12
6. FCC PART 15.247 REQUIREMENTS	13
6.1 PEAK POWER	13
6.2 20DB BANDWIDTH MEASUREMENT	15
6.3 HOPPING CHANNEL SEPARATION	20
6.4 NUMBER OF HOPPING FREQUENCY	23
6.5 TIME OF OCCUPANCY (DWELL TIME)	26
6.6 CONDUCTED BAND EDGES MEASUREMENT	31
6.7 CONDUCTED SPURIOUS EMISSION MEASUREMENT	38
6.8 RADIATED BAND EDGE AND SPURIOUS EMISSION MEASUREMENT	45
6.9 POWERLINE CONDUCTED EMISSIONS	56

**SUMMARY OF TEST RESULT**

Report Section	FCC Rule	Description	Limit	Result
3.1	15.247(a)(1)	Number of Channels	≥ 15Channels	Pass
3.2	15.247(a)(1)	Hopping Channel Separation	≥2/3 of 20dB BW	Pass
3.3	15.247(a)(1)	Dwell Time of Each Channel	≤0.4sec in 31.6sec period	Pass
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass
3.5	15.247(b) (1)	Peak Output Power	≤125mW	Pass
3.6	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass
3.7	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) &15.247(d)	Pass
3.8	15.207	AC Conducted Emission	15.207(a)	Pass
3.9	15.203 &15.247(b)	Antenna Requirement	N/A	Pass



Compliance Certification Services Inc.

Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

1. TEST RESULT CERTIFICATION

Product Name:	Tablet
Trade Name:	PCD
Model Name:	Q PAD
Series Model:	N/A
Applicant Discrepancy:	Initial
Device Category:	Mobile unit
Date of Test:	December 24, 2014 to December 25, 2014
Applicant:	Technology Brokers, INC 7412 SW 48ST Suite B, Miami, FL, 33133
Manufacturer:	Technology Brokers, INC 7412 SW 48ST Suite B, Miami, FL, 33133
Application Type:	Certification

APPLICABLE STANDARDS

STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4:2009 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Jeff Fang

Tested by:

James Yan

Jeff.Fang
RF Manager
Compliance Certification Services Inc.

James.yan
Test Engineer
Compliance Certification Services Inc.



Compliance Certification Services Inc.

Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

2. EUT DESCRIPTION

Product Name:	Tablet
Trade Name:	PCD
Model Name:	Q PAD
Model Discrepancy:	N/A
Hardware Version	KT837701
Software Version	M6502W_01_V006
Power Adapter Power Rating :	Power supply and ADP (rating) : Model : RYH60US0500100A Input: 100-240VAC 50/60HZ 0.2A Output: DC5.0V 1A Battery (rating) : Capacitance: 3500mAh 3.7V
Frequency Range :	Bluetooth:2402 ~ 2480 MHz
Transmit Power :	4.59dBm(2.88mW)
Modulation Technique :	FHSS
Transmit Data Rate :	GFSK(1 Mbps), $\pi/4$ -DQPSK(2 Mbps),8-DPSK(3 Mbps)
Number of Channels :	79 Channels
Antenna Specification :	PIFA Antenna
Antenna Specification:	1 dBi

Remark:

1. This submittal(s) (test report) is intended for **FCC ID: ZTP-QPAD** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4 and FCC CFR 47 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, 15.207, 15.209 and 15.247.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EXERCISEEUT

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4.



3.4 TEST Mode

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
Peak Output Power	GFSK	1 Mbps	0/39/78	1
	8DPSK	3 Mbps		
Hopping Channel Bandwidth	GFSK	1 Mbps	0/39/78	1
	8DPSK	3 Mbps		
Hopping Channel Separation	GFSK	1 Mbps	38-39	1
	8DPSK	3 Mbps		
Number of Hopping Frequency	GFSK	1 Mbps	0-78	1
	8DPSK	3 Mbps		
Dwell Time	DH1/DH3/DH5	1 Mbps	39	1
	3DH1/3DH3/3DH5	3 Mbps		
Spurious Emission	GFSK	1 Mbps	0/39/78	1
	8DPSK	3 Mbps		
Band Edge Emissions	GFSK	1 Mbps	0/78	1
	8DPSK	3 Mbps		
Radiated Emissions Below 1GHz	GFSK	1 Mbps	78	1
Radiated Emissions Above 1GHz	GFSK	1 Mbps	0/39/78	1
	8DPSK	3 Mbps		
AC Power Conducted Emissions	CTX	-	-	-

Remark: For radiated test cases below 1 GHz, the worst mode data rate channel 78 of 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests.



3.5 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.0900 - 0.1100	16.420 - 16.423	399.9 - 410.0	4.50 - 5.15
0.4950 - 0.505 ⁽¹⁾	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960.0 - 1240	7.25 - 7.75
4.1250 - 4.1280	25.50 - 25.67	1300 - 1427	8.025 - 8.500
4.17725 - 4.17775	37.50 - 38.25	1435.0 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73.0 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.2150 - 6.2180	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108.00 - 121.94	1718.8 - 1722.2	13.25 - 13.40
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.50
8.2910 - 8.2940	149.90 - 150.05	2310 - 2390	15.35 - 16.20
8.3620 - 8.3660	156.52475 - 156.52525	2483.5 - 2500.0	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.1700	3260 - 3267	23.6 - 24.0
12.2900 - 12.2930	167.72 - 173.20	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345 - 3358	36.43 - 36.5 ⁽²⁾
12.57675 - 12.57725	322.0 - 335.4	3600 - 4400	
13.3600 - 13.4100			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards. facilities and accreditations

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at CCS China Kunshan Lab at 10#Weiye Rd, Innovation Park Eco. & Tec. Development Zone Kunshan city JiangSu, (215300), CHINA.

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 LABORATORY ACCREDITATIONS AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by American Association for Laboratory Accreditation Program for the specific scope accreditation under Lab Code: 200581-0 to perform Electromagnetic Interference tests according to FCC Part 15 or 18 requirements. In addition, the test facilities are listed with Federal Communication Commission, Laboratory Division, 424105 for 10m chamber, 238958 for 3m chamber .



5.4 TABLE OF ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

Taiwan	TAF
USA	A2LA

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	Industry Canada
Japan	VCCI
Taiwan	BSMI
USA	FCC

Copies of granted accreditation certificates are available for downloading from our web site,
<http://www.ccsrf.com>



Compliance Certification Services Inc.

Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

5.5 LIST OF MEASURING EQUIPMENT

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	RS	FSU26	200789	2015-8-11
Spectrum Analyzer	Agilent	E4446A	MY44020154	2015-4-9
Bluetooth Tester	RS	CBT	100189	N.C.R
OSCILLOSCOPE	Agilent	DSO6104A	MY44002585	2015-3-13
Peak and Avg Power Sensor	Agilent	E9327A	US40441788	2015-3-13
MIMO Power Measurement Test Set	Agilent	U2021XA	MY53120005	2015-7-3
Power SPLITTER	Mini-Circuits	ZN2PD-9G	SF078500430	N.C.R
DC POWER SUPPLY	AGILENT	E3632A	MY50340053	2015-3-13
Temp. / Humidity Chamber	TERCHY	MHK-120AK	X30109	2015-1-23
Test Software	EZ-EMC			

977 Chamber

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	2015-4-9
Pre-Amplifier	MINI	ZFL-1000VH2	d041703	2015-1-22
Pre-Amplifier	Miteq	JS41-00101800-32-10P	1675713	2015-1-22
Bilog Antenna	Sunol	JB1	A062604	2015-3-6
Horn-antenna	SCHWARZBECK	BBHA9120D	D:267	2015-4-27
Turn Table	CT	CT123	4165	N.C.R
Antenna Tower	CT	CTERG23	3256	N.C.R
Controller	CT	CT100	95637	N.C.R
Test Software	EZ-EMC			

Conducted Emission

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI TEST RECEIVER	R&S	ESCI3	100781	2015-3-16
V (V-LISN)	SCHWARZBECK	NNLK 8129	8129-143	N.C.R
LISN (EUT)	FCC	FCC-LISN-50/250-50-2-02	SN:05012	2015-3-16
Pulse LIMITER	R&S	ESH3-Z2	100524	2015-9-24
Test Software	EZ-EMC			

Remark: Each piece of equipment is scheduled for calibration once a year.



5.6 SETUP CONFIGURATION

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

5.7 SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	Series No.	FCC ID
1.	N/A	N/A	N/A	N/A	N/A

Remark:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



6. FCC PART 15.247 REQUIREMENTS

6.1 PEAK POWER


Limit

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
2. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
3. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



Test Procedure

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.



Compliance Certification Services Inc.

Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

Test Results

No non-compliance noted

Test RESULTS

1M GFSK Modulation mode

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Limit (mW)	Result
Low	2402	3.23	2.10	125	PASS
Mid	2441	3.32	2.15		PASS
High	2480	3.16	2.07		PASS

3M 8-DPSK Modulation mode

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Limit (mW)	Result
Low	2402	2.57	1.81	125	PASS
Mid	2441	2.62	1.83		PASS
High	2480	2.40	1.738		PASS




6.2 20DB BANDWIDTH MEASUREMENT

Limit

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Configuration



Test Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 30kHz, VBW = 300kHz, Span = 2MHz, Sweep = auto.
4. Max hold, mark 2 peaks of hopping channel and record the 2 peaks frequency.



Compliance Certification Services Inc.

Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

Test Results of Bandwidth

No non-compliance noted

Operation Mode:	1 Mbps	Test Date:	December 25,2014
Temperature:	24°C	Tested by:	James.Yan

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
00	2402	0.826
39	2441	0.834
78	2480	0.904

Operation Mode:	3 Mbps	Test Date:	December 25,2014
Temperature:	24°C	Tested by:	James.Yan

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
00	2402	1.157
39	2441	1.157
78	2480	1.157



Compliance Certification Services Inc.


Report No: C141224R01-RPB

FCC ID: ZTP-QPAD


Date of Issue :December 25, 2014

Test Plot

1M Channel 00



1M Channel 39





Compliance Certification Services Inc.


Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014


1M Channel 78

* Agilent



3M Channel 00


* Agilent






3M Channel 39

* Agilent



3M Channel 78

* Agilent






6.3 HOPPING CHANNEL SEPARATION

LIMIT

According to §15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel.
4. Set the spectrum analyzer as RBW = 30kHz, VBW = 100kHz, Span = 3MHz, Sweep = auto.
5. Max hold, mark 2 peaks of hopping channel and record the 2 peaks frequency.



Compliance Certification Services Inc.

Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

TEST RESULTS

No non-compliance noted


Operation Mode:	1 Mbps	Test Date:	December 25,2014
Temperature:	24°C	Tested by:	James.Yan

Channel	Frequency	Separation	(2/3 of 20dB BW)	Result
	(MHz)	(MHz)	Limits (MHz)	
39~40	2441~2442	1.000	0.556	Pass

Operation Mode:	3 Mbps	Test Date:	December 25,2014
Temperature:	24°C	Tested by:	James.Yan


Channel	Frequency	Separation	(2/3 of 20dB BW)	Result
	(MHz)	(MHz)	Limits (MHz)	
39~40	2441~2442	1.000	0.771	Pass

1M Channel Separation Plot on Channel 39-40





3M Channel Separation Plot on Channel 39-40






6.4 NUMBER OF HOPPING FREQUENCY

LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2441MHz, Sweep = auto and Start=2441MHz, Stop = 2483.5MHz, Sweep = auto.
4. Set the spectrum analyzer as RBW, VBW=1MHz.
5. Max hold, view and count how many channel in the band.

TEST RESULTS

No non-compliance noted

Test Data

Operation Mode:	1 Mbps	Test Date:	December 25,2014
Temperature:	24°C	Tested by:	James.Yan

Result (No. of CH)	Limit (No. of CH)	Result
79	>15	PASS


Operation Mode:	3 Mbps	Test Date:	December 25,2014
Temperature:	24°C	Tested by:	James.Yan

Result (No. of CH)	Limit (No. of CH)	Result
79	>15	PASS






Test Plot:1M

Channel Number 2.4 GHz – 2.441 GHz



Channel Number 2.441 GHz – 2.4835 GHz



**Test Plot:3M****Channel Number 2.4 GHz – 2.441 GHz****Channel Number 2.441 GHz – 2.4835 GHz**




6.5 TIME OF OCCUPANCY (DWELL TIME)

LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
5. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

No non-compliance noted

Test Data

1M

DH 1

$$0.376 * (1600/2)/79 * 31.6 = 120.32(\text{ms})$$

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
0.376	120.32	31.60	400	PASS

DH 3

$$1.640 * (1600/4)/79 * 31.6 = 262.40 (\text{ms})$$

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
1.640	262.40	31.60	400	PASS

DH 5

$$2.900 * (1600/6)/79 * 31.6 = 309.33 (\text{ms})$$

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2.900	309.33	31.60	400	PASS



Compliance Certification Services Inc.

Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

3M

DH 1

$$0.384 * (1600/2)/79 * 31.6 = 122.88 \text{ (ms)}$$

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
0.384	122.88	31.60	400	PASS

DH 3

$$1.640 * (1600/4)/79 * 31.6 = 261.28 \text{ (ms)}$$

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
1.640	261.28	31.60	400	PASS

DH 5

$$2.900 * (1600/6)/79 * 31.6 = 305.81 \text{ (ms)}$$

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2.900	305.81	31.60	400	PASS



Compliance Certification Services Inc.


Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014


1M-DH1

* Agilent



1M-DH3

* Agilent





Compliance Certification Services Inc.


Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014


1M-DH5

* Agilent



3M-DH1

* Agilent






3M-DH3

* Agilent

R T

Mkr3 3.185 ms
-61.94 dBm




3M-DH5

* Agilent

R T

Mkr3 5.03 ms
-62.91 dBm






6.6 Conducted Band Edges Measurement

LIMIT

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

Test Configuration



TEST PROCEDURE

1. The testing follows the guidelines in Band-edge Compliance of RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz ($\geq 1\%$ span=10MHz), VBW = 300kHz (≥ 3 RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

TEST RESULTS


No non-compliance noted




Test Result of Conducted Band Edges

Operation Mode:	1 Mbps	Test Date:	December 25,2014
Test Channel:	00 and 78	Tested by:	James.Yan
Humidity:	52 % RH	Temperature:	24°C

Low Band Edge Plot on Channel 00



High Band Edge Plot on Channel 78





Compliance Certification Services Inc.


Report No: C141224R01-RPB

FCC ID: ZTP-QPAD


Date of Issue :December 25, 2014

Operation Mode:	2 Mbps	Test Date:	December 25,2014
Test Channel:	00 and 78	Tested by:	James.Yan
Humidity:	52 % RH	Temperature:	24°C

Low Band Edge Plot on Channel 00




High Band Edge Plot on Channel 78






Operation Mode:	3 Mbps	Test Date:	December 25,2014
Test Channel:	00 and 78	Tested by:	James.Yan
Humidity:	52 % RH	Temperature:	24°C

Low Band Edge Plot on Channel 00



High Band Edge Plot on Channel 78







Test Result of Conducted Hopping Mode Band Edges

Operation Mode:	1 Mbps	Test Date:	December 25,2014
Humidity:	52 % RH	Temperature:	24°C

1Mbps Hopping Mode Low Band Edge Plot




1Mbps Hopping Mode High Band Edge Plot






Operation Mode:	2 Mbps	Test Date:	December 25, 2014
Humidity:	52 % RH	Temperature:	24°C

2Mbps Hopping Mode Low Band Edge Plot




2Mbps Hopping Mode High Band Edge Plot






Operation Mode:	3 Mbps	Test Date:	December 25, 2014
Humidity:	52 % RH	Temperature:	24°C

3Mbps Hopping Mode Low Band Edge Plot



3Mbps Hopping Mode High Band Edge Plot






6.7 Conducted Spurious Emission Measurement

LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 300 KHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS

No non-compliance noted





Compliance Certification Services Inc.

Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

Operation Mode:	1 Mbps	Test Date:	December 25,2014
Test Channel:	00	Tested by:	James.Yan
Humidity:	52 % RH	Temperature:	24°C





Compliance Certification Services Inc.

Report No: C141224R01-RPB


FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

Operation Mode:	1 Mbps	Test Date:	December 25,2014
Test Channel:	39	Tested by:	James.Yan
Humidity:	52 % RH	Temperature:	24°C


* Agilent

R T



* Agilent

R T





Compliance Certification Services Inc.


Report No: C141224R01-RPB

FCC ID: ZTP-QPAD


Date of Issue :December 25, 2014

Operation Mode:	1 Mbps	Test Date:	December 25,2014
Test Channel:	78	Tested by:	James.Yan
Humidity:	52 % RH	Temperature:	24°C

* Agilent



* Agilent





Compliance Certification Services Inc.


Report No: C141224R01-RPB

FCC ID: ZTP-QPAD


Date of Issue :December 25, 2014

Operation Mode:	3 Mbps	Test Date:	December 25,2014
Test Channel:	00	Tested by:	James.Yan
Humidity:	52 % RH	Temperature:	24°C

* Agilent



* Agilent





Compliance Certification Services Inc.

Report No: C141224R01-RPB


FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

Operation Mode:	3 Mbps	Test Date:	December 25,2014
Test Channel:	39	Tested by:	James.Yan
Humidity:	52 % RH	Temperature:	24°C


* Agilent

R T



* Agilent

R T





Compliance Certification Services Inc.

Report No: C141224R01-RPB


FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

Operation Mode:	3 Mbps	Test Date:	December 25,2014
Test Channel:	78	Tested by:	James.Yan
Humidity:	52 % RH	Temperature:	24°C


* Agilent

R T



* Agilent

R T





6.8 Radiated Band Edge and Spurious Emission Measurement

LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3


Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (μ V/m at 3-meter)	Field Strength (dB μ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54


Test Configuration

Below 30MHz






Below 1 GHz



Above 1 GHz





TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:

Below 1GHz:

RBW=100kHz / VBW=300kHz / Sweep=AUTO

Above 1GHz:


(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO

7. Repeat above procedures until the measurements for all frequencies are complete.




RESTRICTED BANDEDGE (1Mbps, Low Channel, Horizontal)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	2390.000	46.38	-12.69	33.69	74.00	-40.31	100	200	peak
2	2390.000	34.21	-12.69	21.52	54.00	-32.48	100	200	AVG


RESTRICTED BANDEDGE (1Mbps, Low Channel, Vertical)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	2390.000	48.05	-12.69	35.36	74.00	-38.64	100	157	peak
2	2390.000	34.16	-12.69	21.47	54.00	-32.53	100	157	AVG




RESTRICTED BANDEDGE (1Mbps Mode, High Channel, Horizontal)



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2483.500	46.78	-12.27	34.51	74.00	-39.49	100	281	peak
2	2483.500	34.14	-12.27	21.87	54.00	-32.13	100	280	AVG


RESTRICTED BANDEDGE (1Mbps, High Channel, Vertical)



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2483.500	46.58	-12.27	34.31	74.00	-39.69	100	360	peak
2	2483.500	34.24	-12.27	21.97	54.00	-32.03	100	360	AVG




RESTRICTED BANDEDGE (3Mbps, Low Channel, Horizontal)



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2389.999	34.15	-12.69	21.46	54.00	-32.54	100	60	AVG
2	2390.000	47.83	-12.69	35.14	74.00	-38.86	100	60	peak


RESTRICTED BANDEDGE (3Mbps, Low Channel, Vertical)



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2390.000	46.70	-12.69	34.01	74.00	-39.99	100	298	peak
2	2390.000	48.70	-12.69	36.01	54.00	-17.99	100	297	AVG




RESTRICTED BANDEDGE (3Mbps, High Channel, Horizontal)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	2483.500	46.77	-12.27	34.50	74.00	-39.50	100	304	peak
2	2483.500	34.22	-12.27	21.95	54.00	-32.05	100	304	Avg

RESTRICTED BANDEDGE (3Mbps, High Channel, Vertical)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	2483.500	47.48	-12.27	35.21	74.00	-38.79	100	220	peak
2	2483.500	34.18	-12.27	21.91	54.00	-32.09	100	220	Avg



Compliance Certification Services Inc.

Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

TEST RESULT OF RADIATED EMISSION

30MHz-1GHz

Operation Mode: 1 Mbps **Test Date:** December 25,2014
Test Channel: CH78 **Tested by:** James.Yan
Temperature: 25°C **Polarity:** Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	118.2700	23.33	14.82	38.15	43.50	-5.35	204	274	peak
2	144.4600	27.14	14.58	41.72	43.50	-1.78	100	319	peak
3	205.5700	26.56	13.23	39.79	43.50	-3.71	204	360	peak
4	242.4300	31.12	13.84	44.96	46.00	-1.04	100	60	peak
5	255.0400	26.92	13.90	40.82	46.00	-5.18	100	55	peak
6	299.6600	28.16	14.72	42.88	46.00	-3.12	100	166	peak

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	30.0000	14.51	22.71	37.22	40.00	-2.78	204	264	peak
2	62.0100	26.52	8.28	34.80	40.00	-5.20	276	0	Peak
3	146.4000	27.21	14.21	41.42	43.50	-2.08	204	304	Peak
4	210.4200	27.33	13.13	40.46	43.50	-3.04	204	40	Peak
5	221.0900	29.46	13.36	42.82	46.00	-3.18	164	360	Peak
6	930.1600	16.81	25.35	42.16	46.00	-3.84	100	90	Peak

Notes:

- Measurements above show only up to maximum emissions noted, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- Radiated emissions measured in frequency range from 9 KHz to 1000MHz were made with an instrument using Peak detector mode.
- Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.



Compliance Certification Services Inc.

Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

Above 1 GHz

Operation Mode: 1 Mbps **Test Date:** December 25,2014

Test Channel: CH00 **Tested by:** James.Yan

Temperature: 25°C **Polarity:** Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
7075.320	V	45.17	0.15	45.32	74.00	-28.68	PEAK
12850.961	V	42.48	8.84	51.32	74.00	-22.68	PEAK
6121.795	H	45.38	-3.17	42.21	74.00	-24.85	PEAK
11679.487	H	42.42	7.98	50.40	74.00	-30.30	PEAK

Operation Mode: 1 Mbps **Test Date:** December 25,2014

Test Channel: CH39 **Tested by:** James.Yan

Temperature: 25°C **Polarity:** Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
5576.923	V	46.20	-4.71	41.49	74.00	-32.51	PEAK
12687.500	V	42.61	8.94	51.55	74.00	-22.45	PEAK
5767.628	H	46.39	-4.18	42.21	74.00	-31.79	PEAK
13504.808	H	42.11	8.61	50.72	74.00	-23.28	PEAK

Operation Mode: 1 Mbps **Test Date:** December 25,2014

Test Channel: CH78 **Tested by:** James.Yan

Temperature: 25°C **Polarity:** Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
5386.218	V	46.92	-5.28	41.64	74.00	-32.36	PEAK
12605.769	V	41.74	8.99	50.73	74.00	-23.27	PEAK
5713.141	H	45.94	-4.33	41.61	74.00	-32.39	PEAK
13750.000	H	41.72	9.93	51.65	74.00	-22.35	PEAK



Compliance Certification Services Inc.

Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

Operation Mode: 3 Mbps **Test Date:** December 25,2014
Test Channel: CH00 **Tested by:** James.Yan
Temperature: 25°C **Polarity:** Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
6230.769	V	44.42	-2.86	41.56	74.00	-32.44	PEAK
12169.872	V	41.39	8.02	49.41	74.00	-24.59	PEAK
6394.231	H	44.38	-2.38	42.00	74.00	-32.00	PEAK
14349.359	H	39.72	11.19	50.91	74.00	-23.09	PEAK

Operation Mode: 3 Mbps **Test Date:** December 25,2014
Test Channel: CH39 **Tested by:** James.Yan
Temperature: 25°C **Polarity:** Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
7266.025	V	41.94	0.20	42.14	74.00	-31.86	PEAK
10589.744	V	40.48	7.50	47.98	74.00	-26.02	PEAK
5631.410	H	44.03	-4.55	39.48	74.00	-34.52	PEAK
8437.500	H	41.90	1.65	43.55	74.00	-30.45	PEAK

Operation Mode: 3 Mbps **Test Date:** December 25,2014
Test Channel: CH78 **Tested by:** James.Yan
Temperature: 25°C **Polarity:** Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
5467.949	V	46.81	-5.02	41.79	74.00	-32.21	PEAK
9336.539	V	40.26	2.54	42.80	74.00	-31.20	PEAK
5822.115	H	46.47	-4.02	42.45	74.00	-31.55	PEAK
10616.987	H	41.58	7.58	49.16	74.00	-24.84	PEAK



Compliance Certification Services Inc.

Report No: C141224R01-RPB

FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
 - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto.



6.9 POWERLINE CONDUCTED EMISSIONS


LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration



See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.



Compliance Certification Services Inc.

Report No: C141224R01-RPB


FCC ID: ZTP-QPAD

Date of Issue :December 25, 2014

Test Data

Model: Q PAD	Humidity: 51% RH
Temperature: 23°C	Test Results: Pass
Tested by: James.Yan	


L1



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1	0.1703	26.25	15.26	19.72	45.97	34.98	64.95	54.95	-18.98	-19.97	Pass
2	0.1984	23.88	13.96	19.61	43.49	33.57	63.68	53.68	-20.19	-20.11	Pass
3	0.4840	23.11	16.19	19.82	42.93	36.01	56.27	46.27	-13.34	-10.26	Pass
4	0.6497	22.19	14.35	19.83	42.02	34.18	56.00	46.00	-13.98	-11.82	Pass
5	0.8746	20.01	9.36	19.84	39.85	29.20	56.00	46.00	-16.15	-16.80	Pass
6	16.6437	18.83	7.55	20.94	39.77	28.49	60.00	50.00	-20.23	-21.51	Pass



L2



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1	0.1700	23.17	12.62	19.69	42.86	32.31	64.96	54.96	-22.10	-22.65	Pass
2	0.1988	21.18	11.12	19.64	40.82	30.76	63.66	53.66	-22.84	-22.90	Pass
3	0.2542	17.58	8.52	19.68	37.26	28.20	61.62	51.62	-24.36	-23.42	Pass
4	0.8397	11.44	1.72	19.83	31.27	21.55	56.00	46.00	-24.73	-24.45	Pass
5	1.1340	13.11	7.36	19.84	32.95	27.20	56.00	46.00	-23.05	-18.80	Pass
6	16.2358	11.86	2.21	20.78	32.64	22.99	60.00	50.00	-27.36	-27.01	Pass

Remark:

1. The measuring frequencies range between 0.15 MHz and 30 MHz.
2. The emissions measured in the frequency range between 0.15 MHz and 30MHz were made with an instrument using Quasi-peak detector and Average detector.
3. “—” denotes the emission level was or more than 2dB below the Average limit, and no re-check was made.
4. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10KHz. The IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9kHz.

END OF REPORT