

# FCC Test Report

<b>FCC ID</b>	: ZTT-REC22P
<b>Equipment</b>	: High Power AC1200 Plug-In Wi-Fi Range Extender
<b>Model No.</b>	: REC22P、REC22PG (Different case color for marketing purpose only.)
<b>Brand Name</b>	: Amped
<b>Applicant</b>	: Amped Wireless
<b>Address</b>	: 13089 Peyton Dr. #C307 Chino Hills, California 91709 United State
<b>Standard</b>	: 47 CFR FCC Part 15.247
<b>Received Date</b>	: Dec. 28, 2015
<b>Tested Date</b>	: Jan. 18 ~ Feb. 02, 2016

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

**Approved & Reviewed by:**

Gary Chang  
Gary Chang / Manager



## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	Local Support Equipment List .....	7
1.3	Test Setup Chart .....	7
1.4	The Equipment List .....	8
1.5	Test Standards .....	9
1.6	Measurement Uncertainty .....	9
<b>2</b>	<b>TEST CONFIGURATION.....</b>	<b>10</b>
2.1	Testing Condition .....	10
2.2	The Worst Test Modes and Channel Details .....	10
<b>3</b>	<b>TRANSMITTER TEST RESULTS.....</b>	<b>11</b>
3.1	Conducted Emissions.....	11
3.2	6dB and Occupied Bandwidth .....	14
3.3	RF Output Power.....	17
3.4	Power Spectral Density .....	19
3.5	Unwanted Emissions into Restricted Frequency Bands .....	21
3.6	Emissions in Non-Restricted Frequency Bands .....	49
<b>4</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>62</b>

## Release Record

Report No.	Version	Description	Issued Date
FR5D2803-01AC	Rev. 01	Initial issue	Feb. 19, 2016

## Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 2.173MHz 44.69 (Margin -1.31dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 4824.00MHz 53.83 (Margin -0.17dB) - AV	Pass
15.247(b)(3)	Maximum Output Power	Max Power [dBm]: 27.54	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

## 1 General Description

### 1.1 Information

#### 1.1.1 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N <sub>TX</sub> )	Data Rate / MCS
2400-2483.5	b	2412-2462	1-11 [11]	2	1-11 Mbps
2400-2483.5	g	2412-2462	1-11 [11]	2	6-54 Mbps
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	2	MCS 0-15
2400-2483.5	n (HT40)	2422-2452	3-9 [7]	2	MCS 0-15

Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.  
 Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.  
 Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

#### 1.1.2 Antenna Details

Ant. No.	Model	Type	Connector	Antenna Gain (dBi)		
				2400~2483.5MHz	5150~5250 MHz	5725~5850 MHz
1	WAN8010F245M05	Chip	N/A	3.45	--	--
2	ACM3-5036-A1-CC-S	Chip	N/A	3	3.3	3.3
3	8619 replacement antenna	Dipole	N/A	3.48	3.49	3.17

Note1: Ant 1 and 3 are used for 2.4 GHz transmission.

Note2: Ant 2 and 3 are used for 5 GHz transmission.

#### 1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	AC 110~120V, 60Hz, 7A
-------------------	-----------------------

#### 1.1.4 Accessories

N/A

### 1.1.5 Channel List

Frequency band (MHz)		2400~2483.5	
802.11 b / g / n HT20		802.11n HT40	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	3	2422
2	2417	4	2427
3	2422	5	2432
4	2427	6	2437
5	2432	7	2442
6	2437	8	2447
7	2442	9	2452
8	2447	---	---
9	2452	---	---
10	2457	---	---
11	2462	---	---

### 1.1.6 Test Tool and Duty Cycle

Test Tool	MP_TEST, V1.3.8.0		
Duty Cycle and Duty Factor	Mode	Duty cycle (%)	Duty factor (dB)
	11b	98.99%	0.04
	11g	98.15%	0.08
	HT20	98.02%	0.09
	HT40	87.74%	0.57


### 1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)	Power Set
11b	2412	63/53
11b	2437	63/52
11b	2462	63/52
11g	2412	57/45
11g	2437	57/44
11g	2462	57/44
HT20	2412	56/44
HT20	2437	55/42
HT20	2462	55/42
HT40	2422	57/46
HT40	2437	57/45
HT40	2452	57/44

### 1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Signal cable / Length (m)
1	Notebook	DELL	Latitude E6430	DoC	RJ45, 10m non-shielded.
2	700W Light bulb load	ICC	---	---	---

### 1.3 Test Setup Chart



## 1.4 The Equipment List

<b>Test Item</b>	Conducted Emission				
<b>Test Site</b>	Conduction room 1 / (CO01-WS)				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
EMC Receiver	R&S	ESCS 30	100169	Oct. 21, 2015	Oct. 20, 2016
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 13, 2015	Nov. 12, 2016
RF Cable-CON	EMC	EMCCFD300-BM-BM-6000	50821	Dec. 21, 2015	Dec. 20, 2016
Measurement Software	AUDIX	e3	6.120210k	NA	NA

Note: Calibration Interval of instruments listed above is one year.

<b>Test Item</b>	Radiated Emission				
<b>Test Site</b>	966 chamber 2 / (03CH02-WS)				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
Spectrum Analyzer	R&S	FSV40	101499	Dec. 17, 2015	Dec. 16, 2016
Receiver	R&S	ESR3	101657	Jan. 12, 2016	Jan. 11, 2017
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-523	Nov. 09, 2015	Nov. 08, 2016
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1095	Oct. 07, 2015	Oct. 06, 2016
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 04, 2015	Nov. 03, 2016
Loop Antenna	R&S	HFH2-Z2	11900	Nov. 16, 2015	Nov. 15, 2016
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 10, 2015	Dec. 09, 2016
Preamplifier	Burgeon	BPA-530	100218	Nov. 03, 2015	Nov. 02, 2016
Preamplifier	Agilent	83017A	MY39501309	Sep. 22, 2015	Sep. 21, 2016
Preamplifier	EMC	EMC184045B	980192	Sep. 01, 2015	Aug. 31, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16140/4	Dec. 10, 2015	Dec. 09, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16018/4	Dec. 10, 2015	Dec. 09, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16015/4	Dec. 10, 2015	Dec. 09, 2016
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-003	Dec. 10, 2015	Dec. 09, 2016
LF cable 10M	EMCC	CFD400-E	CFD400-001	Dec. 10, 2015	Dec. 09, 2016
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

<b>Test Item</b>	RF Conducted				
<b>Test Site</b>	(TH01-WS)				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
Spectrum Analyzer	R&S	FSV40	101063	Feb. 03, 2015	Feb. 02, 2016
Power Meter	Anritsu	ML2495A	1241002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor	Anritsu	MA2411B	1207366	Sep. 21, 2015	Sep. 20, 2016
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA

Note: Calibration Interval of instruments listed above is one year.

## 1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2013

FCC KDB 558074 D01 DTS Meas Guidance v03r04

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

## 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±34.134 Hz
Conducted power	±0.808 dB
Power density	±0.463 dB
Conducted emission	±2.670 dB
AC conducted emission	±2.90 dB
Radiated emission ≤ 1GHz	±3.87 dB
Radiated emission > 1GHz	±5.60 dB

## 2 Test Configuration

### 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	18°C / 59%	Sky Huang
Radiated Emissions	03CH01-WS	20°C / 65%	Aska Huang
RF Conducted	TH01-WS	21°C / 64%	Alex Huang

➤ FCC site registration No.: 657002

➤ IC site registration No.: 10807A-2

### 2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
Conducted Emissions	11b	2462	1 Mbps	---
Radiated Emissions ≤1GHz	11b	2462	1 Mbps	---
Radiated Emissions >1GHz				
Maximum Output Power	11b 11g	2412 / 2437 / 2462	1 Mbps	
6dB bandwidth	HT20	2412 / 2437 / 2462	6 Mbps	
Power spectral density	HT40	2422 / 2437 / 2452	MCS 0	
			MCS 0	---

**NOTE:**

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Z-plane** results were found as the worst case and were shown in this report.

## 3 Transmitter Test Results

### 3.1 Conducted Emissions

#### 3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.

#### 3.1.2 Test Procedures


1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V / 60Hz.


#### 3.1.3 Test Setup



Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

### 3.1.4 Test Result of Conducted Emissions





## 3.2 6dB and Occupied Bandwidth

### 3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

### 3.2.2 Test Procedures


#### 6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

#### Occupied Bandwidth


1. Set resolution bandwidth (RBW) = 1 MHz, Video bandwidth = 3 MHz.
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

### 3.2.3 Test Setup




### 3.2.4 Test Result of 6dB and Occupied Bandwidth

Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	6dB Bandwidth (MHz)				Limit (kHz)
			Chain 0	Chain 1	Chain 2	Chain 3	
11b	2	2412	10.03	9.57	---	---	500
11b	2	2437	10.09	10.03	---	---	500
11b	2	2462	10.03	10.03	---	---	500
11g	2	2412	16.35	16.35	---	---	500
11g	2	2437	16.35	16.35	---	---	500
11g	2	2462	16.35	16.35	---	---	500
HT20	2	2412	17.57	17.22	---	---	500
HT20	2	2437	17.62	17.62	---	---	500
HT20	2	2462	17.62	17.57	---	---	500
HT40	2	2422	35.36	35.48	---	---	500
HT40	2	2437	35.36	35.36	---	---	500
HT40	2	2452	35.59	35.36	---	---	500



Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	99% Occupied Bandwidth (MHz)			
			Chain 0	Chain 1	Chain 2	Chain 3
11b	2	2412	15.84	15.48	---	---
11b	2	2437	15.87	15.41	---	---
11b	2	2462	15.74	15.45	---	---
11g	2	2412	16.93	16.86	---	---
11g	2	2437	16.95	16.87	---	---
11g	2	2462	16.93	16.87	---	---
HT20	2	2412	18.03	18.06	---	---
HT20	2	2437	18.04	18.04	---	---
HT20	2	2462	18.02	18.07	---	---
HT40	2	2422	36.34	36.42	---	---
HT40	2	2437	36.30	36.42	---	---
HT40	2	2452	36.32	36.42	---	---



### 3.3 RF Output Power

#### 3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.

- Antenna gain <= 6dBi, no any corresponding reduction is in output power limit.
- Antenna gain > 6dBi
  - Non Fixed, point to point operations.  
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB
  - Fixed, point to point operations  
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.  
Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

#### 3.3.2 Test Procedures

- Maximum Peak Conducted Output Power
  - Spectrum analyzer**
    1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
    2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
    3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.
  - Power meter**
    1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- Maximum Conducted Output Power ( For reference only )
  - Power meter**
    1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

#### 3.3.3 Test Setup



### 3.3.4 Test Result of Maximum Output Power

Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Conducted Average Output Power (dBm)							Ant. Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3	Total Power (mW)	Total Power (dBm)	Limit (dBm)			
11b	2	2412	24.44	24.35	---	---	550.241	27.41	30.00	3.48	30.89	36.00
11b	2	2437	24.56	24.29	---	---	554.293	27.44	30.00	3.48	30.92	36.00
11b	2	2462	24.26	24.78	---	---	567.293	<b>27.54</b>	30.00	3.48	31.02	36.00
11g	2	2412	19.19	19.39	---	---	169.881	22.30	30.00	3.48	25.78	36.00
11g	2	2437	19.17	19.02	---	---	162.403	22.11	30.00	3.48	25.59	36.00
11g	2	2462	19.74	19.56	---	---	184.554	22.66	30.00	3.48	26.14	36.00
HT20	2	2412	18.58	18.28	---	---	139.408	21.44	30.00	3.48	24.92	36.00
HT20	2	2437	18.43	18.38	---	---	138.528	21.42	30.00	3.48	24.90	36.00
HT20	2	2462	18.6	18.74	---	---	147.261	21.68	30.00	3.48	25.16	36.00
HT40	2	2422	18.27	18.41	---	---	136.485	21.35	30.00	3.48	24.83	36.00
HT40	2	2437	18.24	18.42	---	---	136.183	21.34	30.00	3.48	24.82	36.00
HT40	2	2452	18.32	18.23	---	---	134.448	21.29	30.00	3.48	24.77	36.00

Note: Conducted average output power is for reference only.

## 3.4 Power Spectral Density


### 3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

### 3.4.2 Test Procedures

- Method PKPSD
  1. Set the RBW = 3kHz, VBW = 10kHz.
  2. Detector = Peak, Sweep time = auto couple.
  3. Trace mode = max hold, allow trace to fully stabilize.
  4. Use the peak marker function to determine the maximum amplitude level.
- Method AVGSA-1 (802.11b/g/ n HT20)
  1. Set the RBW = 30kHz, VBW = 100 kHz.
  2. Detector = RMS, Sweep time = auto couple.
  3. Employ trace averaging (RMS) mode over a minimum of 100 traces.
  4. Use the peak marker function to determine the maximum amplitude level.
- Method AVGSA-2 (802.11n HT40)
  1. Set the RBW = 30kHz, VBW = 100 kHz.
  2. Detector = RMS, Sweep time = auto couple.
  3. Employ trace averaging (RMS) mode over a minimum of 100 traces
  4. Use the peak marker function to determine the maximum amplitude level.
  5. Add  $10\log(1/x)$ , where X is the duty cycle.


### 3.4.3 Test Setup



### 3.4.4 Test Result of Power Spectral Density

Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
11b	2	2412	4.29	8.00
11b	2	2437	4.34	8.00
11b	2	2462	4.00	8.00
11g	2	2412	-2.82	8.00
11g	2	2437	-2.80	8.00
11g	2	2462	-2.84	8.00
HT20	2	2412	-3.74	8.00
HT20	2	2437	-4.04	8.00
HT20	2	2462	-4.03	8.00
HT40	2	2422	-6.67	8.00
HT40	2	2437	-6.68	8.00
HT40	2	2452	-6.89	8.00

Note: Test result is bin-by-bin summing measured value of each TX port.



## 3.5 Unwanted Emissions into Restricted Frequency Bands

### 3.5.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

**Note 1:**  
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

**Note 2:**  
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

### 3.5.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

### 3.5.3 Test Setup


#### Radiated Emissions below 1 GHz




#### Radiated Emissions above 1 GHz



### 3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	11b	Test Freq. (MHz)	2462																																																																						
Polarization	Horizontal																																																																								
																																																																									
<table border="1"> <thead> <tr> <th></th> <th>Freq. MHz</th> <th>Emission level dBuV/m</th> <th>Limit dBuV/m</th> <th>Margin dB</th> <th>SA reading dBuV</th> <th>Factor dB</th> <th>Remark</th> <th>ANT High cm</th> <th>Turn Table deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>250.05</td> <td>42.84</td> <td>46.00</td> <td>-3.16</td> <td>55.61</td> <td>-12.77</td> <td>QP</td> <td>122</td> <td>254</td> </tr> <tr> <td>2</td> <td>375.32</td> <td>42.37</td> <td>46.00</td> <td>-3.63</td> <td>51.70</td> <td>-9.33</td> <td>Peak</td> <td>---</td> <td>---</td> </tr> <tr> <td>3</td> <td>500.04</td> <td>44.96</td> <td>46.00</td> <td>-1.04</td> <td>51.47</td> <td>-6.51</td> <td>QP</td> <td>193</td> <td>205</td> </tr> <tr> <td>4</td> <td>625.03</td> <td>44.86</td> <td>46.00</td> <td>-1.14</td> <td>49.14</td> <td>-4.28</td> <td>QP</td> <td>132</td> <td>224</td> </tr> <tr> <td>5</td> <td>750.71</td> <td>42.44</td> <td>46.00</td> <td>-3.56</td> <td>44.80</td> <td>-2.36</td> <td>Peak</td> <td>---</td> <td>---</td> </tr> <tr> <td>6</td> <td>875.05</td> <td>44.68</td> <td>46.00</td> <td>-1.32</td> <td>45.60</td> <td>-0.92</td> <td>QP</td> <td>157</td> <td>206</td> </tr> </tbody> </table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	250.05	42.84	46.00	-3.16	55.61	-12.77	QP	122	254	2	375.32	42.37	46.00	-3.63	51.70	-9.33	Peak	---	---	3	500.04	44.96	46.00	-1.04	51.47	-6.51	QP	193	205	4	625.03	44.86	46.00	-1.14	49.14	-4.28	QP	132	224	5	750.71	42.44	46.00	-3.56	44.80	-2.36	Peak	---	---	6	875.05	44.68	46.00	-1.32	45.60	-0.92	QP	157	206
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																
1	250.05	42.84	46.00	-3.16	55.61	-12.77	QP	122	254																																																																
2	375.32	42.37	46.00	-3.63	51.70	-9.33	Peak	---	---																																																																
3	500.04	44.96	46.00	-1.04	51.47	-6.51	QP	193	205																																																																
4	625.03	44.86	46.00	-1.14	49.14	-4.28	QP	132	224																																																																
5	750.71	42.44	46.00	-3.56	44.80	-2.36	Peak	---	---																																																																
6	875.05	44.68	46.00	-1.32	45.60	-0.92	QP	157	206																																																																
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)</p> <p>*Factor includes antenna factor, cable loss and amplifier gain</p> <p>Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p> <p>Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.</p>																																																																									



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

### 3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11b


Modulation	11b	Test Freq. (MHz)	2412																																																																												
Polarization	Horizontal																																																																														
<p>Graph showing Level (dBuV/m) vs Frequency (MHz). The Y-axis ranges from 0 to 90 dBuV/m, and the X-axis ranges from 1000 to 25000 MHz. Six data points are plotted: 1 (2390.00 MHz, 38.08 dBuV/m), 2 (2390.00 MHz, 54.56 dBuV/m), 3 (4824.00 MHz, 52.48 dBuV/m), 4 (4824.00 MHz, 55.94 dBuV/m), 5 (12060.00 MHz, 42.38 dBuV/m), and 6 (12060.00 MHz, 55.29 dBuV/m). Two horizontal lines are shown: FCC CLASS-B (74 dBuV/m) and FCC CLASS-B (AVG) (55 dBuV/m).</p>																																																																															
<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission Limit</th> <th>Margin</th> <th>SA</th> <th>Factor</th> <th>Remark</th> <th>ANT</th> <th>Turn</th> </tr> <tr> <th>MHz</th> <th>level</th> <th>level</th> <th>reading</th> <th>reading</th> <th></th> <th>High</th> <th>Table</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>38.08</td> <td>54.00</td> <td>-15.92</td> <td>41.14</td> <td>-3.06</td> <td>Average</td> <td>278</td> <td>34</td> </tr> <tr> <td>2</td> <td>2390.00</td> <td>54.56</td> <td>74.00</td> <td>-19.44</td> <td>57.62</td> <td>-3.06</td> <td>Peak</td> <td>278</td> <td>34</td> </tr> <tr> <td>3</td> <td>4824.00</td> <td>52.48</td> <td>54.00</td> <td>-1.52</td> <td>48.22</td> <td>4.26</td> <td>Average</td> <td>243</td> <td>62</td> </tr> <tr> <td>4</td> <td>4824.00</td> <td>55.94</td> <td>74.00</td> <td>-18.06</td> <td>51.68</td> <td>4.26</td> <td>Peak</td> <td>243</td> <td>62</td> </tr> <tr> <td>5</td> <td>12060.00</td> <td>42.38</td> <td>54.00</td> <td>-11.62</td> <td>28.53</td> <td>13.85</td> <td>Average</td> <td>275</td> <td>153</td> </tr> <tr> <td>6</td> <td>12060.00</td> <td>55.29</td> <td>74.00</td> <td>-18.71</td> <td>41.44</td> <td>13.85</td> <td>Peak</td> <td>275</td> <td>153</td> </tr> </tbody> </table>				Freq.	Emission Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	level	reading	reading		High	Table	1	2390.00	38.08	54.00	-15.92	41.14	-3.06	Average	278	34	2	2390.00	54.56	74.00	-19.44	57.62	-3.06	Peak	278	34	3	4824.00	52.48	54.00	-1.52	48.22	4.26	Average	243	62	4	4824.00	55.94	74.00	-18.06	51.68	4.26	Peak	243	62	5	12060.00	42.38	54.00	-11.62	28.53	13.85	Average	275	153	6	12060.00	55.29	74.00	-18.71	41.44	13.85	Peak	275	153
Freq.	Emission Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																								
MHz	level	level	reading	reading		High	Table																																																																								
1	2390.00	38.08	54.00	-15.92	41.14	-3.06	Average	278	34																																																																						
2	2390.00	54.56	74.00	-19.44	57.62	-3.06	Peak	278	34																																																																						
3	4824.00	52.48	54.00	-1.52	48.22	4.26	Average	243	62																																																																						
4	4824.00	55.94	74.00	-18.06	51.68	4.26	Peak	243	62																																																																						
5	12060.00	42.38	54.00	-11.62	28.53	13.85	Average	275	153																																																																						
6	12060.00	55.29	74.00	-18.71	41.44	13.85	Peak	275	153																																																																						
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																																															





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).






<b>Modulation</b>	11b	<b>Test Freq. (MHz)</b>	2462																																																																														
<b>Polarization</b>	Horizontal																																																																																
																																																																																	
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Freq.</th> <th style="text-align: left;">Emission</th> <th style="text-align: left;">Limit</th> <th style="text-align: left;">Margin</th> <th style="text-align: left;">SA</th> <th style="text-align: left;">Factor</th> <th style="text-align: left;">Remark</th> <th style="text-align: left;">ANT</th> <th style="text-align: left;">Turn</th> </tr> <tr> <th style="text-align: left;">MHz</th> <th style="text-align: left;">level</th> <th style="text-align: left;">dBuV/m</th> <th style="text-align: left;">dB</th> <th style="text-align: left;">reading</th> <th style="text-align: left;">dB</th> <th></th> <th style="text-align: left;">High</th> <th style="text-align: left;">Table</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2483.50</td> <td>38.53</td> <td>54.00</td> <td>-15.47</td> <td>41.22</td> <td>-2.69</td> <td>Average</td> <td>330</td> <td>14</td> </tr> <tr> <td>2</td> <td>2483.50</td> <td>58.58</td> <td>74.00</td> <td>-15.42</td> <td>61.27</td> <td>-2.69</td> <td>Peak</td> <td>330</td> <td>14</td> </tr> <tr> <td>3</td> <td>4924.00</td> <td>50.36</td> <td>54.00</td> <td>-3.64</td> <td>45.83</td> <td>4.53</td> <td>Average</td> <td>244</td> <td>64</td> </tr> <tr> <td>4</td> <td>4924.00</td> <td>53.91</td> <td>74.00</td> <td>-20.09</td> <td>49.38</td> <td>4.53</td> <td>Peak</td> <td>244</td> <td>64</td> </tr> <tr> <td>5</td> <td>7386.00</td> <td>43.24</td> <td>54.00</td> <td>-10.76</td> <td>33.85</td> <td>9.39</td> <td>Average</td> <td>394</td> <td>55</td> </tr> <tr> <td>6</td> <td>7386.00</td> <td>53.91</td> <td>74.00</td> <td>-20.09</td> <td>44.52</td> <td>9.39</td> <td>Peak</td> <td>394</td> <td>55</td> </tr> </tbody> </table>				Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	dBuV/m	dB	reading	dB		High	Table	1	2483.50	38.53	54.00	-15.47	41.22	-2.69	Average	330	14	2	2483.50	58.58	74.00	-15.42	61.27	-2.69	Peak	330	14	3	4924.00	50.36	54.00	-3.64	45.83	4.53	Average	244	64	4	4924.00	53.91	74.00	-20.09	49.38	4.53	Peak	244	64	5	7386.00	43.24	54.00	-10.76	33.85	9.39	Average	394	55	6	7386.00	53.91	74.00	-20.09	44.52	9.39	Peak	394	55
Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																									
MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																									
1	2483.50	38.53	54.00	-15.47	41.22	-2.69	Average	330	14																																																																								
2	2483.50	58.58	74.00	-15.42	61.27	-2.69	Peak	330	14																																																																								
3	4924.00	50.36	54.00	-3.64	45.83	4.53	Average	244	64																																																																								
4	4924.00	53.91	74.00	-20.09	49.38	4.53	Peak	244	64																																																																								
5	7386.00	43.24	54.00	-10.76	33.85	9.39	Average	394	55																																																																								
6	7386.00	53.91	74.00	-20.09	44.52	9.39	Peak	394	55																																																																								

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11b	<b>Test Freq. (MHz)</b>	2462																																																																														
<b>Polarization</b>	Vertical																																																																																
																																																																																	
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Freq.</th> <th style="text-align: left;">Emission</th> <th style="text-align: left;">Limit</th> <th style="text-align: left;">Margin</th> <th style="text-align: left;">SA</th> <th style="text-align: left;">Factor</th> <th style="text-align: left;">Remark</th> <th style="text-align: left;">ANT</th> <th style="text-align: left;">Turn</th> </tr> <tr> <th style="text-align: left;">MHz</th> <th style="text-align: left;">level</th> <th style="text-align: left;">dBuV/m</th> <th style="text-align: left;">dB</th> <th style="text-align: left;">reading</th> <th style="text-align: left;">dB</th> <th></th> <th style="text-align: left;">High</th> <th style="text-align: left;">Table</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2483.50</td> <td>46.60</td> <td>54.00</td> <td>-7.40</td> <td>49.29</td> <td>-2.69</td> <td>Average</td> <td>271</td> <td>14</td> </tr> <tr> <td>2</td> <td>2483.50</td> <td>70.59</td> <td>74.00</td> <td>-3.41</td> <td>73.28</td> <td>-2.69</td> <td>Peak</td> <td>271</td> <td>14</td> </tr> <tr> <td>3</td> <td>4924.00</td> <td>52.87</td> <td>54.00</td> <td>-1.13</td> <td>48.34</td> <td>4.53</td> <td>Average</td> <td>269</td> <td>52</td> </tr> <tr> <td>4</td> <td>4924.00</td> <td>56.97</td> <td>74.00</td> <td>-17.03</td> <td>52.44</td> <td>4.53</td> <td>Peak</td> <td>269</td> <td>52</td> </tr> <tr> <td>5</td> <td>7386.00</td> <td>49.92</td> <td>54.00</td> <td>-4.08</td> <td>40.53</td> <td>9.39</td> <td>Average</td> <td>231</td> <td>37</td> </tr> <tr> <td>6</td> <td>7386.00</td> <td>58.31</td> <td>74.00</td> <td>-15.69</td> <td>48.92</td> <td>9.39</td> <td>Peak</td> <td>231</td> <td>37</td> </tr> </tbody> </table>				Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	dBuV/m	dB	reading	dB		High	Table	1	2483.50	46.60	54.00	-7.40	49.29	-2.69	Average	271	14	2	2483.50	70.59	74.00	-3.41	73.28	-2.69	Peak	271	14	3	4924.00	52.87	54.00	-1.13	48.34	4.53	Average	269	52	4	4924.00	56.97	74.00	-17.03	52.44	4.53	Peak	269	52	5	7386.00	49.92	54.00	-4.08	40.53	9.39	Average	231	37	6	7386.00	58.31	74.00	-15.69	48.92	9.39	Peak	231	37
Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																									
MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																									
1	2483.50	46.60	54.00	-7.40	49.29	-2.69	Average	271	14																																																																								
2	2483.50	70.59	74.00	-3.41	73.28	-2.69	Peak	271	14																																																																								
3	4924.00	52.87	54.00	-1.13	48.34	4.53	Average	269	52																																																																								
4	4924.00	56.97	74.00	-17.03	52.44	4.53	Peak	269	52																																																																								
5	7386.00	49.92	54.00	-4.08	40.53	9.39	Average	231	37																																																																								
6	7386.00	58.31	74.00	-15.69	48.92	9.39	Peak	231	37																																																																								


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

### 3.5.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11g


Modulation	11g	Test Freq. (MHz)	2412																																																																												
Polarization	Horizontal																																																																														
<p>Graph showing Level (dBuV/m) vs Frequency (MHz). The Y-axis ranges from 0 to 90 dBuV/m, and the X-axis ranges from 1000 to 25000 MHz. Six data points are plotted: 1 (2390.00 MHz, 37.71 dBuV/m), 2 (2390.00 MHz, 50.46 dBuV/m), 3 (4824.00 MHz, 34.40 dBuV/m), 4 (4824.00 MHz, 46.97 dBuV/m), 5 (12060.00 MHz, 42.90 dBuV/m), and 6 (12060.00 MHz, 55.21 dBuV/m). Two horizontal lines are shown: FCC CLASS-B (70 dBuV/m) and FCC CLASS-B (AVG) (54 dBuV/m).</p>																																																																															
<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission Limit</th> <th>Margin</th> <th>SA</th> <th>Factor</th> <th>Remark</th> <th>ANT</th> <th>Turn</th> </tr> <tr> <th>MHz</th> <th>level</th> <th>level</th> <th>reading</th> <th>reading</th> <th></th> <th>High</th> <th>Table</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>37.71</td> <td>54.00</td> <td>-16.29</td> <td>40.77</td> <td>-3.06</td> <td>Average</td> <td>345</td> <td>37</td> </tr> <tr> <td>2</td> <td>2390.00</td> <td>50.46</td> <td>74.00</td> <td>-23.54</td> <td>53.52</td> <td>-3.06</td> <td>Peak</td> <td>345</td> <td>37</td> </tr> <tr> <td>3</td> <td>4824.00</td> <td>34.40</td> <td>54.00</td> <td>-19.60</td> <td>30.14</td> <td>4.26</td> <td>Average</td> <td>244</td> <td>69</td> </tr> <tr> <td>4</td> <td>4824.00</td> <td>46.97</td> <td>74.00</td> <td>-27.03</td> <td>42.71</td> <td>4.26</td> <td>Peak</td> <td>244</td> <td>69</td> </tr> <tr> <td>5</td> <td>12060.00</td> <td>42.90</td> <td>54.00</td> <td>-11.10</td> <td>29.05</td> <td>13.85</td> <td>Average</td> <td>165</td> <td>21</td> </tr> <tr> <td>6</td> <td>12060.00</td> <td>55.21</td> <td>74.00</td> <td>-18.79</td> <td>41.36</td> <td>13.85</td> <td>Peak</td> <td>165</td> <td>21</td> </tr> </tbody> </table>				Freq.	Emission Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	level	reading	reading		High	Table	1	2390.00	37.71	54.00	-16.29	40.77	-3.06	Average	345	37	2	2390.00	50.46	74.00	-23.54	53.52	-3.06	Peak	345	37	3	4824.00	34.40	54.00	-19.60	30.14	4.26	Average	244	69	4	4824.00	46.97	74.00	-27.03	42.71	4.26	Peak	244	69	5	12060.00	42.90	54.00	-11.10	29.05	13.85	Average	165	21	6	12060.00	55.21	74.00	-18.79	41.36	13.85	Peak	165	21
Freq.	Emission Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																								
MHz	level	level	reading	reading		High	Table																																																																								
1	2390.00	37.71	54.00	-16.29	40.77	-3.06	Average	345	37																																																																						
2	2390.00	50.46	74.00	-23.54	53.52	-3.06	Peak	345	37																																																																						
3	4824.00	34.40	54.00	-19.60	30.14	4.26	Average	244	69																																																																						
4	4824.00	46.97	74.00	-27.03	42.71	4.26	Peak	244	69																																																																						
5	12060.00	42.90	54.00	-11.10	29.05	13.85	Average	165	21																																																																						
6	12060.00	55.21	74.00	-18.79	41.36	13.85	Peak	165	21																																																																						
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)</p> <p>*Factor includes antenna factor, cable loss and amplifier gain</p> <p>Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>																																																																															




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

### 3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20


Modulation	HT20	Test Freq. (MHz)	2412																																																																												
Polarization	Horizontal																																																																														
																																																																															
<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission Limit</th> <th>Margin</th> <th>SA</th> <th>Factor</th> <th>Remark</th> <th>ANT</th> <th>Turn</th> </tr> <tr> <th>MHz</th> <th>level</th> <th>dBuV/m</th> <th>reading</th> <th>dBuV</th> <th></th> <th>High</th> <th>Table</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>37.47</td> <td>54.00</td> <td>-16.53</td> <td>40.53</td> <td>-3.06</td> <td>Average</td> <td>345</td> <td>35</td> </tr> <tr> <td>2</td> <td>2390.00</td> <td>50.42</td> <td>74.00</td> <td>-23.58</td> <td>53.48</td> <td>-3.06</td> <td>Peak</td> <td>345</td> <td>35</td> </tr> <tr> <td>3</td> <td>4824.00</td> <td>33.82</td> <td>54.00</td> <td>-20.18</td> <td>29.56</td> <td>4.26</td> <td>Average</td> <td>241</td> <td>68</td> </tr> <tr> <td>4</td> <td>4824.00</td> <td>46.79</td> <td>74.00</td> <td>-27.21</td> <td>42.53</td> <td>4.26</td> <td>Peak</td> <td>241</td> <td>68</td> </tr> <tr> <td>5</td> <td>12060.00</td> <td>42.51</td> <td>54.00</td> <td>-11.49</td> <td>28.66</td> <td>13.85</td> <td>Average</td> <td>160</td> <td>20</td> </tr> <tr> <td>6</td> <td>12060.00</td> <td>54.87</td> <td>74.00</td> <td>-19.13</td> <td>41.02</td> <td>13.85</td> <td>Peak</td> <td>160</td> <td>20</td> </tr> </tbody> </table>				Freq.	Emission Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	dBuV/m	reading	dBuV		High	Table	1	2390.00	37.47	54.00	-16.53	40.53	-3.06	Average	345	35	2	2390.00	50.42	74.00	-23.58	53.48	-3.06	Peak	345	35	3	4824.00	33.82	54.00	-20.18	29.56	4.26	Average	241	68	4	4824.00	46.79	74.00	-27.21	42.53	4.26	Peak	241	68	5	12060.00	42.51	54.00	-11.49	28.66	13.85	Average	160	20	6	12060.00	54.87	74.00	-19.13	41.02	13.85	Peak	160	20
Freq.	Emission Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																								
MHz	level	dBuV/m	reading	dBuV		High	Table																																																																								
1	2390.00	37.47	54.00	-16.53	40.53	-3.06	Average	345	35																																																																						
2	2390.00	50.42	74.00	-23.58	53.48	-3.06	Peak	345	35																																																																						
3	4824.00	33.82	54.00	-20.18	29.56	4.26	Average	241	68																																																																						
4	4824.00	46.79	74.00	-27.21	42.53	4.26	Peak	241	68																																																																						
5	12060.00	42.51	54.00	-11.49	28.66	13.85	Average	160	20																																																																						
6	12060.00	54.87	74.00	-19.13	41.02	13.85	Peak	160	20																																																																						
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																																															



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


<b>Modulation</b>	HT20	<b>Test Freq. (MHz)</b>	2437																																																																																																		
<b>Polarization</b>	Horizontal																																																																																																				
																																																																																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Freq.</th> <th style="text-align: left;">Emission</th> <th style="text-align: left;">Limit</th> <th style="text-align: left;">Margin</th> <th style="text-align: left;">SA</th> <th style="text-align: left;">Factor</th> <th style="text-align: left;">Remark</th> <th style="text-align: left;">ANT</th> <th style="text-align: left;">Turn</th> </tr> <tr> <th style="text-align: left;">MHz</th> <th style="text-align: left;">level</th> <th style="text-align: left;">dBuV/m</th> <th style="text-align: left;">dB</th> <th style="text-align: left;">reading</th> <th style="text-align: left;">dB</th> <th></th> <th style="text-align: left;">High</th> <th style="text-align: left;">Table</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>37.29</td> <td>54.00</td> <td>-16.71</td> <td>40.35</td> <td>-3.06</td> <td>Average</td> <td>330</td> <td>30</td> </tr> <tr> <td>2</td> <td>2390.00</td> <td>50.39</td> <td>74.00</td> <td>-23.61</td> <td>53.45</td> <td>-3.06</td> <td>Peak</td> <td>330</td> <td>30</td> </tr> <tr> <td>3</td> <td>2483.50</td> <td>37.58</td> <td>54.00</td> <td>-16.42</td> <td>40.27</td> <td>-2.69</td> <td>Average</td> <td>330</td> <td>30</td> </tr> <tr> <td>4</td> <td>2483.50</td> <td>50.52</td> <td>74.00</td> <td>-23.48</td> <td>53.21</td> <td>-2.69</td> <td>Peak</td> <td>330</td> <td>30</td> </tr> <tr> <td>5</td> <td>4874.00</td> <td>33.81</td> <td>54.00</td> <td>-20.19</td> <td>29.41</td> <td>4.40</td> <td>Average</td> <td>240</td> <td>56</td> </tr> <tr> <td>6</td> <td>4874.00</td> <td>46.71</td> <td>74.00</td> <td>-27.29</td> <td>42.31</td> <td>4.40</td> <td>Peak</td> <td>240</td> <td>56</td> </tr> <tr> <td>7</td> <td>7311.00</td> <td>37.33</td> <td>54.00</td> <td>-16.67</td> <td>28.12</td> <td>9.21</td> <td>Average</td> <td>370</td> <td>49</td> </tr> <tr> <td>8</td> <td>7311.00</td> <td>50.49</td> <td>74.00</td> <td>-23.51</td> <td>41.28</td> <td>9.21</td> <td>Peak</td> <td>370</td> <td>49</td> </tr> </tbody> </table>				Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	dBuV/m	dB	reading	dB		High	Table	1	2390.00	37.29	54.00	-16.71	40.35	-3.06	Average	330	30	2	2390.00	50.39	74.00	-23.61	53.45	-3.06	Peak	330	30	3	2483.50	37.58	54.00	-16.42	40.27	-2.69	Average	330	30	4	2483.50	50.52	74.00	-23.48	53.21	-2.69	Peak	330	30	5	4874.00	33.81	54.00	-20.19	29.41	4.40	Average	240	56	6	4874.00	46.71	74.00	-27.29	42.31	4.40	Peak	240	56	7	7311.00	37.33	54.00	-16.67	28.12	9.21	Average	370	49	8	7311.00	50.49	74.00	-23.51	41.28	9.21	Peak	370	49
Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																													
MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																																													
1	2390.00	37.29	54.00	-16.71	40.35	-3.06	Average	330	30																																																																																												
2	2390.00	50.39	74.00	-23.61	53.45	-3.06	Peak	330	30																																																																																												
3	2483.50	37.58	54.00	-16.42	40.27	-2.69	Average	330	30																																																																																												
4	2483.50	50.52	74.00	-23.48	53.21	-2.69	Peak	330	30																																																																																												
5	4874.00	33.81	54.00	-20.19	29.41	4.40	Average	240	56																																																																																												
6	4874.00	46.71	74.00	-27.29	42.31	4.40	Peak	240	56																																																																																												
7	7311.00	37.33	54.00	-16.67	28.12	9.21	Average	370	49																																																																																												
8	7311.00	50.49	74.00	-23.51	41.28	9.21	Peak	370	49																																																																																												

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

### 3.5.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT40


Modulation	HT40	Test Freq. (MHz)	2422																																																																												
Polarization	Horizontal																																																																														
																																																																															
<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission Limit</th> <th>Margin</th> <th>SA</th> <th>Factor</th> <th>Remark</th> <th>ANT</th> <th>Turn</th> </tr> <tr> <th>MHz</th> <th>level</th> <th>level</th> <th>reading</th> <th>reading</th> <th></th> <th>High</th> <th>Table</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>37.85</td> <td>54.00</td> <td>-16.15</td> <td>40.91</td> <td>-3.06</td> <td>Average</td> <td>341</td> <td>29</td> </tr> <tr> <td>2</td> <td>2390.00</td> <td>49.65</td> <td>74.00</td> <td>-24.35</td> <td>52.71</td> <td>-3.06</td> <td>Peak</td> <td>341</td> <td>29</td> </tr> <tr> <td>3</td> <td>4844.00</td> <td>32.66</td> <td>54.00</td> <td>-21.34</td> <td>28.34</td> <td>4.32</td> <td>Average</td> <td>265</td> <td>48</td> </tr> <tr> <td>4</td> <td>4844.00</td> <td>45.79</td> <td>74.00</td> <td>-28.21</td> <td>41.47</td> <td>4.32</td> <td>Peak</td> <td>265</td> <td>48</td> </tr> <tr> <td>5</td> <td>7266.00</td> <td>37.42</td> <td>54.00</td> <td>-16.58</td> <td>28.31</td> <td>9.11</td> <td>Average</td> <td>243</td> <td>72</td> </tr> <tr> <td>6</td> <td>7266.00</td> <td>50.60</td> <td>74.00</td> <td>-23.40</td> <td>41.49</td> <td>9.11</td> <td>Peak</td> <td>243</td> <td>72</td> </tr> </tbody> </table>				Freq.	Emission Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	level	reading	reading		High	Table	1	2390.00	37.85	54.00	-16.15	40.91	-3.06	Average	341	29	2	2390.00	49.65	74.00	-24.35	52.71	-3.06	Peak	341	29	3	4844.00	32.66	54.00	-21.34	28.34	4.32	Average	265	48	4	4844.00	45.79	74.00	-28.21	41.47	4.32	Peak	265	48	5	7266.00	37.42	54.00	-16.58	28.31	9.11	Average	243	72	6	7266.00	50.60	74.00	-23.40	41.49	9.11	Peak	243	72
Freq.	Emission Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																								
MHz	level	level	reading	reading		High	Table																																																																								
1	2390.00	37.85	54.00	-16.15	40.91	-3.06	Average	341	29																																																																						
2	2390.00	49.65	74.00	-24.35	52.71	-3.06	Peak	341	29																																																																						
3	4844.00	32.66	54.00	-21.34	28.34	4.32	Average	265	48																																																																						
4	4844.00	45.79	74.00	-28.21	41.47	4.32	Peak	265	48																																																																						
5	7266.00	37.42	54.00	-16.58	28.31	9.11	Average	243	72																																																																						
6	7266.00	50.60	74.00	-23.40	41.49	9.11	Peak	243	72																																																																						
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																																															



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT40	<b>Test Freq. (MHz)</b>	2452																																																																														
<b>Polarization</b>	Horizontal																																																																																
																																																																																	
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Freq.</th> <th style="text-align: left;">Emission</th> <th style="text-align: left;">Limit</th> <th style="text-align: left;">Margin</th> <th style="text-align: left;">SA</th> <th style="text-align: left;">Factor</th> <th style="text-align: left;">Remark</th> <th style="text-align: left;">ANT</th> <th style="text-align: left;">Turn</th> </tr> <tr> <th style="text-align: left;">MHz</th> <th style="text-align: left;">level</th> <th style="text-align: left;">dBuV/m</th> <th style="text-align: left;">dB</th> <th style="text-align: left;">reading</th> <th style="text-align: left;">dB</th> <th></th> <th style="text-align: left;">High</th> <th style="text-align: left;">Table</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2483.50</td> <td>37.94</td> <td>54.00</td> <td>-16.06</td> <td>40.63</td> <td>-2.69</td> <td>Average</td> <td>326</td> <td>31</td> </tr> <tr> <td>2</td> <td>2483.50</td> <td>52.67</td> <td>74.00</td> <td>-21.33</td> <td>55.36</td> <td>-2.69</td> <td>Peak</td> <td>326</td> <td>31</td> </tr> <tr> <td>3</td> <td>4904.00</td> <td>33.01</td> <td>54.00</td> <td>-20.99</td> <td>28.53</td> <td>4.48</td> <td>Average</td> <td>255</td> <td>37</td> </tr> <tr> <td>4</td> <td>4904.00</td> <td>46.01</td> <td>74.00</td> <td>-27.99</td> <td>41.53</td> <td>4.48</td> <td>Peak</td> <td>255</td> <td>37</td> </tr> <tr> <td>5</td> <td>7356.00</td> <td>37.77</td> <td>54.00</td> <td>-16.23</td> <td>28.46</td> <td>9.31</td> <td>Average</td> <td>222</td> <td>54</td> </tr> <tr> <td>6</td> <td>7356.00</td> <td>51.70</td> <td>74.00</td> <td>-22.30</td> <td>42.39</td> <td>9.31</td> <td>Peak</td> <td>222</td> <td>54</td> </tr> </tbody> </table>				Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	dBuV/m	dB	reading	dB		High	Table	1	2483.50	37.94	54.00	-16.06	40.63	-2.69	Average	326	31	2	2483.50	52.67	74.00	-21.33	55.36	-2.69	Peak	326	31	3	4904.00	33.01	54.00	-20.99	28.53	4.48	Average	255	37	4	4904.00	46.01	74.00	-27.99	41.53	4.48	Peak	255	37	5	7356.00	37.77	54.00	-16.23	28.46	9.31	Average	222	54	6	7356.00	51.70	74.00	-22.30	42.39	9.31	Peak	222	54
Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																									
MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																									
1	2483.50	37.94	54.00	-16.06	40.63	-2.69	Average	326	31																																																																								
2	2483.50	52.67	74.00	-21.33	55.36	-2.69	Peak	326	31																																																																								
3	4904.00	33.01	54.00	-20.99	28.53	4.48	Average	255	37																																																																								
4	4904.00	46.01	74.00	-27.99	41.53	4.48	Peak	255	37																																																																								
5	7356.00	37.77	54.00	-16.23	28.46	9.31	Average	222	54																																																																								
6	7356.00	51.70	74.00	-22.30	42.39	9.31	Peak	222	54																																																																								

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

## 3.6 Emissions in Non-Restricted Frequency Bands

### 3.6.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz

### 3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.6.3 Test Procedures


#### Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

#### Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

### 3.6.4 Test Setup





### 3.6.5 Test Result of Emissions in non-restricted frequency bands


This test item is performed on each TX output individually without summing or adding  $10 \log(N_{ANT})$  since measurements are made relative to the in-band emissions on the individual outputs. Only worst test result of each operating mode is presented.

### 3.6.6 Unwanted Emissions into Non-Restricted Frequency Bands


#### 802.11b










802.11g










## 802.11n HT20









## 802.11n HT40







## 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

### Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou  
District, New Taipei City, Taiwan,  
R.O.C.

### Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd  
St., Kwei Shan Hsiang, Tao Yuan  
Hsien 333, Taiwan, R.O.C.

### Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd  
St., Kwei Shan Hsiang, Tao Yuan  
Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: [ICC\\_Service@icertifi.com.tw](mailto:ICC_Service@icertifi.com.tw)

==END==