



FCC PART 15D

MEASUREMENT AND TEST REPORT

For

CETIS, INC.

5025 Galley Road, Colorado Springs CO, 80915 USA

FCC ID: ZTUAC9105S

Report Type: Original Report	Product Type: DECT Telephone (Base)
Test Engineer: <u>Brown Lu</u>	
Report Number: <u>RSZ120129012-00FP</u>	
Report Date: <u>2012-08-03</u>	
Reviewed By: <u>RF Engineer</u> Test Laboratory: <u>Bay Area Compliance Laboratories Corp. (Shenzhen)</u> <u>6/F, the 3rd Phase of WanLi Industrial Building,</u> <u>ShiHua Road, FuTian Free Trade Zone</u> <u>Shenzhen, Guangdong, China</u> <u>Tel: +86-755-33320018</u> <u>Fax: +86-755-33320008</u> <u>www.baclcorp.com.cn</u>	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Shenzhen). This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk “★” (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY.....	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC§ 15.319 (I) & 2.1091 - RF RADIATION EXPOSURE	8
LIMIT	8
MPE CALCULATION.....	8
FCC§15.317&§15.203 - ANTENNA REQUIREMENT	9
APPLICABLE STANDARD	9
FCC§15.315 & §15.207 - CONDUCTED EMISSIONS	10
MEASUREMENT UNCERTAINTY	10
EUT SETUP	10
EMI TEST RECEIVER SETUP.....	11
TEST EQUIPMENT LIST AND DETAILS.....	11
TEST PROCEDURE	11
TEST RESULTS SUMMARY	11
TEST DATA	11
FCC§15.323 (A) - EMISSION BANDWIDTH	14
APPLICABLE STANDARD	14
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST DATA	15
FCC§15.319 (C) - PEAK TRANSMIT POWER	17
APPLICABLE STANDARD	17
TEST PROCEDURE	17
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST DATA	18
FCC§15.319 (D) - POWER SPECTRAL DENSITY	20
APPLICABLE STANDARD	20
TEST PROCEDURE	20
TEST EQUIPMENT LIST AND DETAILS.....	20
TEST DATA	21
FCC§15.323 (D) - EMISSION INSIDE AND OUTSIDE THE SUB-BAND	25
APPLICABLE STANDARD	25
TEST EQUIPMENT LIST AND DETAILS.....	25
TEST DATA	25

FCC§15.319 (G) - RADIATED EMISSIONS.....	34
MEASUREMENT UNCERTAINTY	34
EUT SETUP	34
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	35
TEST EQUIPMENT LIST AND DETAILS.....	35
TEST PROCEDURE	35
CORRECTED AMPLITUDE & MARGIN CALCULATION	35
TEST RESULTS SUMMARY.....	36
TEST DATA	36
FCC§15.323 (F) - FREQUENCY STABILITY.....	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST EQUIPMENT LIST AND DETAILS.....	41
TEST DATA	41
FCC§15.323 (C) (E) & §15.319(F) – SPECIFIC REQUIREMENTS FOR UPCS DEVICE.....	43
DECLARATION LETTER	49

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The *CETIS, INC.* 's product, model number: *AC9210S (FCC ID: ZTUAC9105S)* or the "EUT" in this report is a base of DECT Telephone, which was measures approximately: 22.0 cm (L) x 15.1 cm (W) x 5.0 cm (H), input voltage: DC 12V from adapter.

Adapter information

Model: ZX-12003001200150;
Input: 100-240V~50/60Hz 0.2A Max;
Output: (1-8) DC 12.0V 150 mA
(2-7) DC 12.0V 300 mA

Note: The series product, model AC9105S, AC9110S, AC9205S and AC9210S, the differences between them were explained for details in the attached declaration letter. We select AC9210S to perform full test items.

**All measurement and test data in this report was gathered from production sample serial number: 1201061 (Assigned by BACL, Shenzhen). The EUT was received on 2012-01-29.*

Objective

This document is a test report based on the Electromagnetic Interference (EMI) tests performed on the EUT. The EMI measurements were performed according to the measurement procedure described in ANSI C63.17 – 2006, and ANSI C63.4-2009

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart D, section 15.203, 15.207, 15.315, 15.317, 15.319 and 15.323 rules.

Related Submittal(s)/Grant(s)

FCC ID: ZTUAC9105S, FCC Part 15D submission of Handset portion.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.17 - 2006 American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for TBR6 mode, which is provided by the manufacturer.

Equipment Modifications

No modification was made to the unit tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
R&S	Digital Radio-Communication Tester	CMD60	829902/026

External I/O Cable

Cable Description	Length (m)	From/Port	To
Unshielded Detachable DC Power Cable	4.60	EUT	Adapter

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§ 15.319 (i)&2.1091	RF Radiation Exposure	Compliance
§ 15.317 § 15.203	Antenna Requirement	Compliance
§ 15.315 § 15.207	Conducted Emission	Compliance
§ 15.323 (a)	Emission Bandwidth	Compliance
§ 15.319 (c)	Peak Transmit Power	Compliance
§ 15.319 (d)	Power Spectral Density	Compliance
§ 15.323 (d)	Emission Inside and Outside the sub-band	Compliance
§ 15.319 (g)	Radiated Emission	Compliance
§ 15.323 (f)	Frequency Stability	Compliance
§ 15.323 (c)(e) § 15.319 (f)	Specific Requirements for UPSCS	Compliance

FCC§ 15.319 (i) &2.1091 - RF RADIATION EXPOSURE

Limit

According to FCC §15.319(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	842/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

MPE Calculation

Predication of MPE limit at a given distance

$$S = PG/4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
1921.536	0	1	16.28	42.46	20	0.00845	1.0

Result: The device meets MPE limit at 20 cm distance.

FCC§15.317&§15.203 - ANTENNA REQUIREMENT

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has two integrated antennas with gain 0dBi arrangement, which was soldered on PCB, fulfill the requirement of this section. Please refer to the internal photos.

Test Result: Pass


FCC§15.315 & §15.207 - CONDUCTED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is 2.4 dB.

EUT Setup



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC 15.315 and FCC 15.207 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2011-11-24	2012-11-23
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2011-11-17	2012-11-16
Rohde & Schwarz	Pulse limiter	ESH3Z2	DE25985	2011-07-08	2012-07-07
BACL	CE Test software	BACL-CE	V1.0	-	-

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15 .207, with the worst margin reading of:

8.32 dB at 0.355 MHz in the Line conductor mode

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Brown Lu on 2012-02-03.

Test Mode: Communicating

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (PK/Ave./QP)
0.355	51.82	10.10	60.14	8.32	QP
0.355	40.90	10.10	50.14	9.24	Ave.
10.740	39.09	10.10	50.00	10.91	Ave.
0.525	43.87	10.10	56.00	12.13	QP
1.400	41.97	10.10	56.00	14.03	QP
10.740	45.75	10.10	60.00	14.25	QP
1.400	29.48	10.10	46.00	16.52	Ave.
0.525	29.04	10.10	46.00	16.96	Ave.
2.225	36.67	10.10	56.00	19.33	QP
2.230	23.58	10.10	46.00	22.42	Ave.
19.205	12.79	10.10	50.00	37.21	Ave.
19.210	15.06	10.10	60.00	44.94	QP

AC 120V/ 60 Hz, Neutral:


Frequency (MHz)	Corrected Amplitude (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (QP/Ave./QP)
0.360	51.42	10.10	60.00	8.58	QP
0.360	41.41	10.10	50.00	8.59	Ave.
10.740	41.22	10.10	50.00	8.78	Ave.
0.525	43.65	10.10	56.00	12.35	QP
0.525	32.95	10.10	46.00	13.05	Ave.
10.740	45.67	10.10	60.00	14.33	QP
1.470	30.96	10.10	46.00	15.04	Ave.
1.465	40.17	10.10	56.00	15.83	QP
1.830	37.65	10.10	56.00	18.35	QP
1.825	26.92	10.10	46.00	19.08	Ave.
6.110	24.29	10.10	50.00	25.71	Ave.
6.050	30.76	10.10	60.00	29.24	QP

FCC§15.323 (a) - EMISSION BANDWIDTH

Applicable Standard

Operation shall be contained within the 1920–1930 MHz band. The emission bandwidth shall be less than 2.5 MHz and greater than 50 kHz.

The emission bandwidth is measured in accordance with ANSI C63.17 sub-clause 6.1.3 using the setup below:



The width, in Hz, of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that is 26 dB down relative to the maximum level of the modulated carrier. It is based on the use of measurement instrumentation employing a peak detector function with an instrument resolution bandwidth approximately equal to 1% of the emission band-width of the device under measurement. [Extraction from 47 CFR 15, subpart D, 15.303 (C)].

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2011-11-17	2012-11-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa


The testing was performed by Brown Lu on 2012-02-04.

Test Mode: Transmitting


Test Result: Compliance. Please refer to the following table and plots:

Channel	Center Frequency (MHz)	26 dB Bandwidth (MHz)	Limit
Low	1921.536	1.384	50kHz < OBW <2.5MHz
Middle	1924.992	1.368	50kHz < OBW <2.5MHz
High	1928.448	1.376	50kHz < OBW <2.5MHz


Low Channel



Date: 4.FEB.2012 00:07:09

Middle Channel

Date: 4.FEB.2012 00:09:19

High Channel

Date: 4.FEB.2012 00:11:35

FCC§15.319 (c) - PEAK TRANSMIT POWER

Applicable Standard

The peak transmit power is according to ANSI C63.17-2006 §6.1.2

Per FCC Part15.319 (a), Peak transmit power shall not exceed 100 microwatts multiplied by the square root of the emission bandwidth in hertz.

Per FCC Part15.319 (e), the peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

Calculation of Peak Transmit Power Limit (P_{max}):

$$P_{max} = 100\mu\text{w} \times (EBW)^{1/2}$$

EBW is the transmit emission bandwidth in Hz determined in the other test item:

Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

RBW	≥ Emission bandwidth
Video bandwidth	≥ RBW
Span	Zero
Center frequency	Nominal center frequency of channels
Amplitude scale	Log (linear may be used if analyzer has sufficient linear dynamic range and accuracy)
Detection	Peak detection
Trigger	Video
Sweep rate	Sufficiently rapid to permit the transmit pulse to be resolved accurately

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2011-11-17	2012-11-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Brown Lu on 2012-02-03.


Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table and plots:

Frequency (MHz)	Peak Transmit Power (dBm)	Limit (dBm)
1921.536	16.28	20.71
1924.992	16.28	20.68
1928.448	16.20	20.69


EBW_{Low channel} = 1384000 Hz, EBW_{Middle channel} = 1368000 Hz, EBW_{High channel} = 1376000 Hz
 Peak Transmit Power Limit = $100\mu\text{W} \times (\text{EBW})^{1/2}$

Low Channel




Date: 3.FEB.2012 23:37:46

Middle Channel



Date: 3.FEB.2012 23:36:52

High Channel



Date: 3.FEB.2012 23:35:58

FCC§15.319 (d) - POWER SPECTRAL DENSITY

Applicable Standard

The power spectral density is according to ANSI C63.17-2006 §6.1.5

The average pulse energy in a 3 kHz bandwidth is divided by the pulse duration.

The power spectral density shall not exceed 3mW in any 3 kHz bandwidth as measured with a spectrum analyzer having a resolution bandwidth of 3 kHz.

Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

RBW	3 kHz
Video bandwidth	$\geq 3 \times \text{RBW}$
Span	Zero span at frequency with the maximum level (frequency determined in 6.1.3 if the same type of signal (continuous versus burst) was used in 6.1.3)
Center frequency	Spectral peak as determined in 6.1.3
Sweep time	For burst signals, sufficient to include essentially all of the maximum length burst at the output of a 3 kHz filter (e.g., maximum input burst duration plus 600 μs). For continuous signals, 20 ms.
Amplitude scale	Log power
Detection	Sample detection and averaged for a minimum of 100 sweeps
Trigger	External or internal

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2011-11-17	2012-11-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa


The testing was performed by Brown Lu from 2012-02-03 to 2012-02-04.

Test Mode: Transmitting


Test Result: Compliance. Please refer to the following table and plots:

Frequency (MHz)	Power Spectral Density		Limit (mW/3 kHz)	Result
	(dBm/3 kHz)	(mW/3 kHz)		
1921.536	-5.05	0.313	3	Pass
1924.992	-7.64	0.172	3	Pass
1928.448	-5.63	0.274	3	Pass

Low Channel




Date: 3.FEB.2012 23:41:16




Date: 4.FEB.2012 00:02:12

Middle Channel




Date: 3.FEB.2012 23:42:58




Date: 4.FEB.2012 00:00:32

High Channel



Date: 3.FEB.2012 23:45:04



Date: 3.FEB.2012 23:57:55

FCC§15.323 (d) - EMISSION INSIDE AND OUTSIDE THE SUB-BAND**Applicable Standard**

Emissions inside the sub-band must comply with the following emission mask:

1. In the bands between 1B and 2B measured from the center of the emission bandwidth the total power emitted by the device shall be at least 30 dB below the transmit power permitted for that device;
2. in the bands between 2B and 3B measured from the center of the emission bandwidth the total power emitted by an intentional radiator shall be at least 50 dB below the transmit power permitted for that radiator;
3. in the bands between 3B and the sub-band edge the total power emitted by an intentional radiator in the measurement bandwidth shall be at least 60 dB below the transmit power permitted for that radiator.

Where B = emission bandwidth

Emission Outside the sub-band shall be attenuated below a reference power of 112 mW (20.5 dBm) as follows:

1. 30 dB between the sub-band and 1.25 MHz above or below the sub-band;
2. 50 dB between 1.25 and 2.5 MHz above or below the sub-band;
3. 60 dB at 2.5 MHz or greater above or below the sub-band.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2011-11-17	2012-11-16
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.


Test Data**Environmental Conditions**

Temperature:	20 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa


The testing was performed by Brown Lu from 2012-02-03 to 2012-02-04.

Test Mode: Transmitting


Test Result: Compliance. Please refer to following plots:

Low Channel (Unwanted Emission inside the Sub-band)


Date: 4.FEB.2012 00:47:56

Middle Channel (Unwanted Emission inside the Sub-band)


Date: 4.FEB.2012 00:44:27

High Channel (Unwanted Emission inside the Sub-band)


Date: 4.FEB.2012 00:40:53

Low Channel (Unwanted Emission outside the Sub-band)


Date: 4.FEB.2012 00:20:32




Date: 4.FEB.2012 00:31:19




Date: 4.FEB.2012 00:33:18




Middle Channel (Unwanted Emission outside the Sub-band)




Date: 4.FEB.2012 00:23:54




Date: 4.FEB.2012 00:30:19




Date: 4.FEB.2012 00:34:18




High Channel (Unwanted Emission outside the Sub-band)




Date: 4.FEB.2012 00:26:20



Date: 4.FEB.2012 00:28:55



Date: 4.FEB.2012 00:35:44




FCC§15.319 (g) - RADIATED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is 4.0 dB.

EUT Setup



The radiated emission tests were performed in the 3 meters chamber B test site, using the setup accordance with the ANSI C63.17 - 2006. The specification used was the FCC 15§ 15.319(g).

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 20 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W
30MHz – 1000 MHz	100 kHz	300 kHz
Above 1 GHz	1 MHz	3 MHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447D	2944A09795	2011-11-24	2012-11-23
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2011-11-17	2012-11-16
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2012-11-27
SUPER ULTRA	Amplifier	ZVA-213+	N/A	2011-11-24	2012-11-23
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2012-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23
Agilent	Spectrum Analyzer	8564E	3943A01781	2011-04-12	2012-04-11
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2011-10-14	2012-10-13
R&S	Auto test Software	EMC32	V6.30	-	-

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC 15.209 and FCC Part 15.319 (g), with the worst margin reading of:

5.2 dB at 642.77 MHz in the **Horizontal** polarization

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Brown Lu on 2012-03-05.

Test Mode: Transmitting

30 MHz-20 GHz

Freq. (MHz)	Meter Reading (dB μ V)	Detector PK/QP/Ave	Direction Degree	Antenna			Cable Loss (dB)	Pre- Amp. Gain (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.319(g)/209		
				Height (m)	Polar (H/V)	Antenna Loss				Limit (dB μ V/m)	Margin (dB)	Remarks
Low Channel												
1921.536	105.49	PK	160	1.3	V	29.40	2.97	26.49	111.37	N/A	N/A	Fund.
1921.536	102.36	PK	250	1.5	H	29.20	2.97	26.49	108.04	N/A	N/A	Fund.
642.77	45.80	QP	117	2.1	H	17.80	3.56	26.56	40.60	46.00	5.40	Spurious
11549.1	38.42	PK	180	1.9	H	43.00	6.69	26.12	61.99	74.00	12.01	Harmonic
9607.2	40.37	PK	50	2.1	H	41.20	5.98	26.42	61.13	74.00	12.87	Harmonic
9607.2	40.61	PK	160	1.6	V	40.00	5.98	26.42	60.17	74.00	13.83	Harmonic
5764.6	45.59	PK	190	1.0	V	36.20	4.57	26.68	59.68	74.00	14.32	Harmonic
5764.6	43.81	PK	240	1.3	H	37.40	4.57	26.68	59.10	74.00	14.90	Harmonic
7686.3	40.86	PK	350	2.1	H	39.30	5.31	26.64	58.83	74.00	15.17	Harmonic
7686.3	41.09	PK	310	1.8	V	37.90	5.31	26.64	57.66	74.00	16.34	Harmonic
3843.1	46.53	PK	140	1.4	H	33.90	3.73	26.87	57.29	74.00	16.71	Harmonic
3843.1	47.16	PK	130	1.1	V	33.00	3.73	26.87	57.02	74.00	16.98	Harmonic
Middle Channel												
1924.992	105.09	PK	240	1.2	V	29.40	2.97	26.49	110.97	N/A	N/A	Fund.
1924.992	101.37	PK	150	1.8	H	29.20	2.97	26.49	107.05	N/A	N/A	Fund.
642.77	46.00	QP	117	2.1	H	17.80	3.56	26.56	40.80	46.00	5.20	Spurious
9624.5	43.76	PK	280	1.8	V	40.00	5.98	26.42	63.32	74.00	10.68	Harmonic
11543.7	39.39	PK	190	1.3	H	43.00	6.69	26.12	62.96	74.00	11.04	Harmonic
9624.5	41.55	PK	150	1.5	H	41.20	5.98	26.42	62.31	74.00	11.69	Harmonic
5774.9	46.56	PK	190	1.1	V	36.20	4.57	26.68	60.65	74.00	13.35	Harmonic
5774.9	45.28	PK	310	2.1	H	37.40	4.57	26.68	60.57	74.00	13.43	Harmonic
7699.6	43.60	PK	340	1.4	V	37.90	5.31	26.64	60.17	74.00	13.83	Harmonic
7699.6	40.58	PK	260	1.3	H	39.30	5.31	26.64	58.55	74.00	15.45	Harmonic
3849.8	47.63	PK	310	1.5	V	33.00	3.73	26.87	57.49	74.00	16.51	Harmonic
3849.8	46.48	PK	260	1.3	H	33.90	3.73	26.87	57.24	74.00	16.76	Harmonic
High Channel												
1928.448	105.95	PK	110	1.6	V	29.40	2.97	26.49	111.83	N/A	N/A	Fund.
1928.448	102.73	PK	340	1.4	H	29.20	2.97	26.49	108.41	N/A	N/A	Fund.
642.77	45.70	QP	117	2.1	H	17.80	3.56	26.56	40.50	46.00	5.50	Spurious
11544.6	38.59	PK	260	1.8	H	43.00	6.69	26.12	62.16	74.00	11.84	Harmonic
5785.2	47.42	PK	240	1.8	V	36.20	4.57	26.68	61.51	74.00	12.49	Harmonic
5785.2	45.74	PK	250	1.7	H	37.40	4.57	26.68	61.03	74.00	12.97	Harmonic
9642.1	40.24	PK	240	1.0	H	41.20	5.98	26.42	61.00	74.00	13.00	Harmonic
9642.1	41.17	PK	180	2.0	V	40.00	5.98	26.42	60.73	74.00	13.27	Harmonic
7713.6	41.30	PK	320	1.2	H	39.30	5.31	26.64	59.27	74.00	14.73	Harmonic
7713.6	41.46	PK	160	1.6	V	37.90	5.31	26.64	58.03	74.00	15.97	Harmonic
3856.8	48.09	PK	260	1.1	V	33.00	3.73	26.87	57.95	74.00	16.05	Harmonic
3856.8	46.67	PK	190	2.1	H	33.90	3.73	26.87	57.43	74.00	16.57	Harmonic

Field Strength of Radiated Emission Average							
Freq. (MHz)	Peak Corrected Amplitude. @3m (dB μ V/m)	Polar H/V	Duty Cycle Factor (dB)	Corrected Amplitude. (dB μ V/m)	FCC Part 15.319(g)		Comment
					Limit (dB μ V/m)	Margin (dB)	
Low Channel							
11549.1	61.99	H	-27.70	34.29	54	19.71	Harmonic
9607.2	61.13	H	-27.70	33.43	54	20.57	Harmonic
9607.2	60.17	V	-27.70	32.47	54	21.53	Harmonic
5764.6	59.68	V	-27.70	31.98	54	22.02	Harmonic
5764.6	59.10	H	-27.70	31.40	54	22.60	Harmonic
7686.3	58.83	H	-27.70	31.13	54	22.87	Harmonic
7686.3	57.66	V	-27.70	29.96	54	24.04	Harmonic
3843.1	57.29	H	-27.70	29.59	54	24.41	Harmonic
3843.1	57.02	V	-27.70	29.32	54	24.68	Harmonic
Middle Channel							
9624.5	63.32	V	-27.70	35.62	54	18.38	Harmonic
11543.7	62.96	H	-27.70	35.26	54	18.74	Harmonic
9624.5	62.31	H	-27.70	34.61	54	19.39	Harmonic
5774.9	60.65	V	-27.70	32.95	54	21.05	Harmonic
5774.9	60.57	H	-27.70	32.87	54	21.13	Harmonic
7699.6	60.17	V	-27.70	32.47	54	21.53	Harmonic
7699.6	58.55	H	-27.70	30.85	54	23.15	Harmonic
3849.8	57.49	V	-27.70	29.79	54	24.21	Harmonic
3849.8	57.24	H	-27.70	29.54	54	24.46	Harmonic
High Channel							
11544.6	62.16	H	-27.70	34.46	54	19.54	Harmonic
5785.2	61.51	V	-27.70	33.81	54	20.19	Harmonic
5785.2	61.03	H	-27.70	33.33	54	20.67	Harmonic
9642.1	61.00	H	-27.70	33.30	54	20.70	Harmonic
9642.1	60.73	V	-27.70	33.03	54	20.97	Harmonic
7713.6	59.27	H	-27.70	31.57	54	22.43	Harmonic
7713.6	58.03	V	-27.70	30.33	54	23.67	Harmonic
3856.8	57.95	V	-27.70	30.25	54	23.75	Harmonic
3856.8	57.43	H	-27.70	29.73	54	24.27	Harmonic

Note: Duty Cycle=Ton/Tp*100%


Ton= 412 μ s = 0.412ms

Tp= 10.01ms


Duty Cycle= 4.12%

Duty cycle factor = 20lg(Duty Cycle)= -27.70


AV=PK+20* lg(Duty Cycle)

T_{on}:

Date: 5.MAR.2012 23:20:45

T_p:

Date: 5.MAR.2012 23:21:31



Date: 28.JUL.2012 02:29:33

FCC§15.323 (f) - FREQUENCY STABILITY

Applicable Standard

Per §15.323(f), the frequency stability of the carrier frequency of the intentional radiator shall be maintained within ± 10 ppm over 1 hour or the interval between channel access monitoring, whichever is shorter. The frequency stability shall be maintained over a temperature variation of -20° to $+50^{\circ}$ C at normal supply voltage, and over a variation in the primary supply voltage of 85 percent to 115 percent of the rated supply voltage at a temperature of 20° C. For equipment that is capable only of operating from a battery, the frequency stability tests shall be performed using a new battery without any further requirement to vary supply voltage.

Test Procedure

This procedure should be carried out for each of the following test cases:

Temperature	Supply Voltage
20° C	85-115% of declared nominal voltage
-20° C	Normal
$+50^{\circ}$ C	Normal

^a Use the lowest temperature at which the EUT is specified to operate if it is above -20° C.

Using the mean carrier frequency at 20° C and at nominal supply voltage as the reference, the mean carrier frequency shall be maintained within ± 10 ppm at the two extreme temperatures (or as declared by the manufacturer) and at normal temperature (typically 20° C) at the two extreme supply voltages.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2011-11-24	2012-11-23
R & S	Digital Radio-Communication Tester	CMD60	829902/026	2011-03-16	2012-03-15

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Brown Lu on 2012-02-04.

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table:

Temperature (°C)	Voltage (V _{AC})	Channel Frequency (MHz)	Measured Frequency Offset (kHz)	Measured Frequency Offset (ppm)	Limit (ppm)
20	102	1924.992	-15	-7.79	±10
	120	1924.992	-12	-6.23	±10
	138	1924.992	-11	-5.71	±10
-20	120	1924.992	-14	-7.27	±10
50	120	1924.992	-9	-4.67	±10

FCC§15.323 (c) (e) & §15.319(f) – SPECIFIC REQUIREMENTS FOR UPCS DEVICE

Automatic Discontinuation of Transmission, FCC Part 15.319(f)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. The provisions in this section are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Test Procedure:

Please according to the declaration provided by manufacturer.

Test result:

Meet the requirement

Monitoring Time FCC Part 15.323 (c)(1)

Immediately prior to initiating transmission, devices must monitor the combined time and spectrum window in which they intend to transmit. For a period of at least 10 milliseconds for systems designed to use a 10 milliseconds or shorter frame period or at least 20 milliseconds for systems designed to use a 20 milliseconds frame period

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 7.3.4

Test result:

EUT monitors the combined time and spectrum window prior to initiation of transmission. Test result please according to FCC15.323(c)(4).

Lower Monitoring Threshold Part 15.323 (c)(2)

The monitoring threshold must not be more than 30 dB above the thermal noise power for a bandwidth equivalent to the emission bandwidth used by the device.

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 7.3.1

Test result: Not Apply

Maximum Transmit Period FCC Part 15.323 (c)(3)

If no signal above the threshold level is detected, transmission may commence and continue with the same emission bandwidth in the monitored time and spectrum windows without further monitoring. However, occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria.

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 8.2.2

Test result:

Repetition of Access Criteria	Measured Maximum Transmission Time (Second)	Limit (Second)	Results
First	19800	28,800	Pass
Second	18000	28,800	Pass

System Acknowledgement, FCC Part 15.323 (c) (4)

Once access to specific combined time and spectrum windows is obtained an acknowledgment from a system participant must be received by the initiating transmitter within one second or transmission must cease. Periodic acknowledgments must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgment, at which time the access criteria must be repeated.

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 8.1.1, 8.2.1

Test result:

Test	Time taken (second)	Limit (second)	Result
Connection acknowledgement	0.1	1	Pass
Change of access criteria for control information	22.5	30	Pass
Transmission cease time	1.2	30	Pass
Pulse length	0.000412	0.01	Pass

Least Interfered Channel (LIC) Selection, FCC Part 15.323 (c) (5)

If access to spectrum is not available as determined by the above, and a minimum of 40 duplex system access channels are defined for the system, the time and spectrum windows with the lowest power level below a monitoring threshold of 50 dB above the thermal noise power determined for the emission bandwidth may be accessed.

Calculation of monitoring threshold limits for isochroous devices:

Lower threshold: $T_L = -174 + 10 \log_{10} B + M_u + P_{MAX} - P_{EUT}$ (dBm)

Upper threshold: $T_U = -174 + 10 \log_{10} B + M_u + P_{MAX} - P_{EUT}$ (dBm)

Where: B=Emission bandwidth (Hz)

M_u =dB the threshold may exceed thermal noise (30 for T_L & 50 for T_U)

$P_{MAX} = 5 \log_{10} B - 10$ (dBm)

P_{EUT} =Transmitted power (dBm)

Limit:

Monitor Threshold	B (MHz)	M _u (dB)	P _{MAX} (dBm)	P _{EUT} (dBm)	Threshold (dBm)
T _L	1.384	30	20.71	16.28	-78.16
T _U	1.384	50	20.71	16.28	-58.16

The EUT must not transmit until the interference level is less than or equal to:

Measured Threshold Level $\leq T_U$

Where: T_U =Upper threshold level

Test procedure:

Measurement method according to ANSI C63.17 clause 7.3.2, 7.3.3, 7.3.4

Test result:

Not apply

Monitor threshold	Measured Threshold Level	Limit (dBm)
Lower Threshold(dBm)	N/A	-78.16
Upper Threshold(dBm)	N/A	-58.16

Note: The upper threshold is applicable as the EUT utilizes more than 40 duplex system channels

Random waiting FCC Part 15.323(c)(6)

If the selected combined time and spectrum windows are unavailable, the device may either monitor and select different windows or seek to use the same window after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 milliseconds, commencing when the channel becomes available.

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 8.1.3

Test result:

The manufacturer declares that this provision is not utilized by the EUT.

Monitoring Bandwidth, FCC Part 15.323 (c) (7)

The monitoring system bandwidth must be equal to or greater than the emission bandwidth of the intended transmission and have a maximum reaction time less than $50 \times \text{SQRT}(1.25/\text{emission bandwidth in MHz})$ microseconds for signals at the applicable threshold level but shall not be required to be less than 50 microseconds

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 7.5.

Test result:

Test Equation (μs)	B(bandwidth) (MHz)	Pulse width (μs)	Limit (μs)	Result
$50 (1.25/B)^{1/2}$	1.384	47.52	50	Pass
$35 (1.25/B)^{1/2}$	1.384	33.26	35	Pass

Monitoring Antenna, FCC Part 15.323 (c)(8)

The monitoring system shall use the same antenna used for transmission, or an antenna that yields equivalent reception at that location.

Test procedure:

Measurement method according to ANSI C63.17 2006 paragraph 4

Test result:

The antenna of the EUT used for transmission is the same interior antenna that used for monitoring.

Monitoring threshold relation FCC Part 15.323(c)(9)

Devices that have a power output lower than the maximum permitted under the rules can increase their monitoring detection threshold by one decibel for each one decibel that the transmitter power is below the maximum permitted.

Test procedure:

Measurement method according to ANSI C63.17 2006 paragraph 4

Test result:

Not apply based on 15.323 (c)(5)

Duplex Connections, FCC Part 15.323 (c) (10)

An initiating device may attempt to establish a duplex connection by monitors both its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.

Test procedure:

Measurement method according to ANSI C63.17 clause 8.3

Test result:

The manufacturer declares that this provision is not utilized by the EUT.

Alternative monitoring interval for co-located devices, FCC Part 15.323 (c) (11)

An initiating device that is prevented from monitoring during its intended transmit window due to monitoring system blocking from the transmissions of a co-located (within one meter) transmitter of the same system, may monitor the portions of the time and spectrum windows in which they intend to receive over a period of at least 10 milliseconds. The monitored time and spectrum window must total at least 50 percent of the 10 millisecond frame interval and the monitored spectrum must be within 1.25 MHz of the center frequency of channel(s) already occupied by that device or co-located co-operating devices. If the access criteria is met for the intended receive time and spectrum window under the above conditions, then transmission in the intended transmit window by the initiating device may commence.

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 8.4.

Test result:

The manufacturer declares that this provision is not utilized by the EUT.

Fair Access, FCC Part 15.323 (c)(12)

The provisions of FCC Part15.323(c)(10) or (c)(11) shall not be used to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.

Test result:

The manufacturer declares that this device does not use any mechanisms as provided by Part15.323 (c) (10) or (c) (11) to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other device.

Frame Repetition Stability, Part 15 .323 (e)

The frame period (a set of consecutive time slots in which the position of each time slot can be identified by reference to a synchronizing source) of an intentional radiator operating in these sub-bands shall be 20 milliseconds or 10 milliseconds/X where X is a positive whole number.

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 6.2.2, 6.2.3

Test result:

Frame Repetition Stability:

Frame Repetition Stability (ppm)	Limit (ppm)	Result (Pass/Fail)
3.88	10	Pass

Frame Period and Jitter:

Max. pos. Jitter (us)	Max. neg. Jitter (us)	Frame period (ms)	Limit	
			Frame Period (ms)	Jitter (us)
0.01	-0.06	10.00000	20 or 10/X	25us

Note: X is a positive whole number.

DECALARATION LETTER

Cetis, Inc.

Address: 5025 Galley Road, Colorado Springs CO, 80915, USA

Tel: 719-638-8821

Fax: 719-638-8815

5/20/2012

Product Similarity Declaration

To Whom It May Concern,

We, Cetis, Inc., hereby declare that our DECT Telephone was tested by BACL, and for our marketing purpose, we would like to list four models on reports and certificate, all the models have the same schematic, the differences between these models for details as below:

Production name	Trade name	Model no.	Description
DECT Telephone	Cetis	AC9105S	5 quick dial keys with single line
DECT Telephone	Cetis	AC9110S,	10 quick dial keys with single line
DECT Telephone	Cetis	AC9205S	5 quick dial keys with Double line
DECT Telephone	Cetis	AC9210S	10 quick dial keys with Double line

No other differences are made to them.

Please contact me if you have any question.

Signature:

A handwritten signature in black ink, appearing to read "Brock Munsell".

Brock Munsell

Chief Technology Officer

******* END OF REPORT *******