

FCC 47 CFR PART 15 SUBPART C TEST REPORT

For

Applicant: Ambitio LLC, The Owner of unnecto ™

Address: 1315 N.W 98th ct Suite 13 United States

Product Name: GSM MOBILE PHONE

Model Name: U-500-2

Brand Name: unnecto ™

FCC ID: ZU3UNNECTOTAP

Report No.: STS111224F2B

Date of Issue: January. 06, 2012

Issued by: Shenzhen Super Test Service Technology Co., Ltd.

No.5, Langshan 2nd Rd., North Hi-Tech Industrial park, Nanshan,

Address : Shenzhen, Guangdong, China

Tel: 86-755-2795 8522

Fax: 86-755-2795 8022

The report consists 61 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by STS. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver.

FCC ID: ZU3UNNECTOTAP

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	3
2. GENERAL INFORMATION	4
2.1 Product Information	4
2.2 Objective	5
2.3 Test Standards and Results	5
2.4 Environmental Conditions	5
3. TEST FACILITY	6
4. TEST EQUIPMENT LIST	7
5. 47 CFR Part 15 C 15.247 Requirements	8
5.1 6dB Bandwidth	8
5.2 Peak Output Power	13
5.3 Conducted Spurious Emission	17
5.4 Band Edge	21
5.5 Power Spectral Density (PSD)	27
5.6 Conducted Emission	31
5.7 Radiated Emission	34
APPENDIX 1	46
PHOTOGRAPHS OF TEST SETUP	46
APPENDIX 2	49
PHOTOGRAPHS OF EUT	49

FCC ID: ZU3UNNECTOTAP Report No.: STS111224F2B

1. VERIFICATION OF CONFORMITY

Equipment Under Test: GSM MOBILE PHONE

Brand Name: unnecto ™
Model Number: U-500-2

FCC ID: ZU3UNNECTOTAP

Applicant: Ambitio LLC, The Owner of unnecto ™

1315 N.W 98th ct Suite 13 United States

Manufacturer: Shenzhen Xiangyue Perfect Digital Science & Technology Co.,Ltd

Building A1, Jiujiutongxin Industrial Zone 11, Xinbu, Tongle, Longgang, Shenzhen

Technical Standards: 47 CFR Part 15 Subpart C

File Number: STS111224F2B

Date of test: December. 22,2011 ~ January. 05, 2012

Deviation:NoneCondition of Test Sample:NormalTest Result:PASS

The above equipment was tested by *Shenzhen Super Test Service Technology Co., Ltd.* for compliance with the requirements set forth in FCC rules and the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Tested by (+ signature):

Zhang Ling January. 06, 2012

July Wen

Review by (+ signature):

January. 06, 2012

Approved by (+ signature):

Terry Yang January. 06, 2012

2. GENERAL INFORMATION

2.1 Product Information

FCC ID: ZU3UNNECTOTAP

Description:	GSM MOBILE PHONE
Model Name:	U-500-2
Series Number:	N/A
Model Difference description:	N/A
Dower Cumply	DC 5V by AC/DC adapter 100~240V 50/60Hz
Power Supply:	DC 3.7V by Lithium-ion Battery
Frequency Range:	2412MHz – 2462MHz
Number of Channels:	IEEE 802.11b/g mode: 11 Channels
Madulation Taphaigue	IEEE 802.11b mode: DSSS (1, 2, 5.5 and 11 Mpbs)
Modulation Technique:	IEEE 802.11g mode: OFDM (6, 9, 12, 18, 24, 36, 48 and 54 Mpbs)
Antenna Gain:	0dBi
Temperature Range:	-20℃ ~ +50℃

NOTE:

1. For a more detailed features description about the EUT, please refer to User's Manual.

FCC ID: ZU3UNNECTOTAP

2.2 Objective

The objective of the report is to perform tests according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No.	Identity	Document Title	
1	47 CFR Part 15(10-1-05 Edition)	Radio Frequency Devices	

2.3 Test Standards and Results

Test items and the results are as bellow:

No.	Section	Description	Result	Date of Test
1	15.247(a)(2)	6dB Bandwidth	PASS	2012-01-05
2	15.247(b)(3)	Peak Output Power	PASS	2012-01-05
3	15.247(d)	conducted spurious emission	PASS	2012-01-05
4	15.247(d)	Band Edge	PASS	2012-01-05
5	15.247(e)	Power Spectral Density	PASS	2012-01-05
6	15.207	Conducted Emission	PASS	2011-12-22
7	15.247(d) 15.205 15.209	Radiated Emission	PASS	2011-12-22

Note:

- 1. The test result judgment is decided by the limit of measurement standard
- 2. The information of measurement uncertainty is available upon the customer's request.

2.4 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C - Humidity: 30-60 %

- Atmospheric pressure: 86-106 kPa

FCC ID: ZU3UNNECTOTAP Report No.: STS111224F2B

3. TEST FACILITY

Test Site: Compliance Certification Services Inc. (Kun shan) Laboratory

Location: No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City,

Jiangsu, China

Description: There is one 3m semi-anechoic an area test sites and two line conducted labs for final

test. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009 and CISPR

16 requirements.

The FCC Registration Number is 424105.

Site Filing: The site description is on file with the Federal Communications Commission, 7435

Oakland Mills Road, Columbia, MD 21046.

Instrument Tolerance: All measuring equipment is in accord with ANSI C63.4:2009 and CISPR 16

requirements that meet industry regulatory agency and accreditation agency

requirement.

Ground Plane: Two conductive reference ground planes were used during the Line Conducted

Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond

the periphery of the EUT and the largest measuring antenna, and covered the entire

area between the EUT and the antenna.

4. TEST EQUIPMENT LIST

Instrumentation: The following list contains equipment used at MOST for testing. The equipment conforms to the CISPR 16-1/ANSI C63.2 Specifications for Electromagnetic Interference and Field Strength Instrumentation from 10 kHz to 1.0 GHz or above.

110111	TO KHZ to 1.0 GHZ of above	∃ .			
No.	Equipment	Manufacturer	Model No.	S/N	Calibration due date
1	Test Receiver	Rohde & Schwarz	ESCI	100492	2012/03/14
2	Spectrum Analyzer	Agilent	E7405A	US44210471	2012/03/14
3	L.I.S.N.	Rohde & Schwarz	ENV216	100093	2012/03/14
4	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2012/03/14
5	Terminator	Hubersuhner	50Ω	No.1	2012/03/14
6	RF Cable	SchwarzBeck	N/A	No.1	2012/03/14
7	Test Receiver	Rohde & Schwarz	ESPI	101202	2012/03/14
8	Bilog Antenna	Sunol	JB3	A121206	2012/03/14
9	Horn Antenna	TRC	N/A	N/A	2012/03/14
10	Cable	Resenberger	N/A	NO.1	2012/03/14
11	Cable	SchwarzBeck	N/A	NO.2	2012/03/14
12	Cable	SchwarzBeck	N/A	NO.3	2012/03/14
13	DC Power Filter	DuoJi	DL2×30B	N/A	2012/03/14
14	Single Phase Power Line Filter	DuoJi	FNF 202B30	N/A	2012/03/14
15	3 Phase Power Line Filter	DuoJi	FNF 402B30	N/A	2012/03/14
16	Test Receiver	Rohde & Schwarz	ESCI	100492	2012/03/14
17	Absorbing Clamp	Luthi	MDS21	3635	2012/03/14
18	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2012/03/14
19	AC Power Source	Kikusui	AC40MA	LM003232	2012/03/14
20	Test Analyzer	Kikusui	KHA1000	LM003720	2012/03/14
21	Line Impendence Network	Kikusui	LIN40MA- PCR-L	LM002352	2012/03/14
22	ESD Tester	Kikusui	KES4021	LM003537	2012/03/14
23	EMCPRO System	EM Test	UCS-500-M4	V0648102026	2012/03/14
24	Signal Generator	IFR	2032	203002/100	2012/03/14
25	Amplifier	A&R	150W1000	301584	2012/03/14
26	CDN	FCC	FCC-801-M2-25	47	2012/03/14
27	CDN	FCC	FCC-801-M3-25	107	2012/03/14
28	EM Injection Clamp	FCC	F-203I-23mm	403	2012/03/14
29	RF Cable	MIYAZAKI	N/A	No.1/No.2	2012/03/14
30	Universal Radio Communication Tester	ROHDE&SCHWARZ	CMU200	0304789	2012/03/14
31	Telecommunication Antenna	European Antennas	PSA 75301R/170	0304213	2012/03/14

NOTE: Equipments listed above have been calibrated and are in the period of validation.

5. 47 CFR Part 15 C 15.247 Requirements

5.1 6dB Bandwidth

5.1.1 Definition

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.1.2 Test Description

The EUT is powered by the Battery, is coupled to the Spectrum Analyzer (SA) through the Attenuator/DC Block. The path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated and is set to operate at maximum power. The RF load attached to the EUT antenna terminal is 500hm.




Figure 1: RF Test Setup

5.1.3 Test Result

The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the Module.


5.1.3.1 802.11b Test Mode


The minimum occupied bandwidth for the fundamental frequency 2412MHz is 10.4MHz. This occupied bandwidth complies with the FCC requirement.

A. Test Verdict:


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	10.4	≥500	PASS
6	2437	10.4	≥500	PASS
11	2462	10.8	≥500	PASS

B. Test Plot:





(CH Mid)



(CH High)


5.1.3.2 802.11g Test Mode

The occupied bandwidth for the fundamental frequency 2412MHz is 16.6MHz. This occupied bandwidth complies with the FCC requirement.


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	16.6	≥500	PASS
6	2437	16.6	≥500	PASS
11	2462	16.6	≥500	PASS


B. Test Plot:



(CH Low)



(CH Mid)



(CH High)

5.2 Peak Output Power

5.2.1 Definition

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

5.2.2 Test Description

See section 5.1.2 of this report.

5.2.3 Test Result

The EUT operates at maximum output power mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.


5.2.3.1 802.11b Test Mode

The maximum output power for the fundamental frequency 2412MHz is 16.00dBm. This power complies with the FCC requirement.


A. Test Verdict:


Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
Charine	r requericy (ivil iz)	dBm	W	dBm	W	verdict
1	2412	16.00	0.040			PASS
6	2437	15.24	0.034	30	1	PASS
11	2462	15.23	0.033			PASS

B. Test Plot:



(CH Low)






5.2.3.2 802.11g Test Mode

The maximum output power for the fundamental frequency 2412 MHz is 15.18dBm. This power complies with the FCC requirement.


A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
Charmer	r requericy (ivil iz)	dBm	W	dBm	W	verdict
1	2412	15.18	0.033			PASS
6	2437	14.48	0.028	30	1	PASS
11	2462	14.49	0.028			PASS


B. Test Plot:



(CH Low)



(CH Mid)



5.3 Conducted Spurious Emission

5.3.1 Definition

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

5.3.2 Test Description


See section 5.1.2 of this report.

5.3.3 Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.


5.3.3.1 802.11b Test Mode

Test Plot:



(CH Low, 9kHz to 25GHz)

(CH Mid, 9kHz to 25GHz)




(CH High, 9kMHz to 25GHz)

Note:


1. The power of the Module transmitting frequency should be ignored.

5.3.3.2 802.11g Test Mode

Test Plot:



(CH Low, 9kHz to 25GHz)



(CH Mid, 9kHz to 25GHz)

(CH High, 9kHz to 25GHz)

Note:


1. The power of the Module transmitting frequency should be ignored.

5.4 Band Edge

5.4.1 Definition

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

5.4.2 Test Description




5.4.3 Test Result

The EUT operates at continuous transmit test mode. The lowest and highest channels are tested to verify the band edge emissions.


5.4.3.1 802.11b Test Mode

Test Mode				Test Result Highest Emission (dBuv/m)			
		Channel Marked Lii	Limit (dBuv/m)	Vertical		Horiz	zontal
		- 17		Peak	Average	Peak	Average
	Low	2390MHz	74(Peak)	58.83	38.19	58.81	37.62
WIFI	Channel	2400MHz		72.17	45.77	70.63	46.31
High Channel	2483.5MHz	54(Average)	59.43	45.43	60.13	46.24	
	Channel	2500MHz		60.12	37.29	59.10	38.56


Test Plot:




(CH Low, Vertical, Peak)



(CH Low, Horizontal, Peak)



(CH High, Vertical, Peak)




(CH High, Horizontal, Peak)


5.4.3.2 802.11g Test Mode

Test Mode				Test Result Highest Emission (dBuv/m)			
		Channel Marked Frequency	Limit (dBuv/m)	Vertical		Horizontal	
		2 12 27		Peak	Average	Peak	Average
	Low Channel	2390MHz	74(Peak)	61.54	39.45	61.50	38.92
WIFI		2400MHz		72.70	47.15	70.52	48.63
High Channel	2483.5MHz	54(Average)	61.78	43.24	65.06	42.17	
	Channel	2500MHz	2500MHz		37.57	60.13	37.42


Test Plot:




(CH Low, Vertical, Peak)



(CH Low, Horizontal, Peak)



(CH High, Vertical, Peak)



(CH High, Horizontal, Peak)

5.5 Power Spectral Density (PSD)

5.5.1 Definition

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.5.2 Test Description

See section 5.1.2 of this report.

5.5.3 Test Result


The lowest, middle and highest channels are tested to verify the power spectral density.

5.5.3.1 802.11b Test Mode


A. Test Verdict:

Channel	Frequency (MHz)	PSD (dBm)	Limits(dBm)	Result
1	2412	-4.114	≤8	PASS
6	2437	-4.440	≤8	PASS
11	2462	-5.674	≤8	PASS


B. Test Plot:



(CH Low)



(CH Mid)



(CH High)


FCC ID: ZU3UNNECTOTAP Report No.: STS111224F2B

5.5.3.2 802.11g Test Mode


A. Test Verdict:

Channel	Frequency (MHz)	PSD (dBm)	Limits(dBm)	Result
1	2412	-6.803	≤8	PASS
6	2437	-6.678	≤8	PASS
11	2462	-6.680	≤8	PASS


B. Test Plot:



(CH Low)



(CH Mid)



(CH High)

5.6 Conducted Emission

5.6.1 Definition

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 µH/50 ohms line impedance stabilization network (LISN).


Frequency	Maximum RF Line Voltage					
Frequency	Q.P.(dBuV)	Average(dBuV)				
150kHz-500kHz	66-56	56-46				
500kHz-5MHz	56	46				
5MHz-30MHz	60	50				

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz


5.6.2 Test Description

The EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated and is set to operate at maximum power.



5.6.3 Test Result

A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.



Limit: FCC Part15 B Class B QP

EUT: GSM MOBILE PHONE

M/N: U-500-2 Mode: WIFI Note:

No. N	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHZ	dBuV	dB	dBuV	dBuV	₫B	Detector	Comment
1		0.1780	39.98	0.00	39.98	64.58	-24.60	peak	
2 *	*	0.3620	36.34	0.00	36.34	58.68	-22.34	peak	
3		1.0940	33.19	0.00	33,19	56.00	-22.81	peak	
4		1.8900	32.34	0.00	32.34	58.00	-23,66	peak	
5		5.1540	30.59	0.00	30.59	60.00	-29.41	peak	

^{*:}Maximum data x:Over limit 1:over margin

Site site #1

Limit: FCC Part15 B Class B QP

EUT: GSM MOBILE PHONE

M/N: U-500-2 Mode: WIFI Note:

No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1700	38.20	0.00	38.20	64.96	-26.76	peak	
2 ×	0.9820	32.82	0.00	32.82	56.00	-23.18	peak	
3	1.8580	29.50	0.00	29.50	56.00	-26.50	peak	
4	4.9580	27.05	0.00	27.05	56.00	-28.95	peak	
5	10.6260	27.91	0.00	27.91	60.00	-32.09	peak	

Phase:

Power: AC 120V/60Hz

Report No.: STS111224F2B

Temperature: 26

Humidity: 60 %

^{*:}Maximum data x:Over limit !:over margin

FCC ID: ZU3UNNECTOTAP Report No.: STS111224F2B

5.7 Radiated Emission

5.7.1 Definition

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).


According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

5.7.2 Test Description


A. Test Setup:



Blow 1GHz:



Above 1GHz:



B. Test procedures

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Set the spectrum analyzer in the following setting as:

Below 1GHz: RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz: (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO

7. Repeat above procedures until the measurements for all frequencies are complete.

5.7.3 Test Result

5.7.3.1 Below 1 GHz

Operation Mode: Normal Link(WIFI) Test Date: December. 22, 2011

Temperature: 20°C **Tested by:** Hbby Guo

Humidity: 70 % RH **Polarity:** Ver. / Hor.


Form 9 KHz to 30MHz:

Frequency (MHz)	Ant.Pol H/V	Peak Reading	AV Reading	Ant./CL CF	Actu	al Fs	Peak Limit	AV Limit	AV Margin
(11.12)	7 17 4	(dBuv)		(dB)	Peak (dBuv/m)	AV (dBuv/m)	(dBuv/m)	(dBuv/m)	(dB)
Н					,	,			>20
V									>20

⁻Note: No test data was detected in below 30MHz.

Humidity: 61 %

Form 30 MHz to 1GHz:



Power: AC 120V/60Hz

Distance:


Limit: FCC Part15 B 3M Radiation

EUT: GSM MOBILE PHONE

M/N: U-500-2 Mode: WIFI Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height		
		MHz	dBuV	dΒ	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	į	31.9400	12.43	23.31	35.74	40.00	-4.26	peak			
2	×	80.4400	24.71	11.39	36.10	40.00	-3.90	peak			
3		196.8400	15.92	17.05	32.97	43.50	-10.53	peak			
4	(370.2000	4.71	24.50	29.21	46.00	-16.79	peak			
- 5	(n4 04nn	5.13	27.50	32.63	48.00	-13 37	neak			

^{*:}Maximum data x:Over limit !:over margin



Limit: FCC Part15 B 3M Radiation

EUT: GSM MOBILE PHONE

M/N: U-500-2 Mode: WIFI Note: Power: AC 120V/60Hz

	numinity.
Distance	

Report No.: STS111224F2B

61 %

No.	Mk.	. Fre		Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height		
		MH	z	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	108.57	00	18.36	15.69	34.05	43.50	-9.45	peak			
2		205.57	00	16.13	17.01	33.14	43.50	-10.36	peak			
3		245.34	00	14.49	17.40	31.89	46.00	-14.11	peak			
4		778.84	00	4.99	26.17	31.16	46.00	-14.84	peak			
5		916.58	00	4.44	27.70	32.14	46.00	-13.86	peak			

- 1. Measuring frequencies from 30 MHz to the 1GHz.
- 2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.
- 3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
- 4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 5. Margin (dB) = Result (dBuV/m) Limit (dBuV/m).

^{*:}Maximum data x:Over limit !:over margin

Above 1 GHz

Operation Mode: TX/ IEEE 802.11b/CH Low Test Date: December .22, 2011

Temperature: 20°C Tested by: Habby Guo

Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actu	al Ec	Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF	Actu	airs	Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
4824.5	V	43.68	24.31	23.16	66.84	47.47	74.00	54.00	-6.53
N/A	V								
4824.5	Н	44.82	23.60	23.05	67.87	46.65	74.00	54.00	-7.35
N/A	Н								
					·				

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).

Operation Mode: TX/ IEEE 802.11b/CH Mid Test Date: December. 22, 2011

Temperature:20°CTested by:Habby GuoHumidity:70 % RHPolarity:Ver. / Hor.

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actu	al Ec	Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF	Actu	airs	Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
4874.5	V	44.92	24.85	23.31	68.23	48.16	74.00	54.00	-5.84
N/A	V								
4874.5	Н	45.30	25.19	23.31	68.61	48.50	74.00	54.00	-5.50
N/A	Н								
									·
									·

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).

Operation Mode: TX/ IEEE 802.11b/CH High Test Date: December. 22, 2011

Temperature:20°CTested by:Habby GuoHumidity:70 % RHPolarity:Ver. / Hor.

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Antii	al Fs	Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF	Actu	ai rs	Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
4924.5	V	46.40	25.72	23.16	69.56	48.88	74.00	54.00	-5.12
N/A	V								
4924.5	Н	45.71	24.64	23.05	68.76	47.69	74.00	54.00	-6.31
N/A	Н								

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).

Operation Mode: TX/ IEEE 802.11g/CH Low Test Date: December. 22, 2011

Temperature: 20°C Tested by: Habby Guo

Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actu	al Ec	Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF	Actu	airs	Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
4824.5	٧	44.92	24.84	23.16	68.08	48.00	74.00	54.00	-6.00
N/A	V								
4824.5	Н	43.76	25.47	23.05	66.81	48.52	74.00	54.00	-5.48
N/A	Н								

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).

Operation Mode: TX/ IEEE 802.11g/CH Mid Test Date: December. 22, 2011

Temperature: 20°C **Tested by:** Habby Guo

Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actu	al Ec	Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF	Actu	airs	Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
4874.5	V	45.27	25.64	23.31	68.58	48.95	74.00	54.00	-5.05
N/A	V								
4874.5	Н	44.34	24.12	23.31	67.65	47.43	74.00	54.00	-6.57
N/A	Н								
							·		·

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).

Operation Mode: TX/ IEEE 802.11g/CH High Test Date: December. 22, 2011

Temperature:20°CTested by:Habby GuoHumidity:70 % RHPolarity:Ver. / Hor.

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actu	al Ec	Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF	Actu	airs	Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
4924.5	V	45.07	24.96	23.16	68.23	48.12	74.00	54.00	-5.88
N/A	V								
	•	•	•	•					
4924.5	Н	44.36	24.19	23.05	67.41	47.24	74.00	54.00	-6.76
N/A	Н								
	i								


- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).


APPENDIX 1 PHOTOGRAPHS OF TEST SETUP

CE TEST SETUP



RE TEST SETUP





CONDUCTED SPURIOUS EMISSION TEST SETUP



APPENDIX 2 PHOTOGRAPHS OF EUT

FCC ID: ZU3UNNECTOTAP

FRONT VIEW OF SAMPLE



BACK VIEW OF SAMPLE



LEFT VIEW OF SAMPLE



RIGHT VIEW OF SAMPLE



TOP VIEW OF SAMPLE



BOTTOM VIEW OF SAMPLE



PHOTO OF USB LINE



PHOTO OF EARPHONE



PHOTO OF POWER SUPPLY



PHOTO OF BATTERY



PHOTO OF THE ENTIRE SAMPLE




INTERNAL PHOTO OF SAMPLE - 1






INTERNAL PHOTO OF SAMPLE -3







INTERNAL PHOTO OF SAMPLE -5







INTERNAL PHOTO OF SAMPLE -7






INTERNAL PHOTO OF SAMPLE -9






INTERNAL PHOTO OF POWER SUPPLY-1



INTERNAL PHOTO OF POWER SUPPLY-2



-----END OF REPORT-----