

Test report No: 4395567.59

TEST REPORT

Radio Spectrum Matters (RF)

Identification of item tested	C-shape couples' vibrator
Trademark	We-Vibe Sync Lite
Model and /or type reference	SCL2A
FCC ID	ZUESCL2A
Features	5 Vdc, 0,5 A
Applicant's name / address	WOW Tech Canada Ltd., 1545 Carling Avenue, Suite 401. Ottawa, Ontario, K1Z 8P9, Canada
Test method requested, standard	KDB 447498 D01V06 FCC Part 1.1310
Verdict Summary	COMPLIANCE
Tested by (name & signature)	Harry Deng 
Approved by (name & signature)	Tim Yan 
Date of issue	2022-11-23
Report template No	TRF_EMC 2017-06- FCC_Exposure

INDEX

	page
General conditions	3
Uncertainty	3
Environmental conditions	3
Possible test case verdicts	3
Definition of symbols used in this test report	4
Abbreviations	4
Document History	4
Remarks and Comments	4
1 General Information	5
1.1 General Description of the Item(s)	5
1.2 Test data	6
1.3 The environment(s) in which the EUT is intended to be used	6
2 Description of Test Setup	7
2.1 Operating mode(s) used for tests	7
2.2 Support / Auxiliary equipment / unit / software for the EUT	7
2.3 Test Configuration / Block diagram used for tests	7
3 RF Exposure Evaluation	8
3.1 Limits	8
3.2 Test Procedure	9
3.3 Test Result	9

GENERAL CONDITIONS

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.
5. This report will not be used for social proof function in China market.

UNCERTAINTY

For all measurements where guidance for the calculation of the instrumentation uncertainty of a measurement is specified in EN 55016-4-2 (CISPR 16-4-2), EN/IEC 61000-4 series or a product standard, the measurement instrumentation uncertainty has been calculated and applied in accordance with these standards.

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%
Atmospheric pressure	86 kPa – 106 kPa

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

DEFINITION OF SYMBOLS USED IN THIS TEST REPORT

☒ Indicates that the listed condition, standard or equipment is applicable for this report/test/EUT.			
☐ Indicates that the listed condition, standard or equipment is not applicable for this report/test/EUT.			
Decimal separator used in this report	☒	Comma (,)	☐ Point (.)

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
Tx	: Transmitter
Rx	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report nr.	Date	Description
4395567.59	2022-11-23	First release.

REMARKS AND COMMENTS

The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

Description of the item	C-shape couples' vibrator
Trademark.....	We-Vibe Sync Lite
Model / Type number	SCL2A
FCC ID	ZUESCL2A
Ratings	5 Vdc, 0,5 A
Manufacturer	WOW Tech Europe GmbH Hermann-Blankenstein-Str. 5, 10249 Berlin, Germany
Factory	WOW Tech (Shanghai) Co., Ltd. Building 14 & Building 19, No.3398 Puwei Road, Fengxian District, Shanghai,P.R. China

Operating frequency range(s) – Tx.:	2402-2480 MHz
Operating frequency range(s) – Rx :	2402-2480 MHz
Maximum RF output power (conducted)	-6,9 dBm
E.I.R.P.	-1,9 dBm
Type of Modulation	GFSK
PHYs	LE 1M, LE 2M
Data Rate	1 Mbit/s, 2 Mbit/s
Antenna type.....	Integral Antenna
Antenna gain.....	5,0 dBi
Number of channel	40
Operating Temperature Range.....	-20 – 45 °C

Rated power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	☐	AC: 220 – 240 V, 50/60 Hz	☐	☐	☐	☐	☐
	☒	DC: 5 V					
	☐	Battery: 3 V					
Mounting position.....	☐	Table top equipment					
	☐	Wall/Ceiling mounted equipment					
	☐	Floor standing equipment					
	☒	Hand-held equipment					
	☐	Other:					

Intended use of the Equipment Under Test (EUT)
The apparatus as supplied for the test is C-shape couples' vibrator which intended for residential use, the product contains electronic control circuitry.

Copy of marking plate:
No provide.

1.2 Test data

Test Location	DEKRA Testing and Certification (Shanghai) Ltd. Guangzhou Branch Block 5, No.3, Qiyun Road, Huangpu District, Guangzhou, Guangdong, China FCC Designation Number: CN1324; ISED CAB identifier: CN0130
Date of receipt of test item	2022-10-13
Date (s) of performance of tests	2022-10-13 to 2022-11-18

1.3 The environment(s) in which the EUT is intended to be used

The equipment under test (EUT) is intended to be used in the following environment(s):

☒	Residential (domestic) environment.
☒	Commercial and light-industrial environment.
☐	Industrial environment.

2 DESCRIPTION OF TEST SETUP

2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.

Operating mode	Operating mode description	Used for methos	
		Conducted	Radiated
1	Transmitting at 1 Mbit/s,	☒	☐
2	Transmitting at 2 Mbit/s,	☒	☐
3		☐	☐
Supplemental information: ---			

2.2 Support / Auxiliary equipment / unit / software for the EUT

The EUT has been tested with the following auxiliary equipment / unit / software:

Auxiliary equipment / unit / software	Type / Version	Manufacturer	Supplied by
---	---	---	---
Supplemental information: ---			

2.3 Test Configuration / Block diagram used for tests

Refer to Annex 3.

3 RF EXPOSURE EVALUATION

3.1 Limits

According to KDB 447498 D01 General RF Exposure Guidance v06: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in section 4.3.1 & Appendix A.

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Appendix A

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	<i>SAR Test Exclusion Threshold (mW)</i>
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
MHz	30	35	40	45	50	mm
150	232	271	310	349	387	<i>SAR Test Exclusion Threshold (mW)</i>
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

Note: 10-g Extremity SAR Test Exclusion Power Thresholds are 2.5 times higher than the 1-g *SAR Test Exclusion Thresholds* indicated above. These thresholds do not apply, by extrapolation or other means, to occupational exposure limits.

3.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 23°C and 50% RH.

3.3 Test Result

Test Mode	Frequency Band (MHz)	Conducted RF Power Output (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	Maximum Power (mW)	Limit of Power (mW)
BLE	2400 ~ 2483.5	-6,9	5	-1,9	0,64	10

Remark:

The test separation distances at <5mm.

--- END ---