FCC 47 CFR PART 15 SUBPART C

Report No.: C180314Z05-RP1

for

Beacon

Model: EXTx Air

Brand: WHERE

Test Report Number: C180314Z05-RP1

Issued for

TCL Technoly Electronics (Huizhou) Co., Ltd.
Section 37, Zhongkai High-tech development Zone Huizhou City
Guangdong Province China 516006.

Issued by:

Compliance Certification Services (Shenzhen) Inc.

No.10-1, Mingkeda Logistics Park, No.18 Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China

> TEL: 86-755-28055000 FAX: 86-755-28055221 E-Mail: service@ccssz.com

Issued Date: April 8, 2018



Certificate Number: 2861.01

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services (Shenzhen) Inc. This document may be altered or revised by Compliance Certification Services (Shenzhen) Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST, CNAS or any government agencies. The test results in the report only apply to the tested sample.

FCC ID: ZVAOH000022

Page 1 / 47

This report shall not be reproduced execut in full without the written expressed of Compliance Continues (Shorphan) In

Revision History

Report No.: C180314Z05-RP1

Rev.	Issue Data	Revisions	Effect Page	Revised By
00	April 8, 2018	Initial Issue	ALL	Anna Liu

FCC ID: ZVAOH000022 Page 2 / 47

TABLE OF CONTENTS

Report No.: C180314Z05-RP1

1 T	EST CERTIFICATION	. 4
2 T	EST RESULT SUMMARY	. 5
	UT DESCRIPTION	
	EST METHODOLOGY	
4.1.	DESCRIPTION OF TEST MODES	7
	ETUP OF EQUIPMENT UNDER TEST	
	DESCRIPTION OF SUPPORT UNITS	
	CONFIGURATION OF SYSTEM UNDER TEST	
6 F	ACILITIES AND ACCREDITATIONS	. 9
6.1.	FACILITIES	9
6.2.	ACCREDITATIONS	.9
6.3.	MEASUREMENT UNCERTAINTY	10
7 F	CC PART 15.247 REQUIREMENTS1	11
7.1.	POWER LINE CONDUCTED EMISSIONS MEASUREMENT	11
	SPURIOUS EMISSIONS MEASUREMENT	
	6dB BANDWIDTH MEASUREMENT	
	ANTENNA GAIN	
	PEAK OUTPUT POWER	
7.6.	BAND EDGES MEASUREMENT	38
7.7.	PEAK POWER SPECTRAL DENSITY MEASUREMENT	44

1 TEST CERTIFICATION

Product	Beacon
Model	EXTx Air
Brand	WHERE
Tested	February 22~April 8, 2018
Applicant	TCL Technoly Electronics (Huizhou) Co., Ltd. Section 37, Zhongkai High-tech development Zone Huizhou City Guangdong Province China 516006.
Manufacturer	TCL Technoly Electronics (Huizhou) Co., Ltd. Section 37, Zhongkai High-tech development Zone Huizhou City Guangdong Province China 516006.

APPLICABLE STANDARDS							
Standard	Test Type	Standard	Test Type				
15.207(a)	Power Line Conducted Emissions	15.247(d) 15.209(a)	Spurious EmissionsConducted MeasurementRadiated Emissions				
15.247(a)(2)	6dB Bandwidth Measurement	15.247(b)(3) 15.247(b)(4)	Peak Power Measurement				
15.247(d)	Band Edges Measurement	15.247(e)	Peak Power Spectral Density				

We hereby certify that:

The above equipment was tested by Compliance Certification Services (Shenzhen) Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.10: 2013** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Reviewed by:

Eve Wang

Supervisor of EMC Dept.

Compliance Certification Services (Shenzhen) Inc.

Nancy Fu

Supervisor of Report Dept.

Compliance Certification Services (Shenzhen) Inc.

Report No.: C180314Z05-RP1

FCC ID: ZVAOH000022 Page 4 / 47

2 TEST RESULT SUMMARY

	APPLICABLE STANDARDS						
Standard Test Type		Result	Remark				
15.247(a)(2)	6dB Bandwidth Measurement	Pass	Meet the requirement of limit.				
15.247(b)(3) 15.247(b)(4)	Peak Power Measurement	Pass	Meet the requirement of limit.				
15.247(d)	Band Edges Measurement	Pass	Meet the requirement of limit.				
15.247(e)	Peak Power Spectral Density	Pass	Meet the requirement of limit.				
15.247(d) 15.209(a)	Spurious EmissionsConducted MeasurementRadiated Emissions	Pass	Meet the requirement of limit.				
15.207(a)	Power line Conducted Emissions	N/A	Not applicable, since the EUT powered by the DC Power				

Report No.: C180314Z05-RP1

Note: 1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.

^{2.} The information of measurement uncertainty is available upon the customer's request.

EUT DESCRIPTION

Product	Beacon
Model	EXTx Air
Brand	WHERE
Model Discrepancy	N/A
Identify Number	C180314Z05-RP1
Received Date	February 22, 2018
Power Supply	DC 3.75V from battery(100mAh)
Frequency Range	2402MHz ~2480MHz
Transmit Power	-0.02dBm
Modulation Technique	GFSK for 1Mbps
Number of Channels	40 Channels
Antenna Specification	PCB Antenna with 3.57dBi gain (Max)
Temperature Range	-10°C ~+60 °C
Hardware Version	40-WEXBCD-MAB2G
Software Version	V1.0

Report No.: C180314Z05-RP1

FCC ID: ZVAOH000022 Page 6 / 47 This report shall not be reproduced except in full, without the written approval of Compliance Certification Services (Shenzhen) Inc.

Note: 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

^{2.} This submittal(s) (test report) is intended for FCC ID: ZVAOH000022 filing to comply with Section 15.207, 15.209 and 15.247of the FCC Part 15, Subpart C Rules.

4 TEST METHODOLOGY

4.1. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Use Certification Tool 1.26 to control the EUT for staying in continuous transmitting and receiving mode.

Report No.: C180314Z05-RP1

Test Item	Test mode	Worse mode
Conducted Emission	Not applicable, since the EUT powered by the DC Power.	
Radiated Emission	Mode 4: Continuously Transmitting	

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.

BT4.0 mode: Channel Low (2402MHz), Channel Mid (2440MHz) and Channel High (2480MHz) with 1Mbps data rate were chosen for full testing.

FCC ID: ZVAOH000022 Page 7 / 47

5 SETUP OF EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Report No.: C180314Z05-RP1

No	. Equipment	Model No.	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1	Notebook	TIANYI 310	MP18DLC6	DoC	LENOVO	N/A	N/A

Note:

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

5.2. CONFIGURATION OF SYSTEM UNDER TEST

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

FCC ID: ZVAOH000022 Page 8 / 47

6 FACILITIES AND ACCREDITATIONS

6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at No. 10-1, Mingkeda Logistics Park, No.18 Huanguan South RD. Guan Lan Town, Baoan District, Shenzhen China

The sites are constructed in conformance with the requirements of ANSI C63.10, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

Report No.: C180314Z05-RP1

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

USA A2LA China CNAS

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

USA FCC

Japan VCCI(C-4815, R-4320, T-2317, G-10624)

Canada INDUSTRY CANADA

Copies of granted accreditation certificates are available for downloading from our web site, http://www.ccssz.com

FCC ID: ZVAOH000022 Page 9 / 47

6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Report No.: C180314Z05-RP1

Parameter	Uncertainty
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.6880dB
Radiated Emission, 200 to 1000 MHz Test Site : 966(2)	+/-3.6695dB
Radiated Emission, 1 to 8 GHz	+/-5.1782dB
Radiated Emission, 8 to 18 GHz	+/-5.2173dB
Conducted Emissions	+/-3.6836dB
Band Width	178kHz
Peak Output Power MU	+/-1.906dB
Band Edge MU	+/-0.182dB
Channel Separation MU	416.178Hz
Duty Cycle MU	0.054ms
Frequency Stability MU	226Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.

FCC ID: ZVAOH000022 Page 10 / 47

7 FCC PART 15.247 REQUIREMENTS

7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT

7.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Report No.: C180314Z05-RP1

Frequency Range		nits μV)
(MHz)	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

NOTE:

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

7.1.2. TEST INSTRUMENTS

Conducted Emission Test Site									
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration				
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	01/27/2018	01/26/2019				
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	01/27/2018	01/26/2019				
LISN	EMCO	3825/2	8901-1459	01/27/2018	01/26/2019				
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	01/29/2018	01/28/2019				
Test S/W	FARAD		EZ-EMC/ CCS-3A	1-CE					

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. N.C.R = No Calibration Request.

FCC ID: ZVAOH000022 Page 11 / 47

7.1.3. TEST PROCEDURES (please refer to measurement standard)


• The EUT and Support equipment, if needed, was placed on a non-conducted table, which is 0.8m above the ground plane and 0.4m away from the conducted wall.

Report No.: C180314Z05-RP1

- The test equipment EUT installed received AC main power, through a Line Impedance Stabilization Network (LISN), which supplied power source and was grounded to the ground plane. All support equipment power received from a second LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The frequency range from 150 kHz to 30 MHz was searched. The test data of the worst-case condition(s) was recorded. Emission levels under limit 20dB were not recorded.

FCC ID: ZVAOH000022 Page 12 / 47

7.1.4. TEST SETUP



Report No.: C180314Z05-RP1

For the actual test configuration, please refer to the related item - Photographs of the Test Configuration.

7.1.5. DATA SAMPLE

Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)		QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Margin	Remark (Pass/Fail)
x.xxxx	34.99	19.33	10.15	45.14	29.48	65.99	56.00	-20.85	-26.52	Pass

Factor = Insertion loss of LISN + Cable Loss

Result = Quasi-peak Reading/ Average Reading + Factor

Limit = Limit stated in standard Margin = Result (dBuV) – Limit (dBuV)

7.1.6. TEST RESULTS

Not applicable, since the EUT powered by the DC Power.

FCC ID: ZVAOH000022 Page 13 / 47

7.2. SPURIOUS EMISSIONS MEASUREMENT

7.2.1. CONDUCTED EMISSIONS MEASUREMENT

7.2.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Report No.: C180314Z05-RP1

7.2.1.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY55370330	01/27/2018	01/26/2019

7.2.1.3. TEST PROCEDURE (please refer to measurement standard)


Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site. The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

Measurements are made over the 9kHz to 26.5GHz range with the transmitter set to the lowest, middle, and highest channels. No emission found between lowest internal used/generated frequency to 10MHz, it is only recorded 10MHz to 26GHz.

FCC ID: ZVAOH000022 Page 14 / 47


7.2.1.4. TEST RESULTS

Test Plot




FCC ID: ZVAOH000022 Page 15 / 47

-2.416 dBm -59.897 dBm



FCC ID: ZVAOH000022 Page 16 / 47



FCC ID: ZVAOH000022 Page 17 / 47

7.2.2. RADIATED EMISSIONS MEASUREMENT

7.2.2.1. LIMITS OF RADIATED EMISSIONS MEASUREMENT

According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Report No.: C180314Z05-RP1

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

1. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (µV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

NOTE: (1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).

FCC ID: ZVAOH000022 Page 18 / 47

7.2.2.2. TEST INSTRUMENTS

	Radiated Emission Test Site 966(2)										
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration						
PSA Series Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019						
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	01/27/2018	01/26/2019						
Amplifier	EMEC	EM330	060661	01/27/2018	01/26/2019						
High Noise Amplifier	Agilent	8449B	3008A01838	01/27/2018	01/26/2019						
Loop Antenna	COM-POWER	AL-130	121044	09/25/2017	09/24/2018						
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/21/2018	02/20/2019						
Horn Antenna	SCHWARZBECK	BBHA9120	D286	01/27/2018	01/26/2019						
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	01/24/2018	01/23/2019						
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R						
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R						
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R						
Controller	СТ	N/A	N/A	N.C.R	N.C.R						
Temp. / Humidity Meter	Anymetre	JR913	N/A	01/29/2018	01/28/2019						
Test S/W	FARAD		LZ-RF / CCS	S-SZ-3A2	_						

Report No.: C180314Z05-RP1

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The FCC Site Registration number is 101879.
- 3. N.C.R = No Calibration Required.

FCC ID: ZVAOH000022 Page 19 / 47

7.2.2.3. Measuring Instruments and Setting

The following table is the setting of spectrum analyzer and receiver.

The following table is the setting of spectrum analyzer and receiver.					
Spectrum Parameter	Setting				
Attenuation	Auto				
Start Frequency	1000 MHz				
Stop Frequency	10th carrier harmonic				
RB / VB (Emission in restricted	1MHz / 1MHz for Peak, 1 MHz /1/T for				
band)	Average				
RB / VB (Emission in non-restricted	1MHz / 1MHz for Peak, 1 MHz / 1/T for				
band)	Average				

Report No.: C180314Z05-RP1

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

7.2.2.4. TEST PROCEDURE (please refer to measurement standard)

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- --- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- --- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- --- If the EUT is a floor standing device, it is placed on the ground.
- --- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- --- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- --- The measurement distance is 3 meter.
- --- The EUT was set into operation.

Pre measurement:

- --- The turntable rotates from 0° to 315° using 45° steps.
- --- The antenna height is 0.8 meter.
- --- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

FCC ID: ZVAOH000022 Page 20 / 47

Final measurement:

- --- Identified emissions during the pre measurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- --- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

Report No.: C180314Z05-RP1

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

- --- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- --- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- --- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- --- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- --- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- --- The measurement distance is 3 meter.
- --- The EUT was set into operation.

Pre measurement:

- --- The turntable rotates from 0° to 315° using 45° steps.
- --- The antenna is polarized vertical and horizontal.
- --- The antenna height changes from 1 to 3 meter.
- --- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

FCC ID: ZVAOH000022 Page 21 / 47

Final measurement:

- --- The final measurement will be performed with minimum the six highest peaks.
- --- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter.

Report No.: C180314Z05-RP1

- --- The final measurement will be done with QP detector with an EMI receiver.
- --- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

- --- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- --- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- --- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- --- Auxiliary equipment and cables were positioned to simulate normal operation
- --- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- --- The measurement distance is 3 meter.
- --- The EUT was set into operation.

Pre measurement:

- --- The turntable rotates from 0° to 315° using 45° steps.
- --- The antenna is polarized vertical and horizontal.
- --- The antenna height scan range is 1 meter to 2.5 meter.
- --- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

FCC ID: ZVAOH000022 Page 22 / 47

Final measurement:

- --- The final measurement will be performed with minimum the six highest peaks.
- --- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.

Report No.: C180314Z05-RP1

- --- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- --- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz Setup:

- --- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- --- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- --- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- --- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- --- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- --- The measurement distance is 1 meter.
- --- The EUT was set into operation.

Pre measurement:

--- The antenna is moved spherical over the EUT in different polarisations of the antenna.


Final measurement:

- --- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- --- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.


FCC ID: ZVAOH000022 Page 23 / 47

7.2.2.5. TEST SETUP

Below 30MHz




Below 1 GHz



FCC ID: ZVAOH000022 Page 24 / 47

Above 1 GHz



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

FCC ID: ZVAOH000022 Page 25 / 47

7.2.2.6. DATA SAMPLE

Below 1GHz

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXX.XXXX	53.41	-18.63	34.78	43.50	-8.72	V	QP

Report No.: C180314Z05-RP1

Frequency (MHz) = Emission frequency in MHz

Reading (dBuV) = Uncorrected Analyzer / Receiver reading
Correct Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain
Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)

Limit (dBuV/m) = Limit stated in standard

Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)

Q.P. = Quasi-peak Reading

Above 1GHz

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXXX.XXXX	62.09	-11.42	50.67	74.00	-23.33	V	Peak
XXXX.XXXX	49.78	-11.42	38.36	54.00	-15.64	V	AVG

Frequency (MHz) = Emission frequency in MHz

Reading (dBuV) = Uncorrected Analyzer / Receiver reading Correction Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)

Limit (dBuV/m) = Limit stated in standard

Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)

Peak = Peak Reading AVG = Average Reading

Calculation Formula

Margin (dB) = Result (dBuV/m) – Limits (dBuV/m) Result (dBuV/m) = Reading (dBuV) + Correction Factor

FCC ID: ZVAOH000022 Page 26 / 47

7.2.2.7. TEST RESULTS

Below 1 GHz

Test Mode: TX / GFSK(CH Low) Tested by: Leon Yuan

Report No.: C180314Z05-RP1

Ambient temperature: 24°C Relative humidity: 52% RH Date: February 22, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
55.2200	46.74	-22.75	23.99	40.00	-16.01	V	QP
181.3200	39.58	-22.94	16.64	43.50	-26.86	V	QP
219.1500	38.07	-20.45	17.62	46.00	-28.38	V	QP
261.8300	40.70	-20.02	20.68	46.00	-25.32	V	QP
598.4200	34.97	-12.90	22.07	46.00	-23.93	V	QP
735.1900	32.02	-11.47	20.55	46.00	-25.45	V	QP
68.8000	47.84	-25.49	22.35	40.00	-17.65	Н	QP
187.1400	51.15	-22.89	28.26	43.50	-15.24	Н	QP
199.7500	49.63	-22.73	26.90	43.50	-16.60	Н	QP
208.4800	49.62	-21.70	27.92	43.50	-15.58	Н	QP
266.6800	43.79	-20.30	23.49	46.00	-22.51	Н	QP
615.8800	34.81	-12.80	22.01	46.00	-23.99	Н	QP

^{**}Remark: 1. No emission found between lowest internal used/generated frequency to 30MHz.

Notes:

- 1. Radiated emissions measured in frequency range from 9 kHz to 1GHz were made with an instrument using Quasi-peak detector mode.
- 2. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3. The IF bandwidth of Receiver between 30MHz to 1GHz was 120 kHz.

4. Frequency (MHz). = Emission frequency in MHz

Reading $(dB\mu V/m)$ = Receiver reading

Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain

Limit ($dB\mu V/m$) = Limit stated in standard


Margin (dB) = Measured (dB μ V/m) – Limits (dB μ V/m)

Antenna Pol e(H/V) = Current carrying line of reading


FCC ID: ZVAOH000022 Page 27 / 47

^{2.} Pre-scan all modes and recorded the worst case results in this report (BT LE (Low Channel)

Vertical



Horizontal



FCC ID: ZVAOH000022 Page 28 / 47

Above 1 GHz

Test Mode: GFSK (CH Low) Tested by: Leon Yuan

Ambient temperature: 24°C Relative humidity: 52% RH Date: February 22, 2018

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1711.000	47.22	-6.46	40.76	74.00	-33.24	V	peak
1900.000	48.83	-5.63	43.20	74.00	-30.80	V	peak
2242.000	46.33	-3.67	42.66	74.00	-31.34	V	peak
2638.000	44.59	-2.01	42.58	74.00	-31.42	V	peak
3079.000	43.88	-1.23	42.65	74.00	-31.35	V	peak
5032.000	42.11	5.04	47.15	74.00	-26.85	V	peak
1324.000	46.73	-7.34	39.39	74.00	-34.61	Н	peak
2134.000	45.45	-4.27	41.18	74.00	-32.82	Н	peak
2647.000	44.55	-2.00	42.55	74.00	-31.45	Н	peak
2809.000	44.23	-1.70	42.53	74.00	-31.47	Н	peak
4969.000	41.79	4.88	46.67	74.00	-27.33	Н	peak
5338.000	42.13	5.58	47.71	74.00	-26.29	Н	peak

REMARKS:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).

FCC ID: ZVAOH000022 Page 29 / 47

Test Mode: GFSK (CH Mid) Tested by: Leon Yuan

Ambient temperature: 24°C Relative humidity: 52% RH Date: February 22, 2018

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1792.000	49.59	-6.29	43.30	74.00	-30.70	V	peak
1900.000	48.51	-5.63	42.88	74.00	-31.12	V	peak
2188.000	45.52	-3.97	41.55	74.00	-32.45	V	peak
2647.000	44.79	-2.00	42.79	74.00	-31.21	V	peak
2827.000	43.41	-1.67	41.74	74.00	-32.26	V	peak
5176.000	41.87	5.29	47.16	74.00	-26.84	V	peak
1351.000	48.13	-7.24	40.89	74.00	-33.11	Н	peak
2125.000	46.01	-4.31	41.70	74.00	-32.30	Н	peak
2530.000	46.46	-2.21	44.25	74.00	-29.75	Н	peak
2800.000	43.45	-1.72	41.73	74.00	-32.27	Н	peak
3097.000	43.25	-1.20	42.05	74.00	-31.95	Н	peak
3799.000	41.81	0.74	42.55	74.00	-31.45	Н	peak

REMARKS:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).

FCC ID: ZVAOH000022 Page 30 / 47

Test Mode: GFSK (CH High)

Tested by: Leon Yuan

Report No.: C180314Z05-RP1

Ambient temperature: 24°C Relative humidity: 52% RH Date: February 22, 2018

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1603.000	51.14	-6.69	44.45	74.00	-29.55	V	peak
1738.000	51.36	-6.40	44.96	74.00	-29.04	٧	peak
1999.000	47.34	-5.01	42.33	74.00	-31.67	٧	peak
2557.000	44.70	-2.16	42.54	74.00	-31.46	٧	peak
2809.000	43.10	-1.70	41.40	74.00	-32.60	V	peak
3358.000	42.78	-0.76	42.02	74.00	-31.98	٧	peak
1738.000	48.50	-6.40	42.10	74.00	-31.90	Н	peak
2260.000	45.03	-3.58	41.45	74.00	-32.55	Н	peak
2593.000	46.16	-2.09	44.07	74.00	-29.93	Н	peak
3097.000	42.69	-1.20	41.49	74.00	-32.51	Н	peak
4015.000	42.22	1.64	43.86	74.00	-30.14	Н	peak
4960.000	42.18	4.85	47.03	74.00	-26.97	Н	peak

REMARKS:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).

FCC ID: ZVAOH000022 Page 31 / 47

7.3. 6dB BANDWIDTH MEASUREMENT

7.3.1. LIMITS

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5MHz. The minimum 6 dB bandwidth shall be at least 500 kHz.

Report No.: C180314Z05-RP1

7.3.2. TEST INSTRUMENTS


Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Spectrum Analyzer	Agilent	N9010A	MY55370330	01/27/2018	01/26/2019

7.3.3. TEST PROCEDURES (please refer to measurement standard)

8.1 Option 2:

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = $100 \, \text{kHz}$, VBW $\geq 3 \, \text{RBW}$, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq 6 \, \text{dB}$.

7.3.4. TEST SETUP



7.3.5. TEST RESULTS


No non-compliance noted

Test Data


Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
Low	2402	688.0		PASS
Mid	2440	687.6	>500	PASS
High	2480	704.9		PASS

FCC ID: ZVAOH000022 Page 32 / 47

Test Plot



FCC ID: ZVAOH000022 Page 33 / 47



FCC ID: ZVAOH000022 Page 34 / 47

7.4. ANTENNA GAIN

MEASUREMENT

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For BT LE devices, the GFSK mode is used.

Report No.: C180314Z05-RP1

MEASUREMENT PARAMETERS

Measurement parameter					
Detector	Peak				
Sweep time	Auto				
Resolution bandwidth	3 MHz				
Video bandwidth	3 MHz				
Trace-Mode	Max hold				

LIMITS

FCC	IC
Antenna	a Gain
6 dl	Bi

TEST RESULTS

T _{nom}	V _{nom}	Lowest channel 2402MHz	Middle channel 2440MHz	Highest channel 2480MHz
Conducted power [dBm/MHz] Measured with GFSK modulation		-1.89	-0.98	-0.02
	Radiated power [dBm/MHz] Measured with GFSK modulation		4.50	3.47
Gain [dBi] Calculated		3.54	3.45	
Measurement und	ertainty	± 1.5	dB (cond.) / ± 3 dB	(rad.)

FCC ID: ZVAOH000022 Page 35 / 47

7.5. PEAK OUTPUT POWER

7.5.1. LIMITS

The maximum peak output power of the intentional radiator shall not exceed the following:

Report No.: C180314Z05-RP1

- 1. According to §15.247(b) (3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz: 1 Watt.
- 2. According to §15.247(b) (4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.5.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due	
Power Meter	Anritsu	ML2495A	1204003	02/21/2018	02/20/2019	
Power Sensor	Anritsu	MA2411B	1126150	02/21/2018	02/20/2019	

7.5.3. TEST PROCEDURES (please refer to measurement standard)

9.1.1 RBW ≥ DTS bandwidth

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the *DTS* bandwidth.


- a) Set the RBW ≥ DTS bandwidth.
- b) Set VBW ≥ 3 RBW.
- c) Set span ≥ 3 x RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

9.1.2 PKPM1 Peak power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

FCC ID: ZVAOH000022 Page 36 / 47

7.5.4. TEST SETUP



7.5.5. TEST RESULTS

No non-compliance noted

Test Data

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Peak /AVG	RASHIT
Low	2402	-1.89	0.00065			PASS
Mid	2440	-0.98	0.00080	1	1 peak	PASS
High	2480	-0.02	0.00100			PASS
Low	2402	-2.49	0.00056			PASS
Mid	2440	-1.50	0.00071	1	AVG	PASS
High	2480	-0.50	0.00089			PASS

FCC ID: ZVAOH000022 Page 37 / 47

7.6. BAND EDGES MEASUREMENT

7.6.1. LIMITS

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Report No.: C180314Z05-RP1

7.6.2. TEST INSTRUMENTS

	Radiated I	Emission Test	Site 966(2)				
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration		
PSA Series Spectrum Analyzer	Agilent	N9010A	MY55370330	01/27/2018	01/26/2019		
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	01/27/2018	01/26/2019		
Amplifier	EMEC	EM330	060661	01/27/2018	01/26/2019		
High Noise Amplifier	Agilent	8449B	3008A01838	01/27/2018	01/26/2019		
Loop Antenna	COM-POWER	AL-130	121044	09/25/2017	09/24/2018		
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/21/2018	02/20/2019		
Horn Antenna	SCHWARZBECK	BBHA9120	D286	01/27/2018	01/26/2019		
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	01/24/2018	01/23/2019		
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R		
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R		
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R		
Controller CT		N/A	N/A	N.C.R	N.C.R		
Temp. / Humidity Meter	Anymetre	JR913	N/A	01/29/2018	01/28/2019		
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2					

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


- 2. The FCC Site Registration number is 101879.
- 3. N.C.R = No Calibration Required.

FCC ID: ZVAOH000022 Page 38 / 47

7.6.3. TEST PROCEDURES (please refer to measurement standard)

- 1. The EUT is placed on a turntable, which is 1.5m above the ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
- 4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=1MHz / VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=1/T / Sweep=AUTO
- 5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are

7.6.4. TEST SETUP




This report shall not be reproduced except in full, without the written approval of Compliance Certification Services (Shenzhen) Inc.

Report No.: C180314Z05-RP1


7.6.5. TEST RESULTS


Test Plot Band Edges (CH Low)



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1	2390.000	55.35	-2.86	52.49	74.00	-21.51	Peak	Vertical
2	2402.200	90.16	-2.80	87.36			Peak	Vertical
1	2390.000	44.19	-2.86	41.33	54.00	-12.67	Average	Vertical
2	2402.100	88.82	-2.80	86.02			Average	Vertical

FCC ID: ZVAOH000022 Page 40 / 47






No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1	2390.000	54.92	-2.86	52.06	74.00	-21.94	Peak	Horizontal
2	2402.300	96.17	-2.80	93.37			Peak	Horizontal
1	2390.000	44.27	-2.86	41.41	54.00	-12.59	Average	Horizontal
2	2402.100	95.21	-2.80	92.41			Average	Horizontal


FCC ID: ZVAOH000022 Page 41 / 47

Band Edges (CH-High)



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1	2479.725	90.53	-2.37	88.16			Peak	Vertical
2	2483.500	55.34	-2.35	52.99	74.00	-21.01	Peak	Vertical
1	2480.050	89.44	-2.37	87.07			Average	Vertical
2	2483.500	44.11	-2.35	41.76	54.00	-12.24	Average	Vertical

FCC ID: ZVAOH000022 Page 42 / 47



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1	2479.750	96.15	-2.37	93.78			Peak	Horizontal
2	2483.500	54.36	-2.35	52.01	74.00	-21.99	Peak	Horizontal
1	2480.025	95.10	-2.37	92.73			Average	Horizontal
2	2483.500	44.89	-2.35	42.54	54.00	-11.46	Average	Horizontal

FCC ID: ZVAOH000022 Page 43 / 47

7.7. PEAK POWER SPECTRAL DENSITY MEASUREMENT

7.7.1. LIMITS

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Report No.: C180314Z05-RP1

According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.


7.7.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Spectrum Analyzer	Agilent	N9010A	MY55370330	01/27/2018	01/26/2019

7.7.3. TEST PROCEDURES (please refer to measurement standard)

- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to 1.5 times the DTS bandwidth.
- 3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- 4. Set the VBW ≥ 3 RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.7.4. TEST SETUP



FCC ID: ZVAOH000022 Page 44 / 47

7.7.5. TEST RESULTS

No non-compliance noted


Test Data

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2402	-17.309		PASS
Mid	2440	-16.430	8.00	PASS
High	2480	-15.339		PASS


Report No.: C180314Z05-RP1

FCC ID: ZVAOH000022 Page 45 / 47

Test Plot



FCC ID: ZVAOH000022 Page 46 / 47
This report shall not be reproduced except in full, without the written approval of Compliance Certification Services (Shenzhen) Inc.



FCC ID: ZVAOH000022 Page 47 / 47