

**Kenxen Limited**

Application  
For  
Certification

**FCC ID: ZVTW4SD00**

**Portable Scanner**

**Model: W4SD**  
**Additional Model: W4S**

**WiFi Transceiver**

Report No.: SZ12080538-1

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-12]

Prepared and Checked by:

Sign on file

Jimmy Wen  
Testing Engineer

Approved by:

---

Billy Li  
Supervisor  
Date: 22 March, 2013

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF no.: FCC 15C\_Tx\_b

## INTERTEK TESTING SERVICE

---

---

### LIST OF EXHIBITS

#### *INTRODUCTION*

<i>EXHIBIT 1:</i>	Summary of Tests
<i>EXHIBIT 2:</i>	General Description
<i>EXHIBIT 3:</i>	System Test Configuration
<i>EXHIBIT 4:</i>	Measurement Results
<i>EXHIBIT 5:</i>	Equipment Photographs
<i>EXHIBIT 6:</i>	Product Labeling
<i>EXHIBIT 7:</i>	Technical Specifications
<i>EXHIBIT 8:</i>	Instruction Manual
<i>EXHIBIT 9:</i>	Confidentiality Request
<i>EXHIBIT 10:</i>	Miscellaneous Information
<i>EXHIBIT 11:</i>	Test Equipment List

# INTERTEK TESTING SERVICES

---

---

## MEASUREMENT/TECHNICAL REPORT

**Kenxen Limited - MODEL: W4SD**

**FCC ID: ZVTW4SD00**

This report concerns (check one)    Original Grant  Class II Change

Equipment Type: DTS - Part 15 Digital Transmission Systems (WiFi transmitter portion)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)?    Yes     No

If yes, defer until : \_\_\_\_\_  
date

Company Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37?    Yes     No

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-12 Edition] provision.

Report prepared by:

Billy Li  
Intertek Testing Services Shenzhen Ltd.  
Kejiyuan Branch  
6F, Block D, Huahan Building, Langshan Road,  
Nanshan District, Shenzhen, P. R. China  
Phone: (86 755) 8614 0645  
Fax: (86 755) 8614 6751

# INTERTEK TESTING SERVICES

---

---

## Table of Contents

<b>1.0 <u>Summary of test results</u></b> .....	2
<b>2.0 <u>General Description</u></b> .....	4
2.1 Product Description .....	4
2.2 Related Submittal(s) Grants .....	5
2.3 Test Methodology.....	5
2.4 Test Facility .....	5
<b>3.0 <u>System Test Configuration</u></b> .....	7
3.1 Justification .....	7
3.2 EUT Exercising Software.....	7
3.3 Details of EUT and Description of Peripherals .....	8
3.4 Measurement Uncertainty.....	8
3.5 Equipment Modification .....	8
3.6 Support Equipment List and Description.....	8
<b>4.0 <u>Measurement Results</u></b> .....	10
4.1 Maximum Conducted Output Power at Antenna Terminals.....	10
4.2 Minimum 6dB RF Bandwidth .....	16
4.3 Maximum Power Density .....	26
4.4 Out of Band Conducted Emissions .....	36
4.5 Out of Band Radiated Emissions.....	49
4.6 Transmitter Radiated Emissions in Restricted Bands.....	50
4.7 Field Strength Calculation.....	51
4.8 Radiated Spurious Emission.....	52
4.9 Conducted Emission .....	66
4.10 Radiated Emission from Digital Section of Transceiver.....	69
4.11 Transmitter Duty Cycle Calculation and Measurements.....	70
<b>5.0 <u>Equipment Photographs</u></b> .....	72
<b>6.0 <u>Product Labelling</u></b> .....	74
<b>7.0 <u>Technical Specifications</u></b> .....	76
<b>8.0 <u>Instruction Manual</u></b> .....	78
<b>9.0 <u>Confidentiality Request</u></b> .....	80
<b>10.0 <u>Miscellaneous Information</u></b> .....	82
<b>11.0 <u>Test Equipment List</u></b> .....	84

## INTERTEK TESTING SERVICES

---

---

### List of attached file

Exhibit type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Operation Description	Technical Description	descri.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidentiality Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf
Cover Letter	Certification Agreement	agreement.pdf

# **INTERTEK TESTING SERVICES**

---

---

## **EXHIBIT 1**

### **SUMMARY OF TEST RESULTS**

# INTERTEK TESTING SERVICES

---

## 1.0 Summary of Test

**Kenxen Limited - MODEL: W4SD**

**FCC ID: ZVTW4SD00**

TEST	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
AC Conducted Emission	15.207	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

## **INTERTEK TESTING SERVICES**

---

---

### **EXHIBIT 2**

### **GENERAL DESCRIPTION**

## INTERTEK TESTING SERVICES

---

---

### 2.0 General Description

#### 2.1 Product Description

The Equipment Under Test (EUT) is a Portable Scanner with internal WiFi function operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing and 2422-2452MHz for 802.11n-HT40, 7 channels with 5MHz channel spacing. The EUT can be powered by DC6V (4 x 1.5V AAA batteries in scanner cell box) or DC9V (6 x 1.5V AA batteries in docking station cell box) or power by USB port (Both Scanner or Docking station). For more detailed features description, please refer to the user's manual.

The Model: W4SD includes two parts (Scanner and Docking station). The Model: W4S (scanner) is the main operation unit with WiFi function. The models are difference in marketing purpose only.

Type of Modulation: BPSK, QPSK, 16QAM, 64QAM, CCK, DQPSK, DBPSK .  
Antenna Type: Integral Antenna.

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

## INTERTEK TESTING SERVICES

---

### 2.2 Related Submittal(s) Grants

This is an application for certification of:  
DTS- Part 15 Digital Transmission Systems (WiFi transmitter portion)

Remaining portions are subject to the following procedures:

1. Receiver portion of WiFi: exempt from technical requirement of this Part.
2. Data Transfer Function: (FCC DOC report).
3. Other Digital Function: (FCC VOC report)

### 2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009) and KDB 558074. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

### 2.4 Test Facility

The Semi-Anechoic chamber and shield room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch** and located at 6F, Block D, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).

## **INTERTEK TESTING SERVICES**

---

---

### **EXHIBIT 3**

### **SYSTEM TEST CONFIGURATION**

## INTERTEK TESTING SERVICES

---

### 3.0 System Test Configuration

#### 3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered separately by DC6V (4 x 1.5V AAA new batteries) or DC9V (6 x 1.5V AA new batteries) or PC USB port (the PC was powered through AC 120V/60Hz input) during the test. Only the worst case data was reported.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

#### 3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

#### Power Parameters of IEEE 802.11b/g/n

Test software setting of IEEE 802.11b/g/n			
Channel No.	Output Power (dBm)	Data rate	Modulation type
1,6,11	24.0	802.11b: 1-11Mbps	802.11b: CCK
	24.0	802.11g: 6-54Mbps	802.11g: BPSK, QPSK, 16QAM
1,6,11	24.0	802.11n-HT20: 6.5-65Mbps	802.11n: BPSK, QPSK, 16QAM,
3,6,9	24.0	802.11n-HT40: 13.5-135Mbps	802.11n: BPSK, QPSK, 16QAM, 64QAM

On 802.11b/g/n (HT20 & HT40) mode, only one antenna is used for transmission.

TRF no.: FCC 15C\_TX\_b

FCC ID: ZVTW4SD00

Report No.: SZ12080538-1

## INTERTEK TESTING SERVICES

---

### 3.3 Special Accessories

One shielded USB cable with one ferrite core attached with the EUT.

### 3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance – Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

### 3.5 Equipment Modification

Any modifications installed previous to testing by Kenxen Limited will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch.

### 3.6 Support Equipment List and Description

This product was tested in the following configuration:

Refer List:

Description	Manufacturer	Model No.
Laptop	Lenovo	T420
Hard Disk	Smart.drive	HD-003
USB Cable	Smart.drive	Unshielded, Length 155cm
1394 Cable	Smart.drive	Unshielded, Length 180cm
iPhone	Apple	A1303
Mini SD Card	SanDisk	4G
USB Cable	N/A	Unshielded, Length 100cm
USB Cable	Kenxen	Shielded with one ferrite and Length 100cm

## **INTERTEK TESTING SERVICES**

---

---

### **EXHIBIT 4**

### **MEASUREMENT RESULTS**

# INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited  
Model: W4SD

Date of Test: 22 March 2013

## 4.0 Measurement Results

### 4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

[ ] The antenna power of the EUT was connected to the input of a spectrum analyzer. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.

[x] The antenna port of the EUT was connected to the input of a spectrum analyzer. The analyzer was set according to the FCC KDB 558074 spectrum analyzer's integrated band power measurement function with band limits set equal to the EBW band edges and power was read directly in dBm. External attenuation and cable loss were compensated from the measured value.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

IEEE 802.11b (Antenna Gain = 2.0dBi) (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	5.93	3.92
Middle Channel: 2437	5.82	3.82
High Channel: 2462	5.62	3.65

IEEE 802.11g (Antenna Gain = 2.0dBi) (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	6.34	4.31
Middle Channel: 2437	6.19	4.16
High Channel: 2462	5.94	3.93

IEEE 802.11n-HT20 (Antenna Gain = 2.0 dBi) (16QAM, 6.5Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2412	6.52	4.49
Middle Channel: 2437	6.39	4.36
High Channel: 2462	6.19	4.16

TRF no.: FCC 15C\_TX\_b

FCC ID: ZVTW4SD00

Report No.: SZ12080538-1

## INTERTEK TESTING SERVICES

---

---

IEEE 802.11n-HT40 (Antenna Gain = 2.0dBi) (64QAM, 13.5Mbps)		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2422	6.30	4.27
Middle Channel: 2437	6.10	4.07
High Channel: 2452	6.25	4.22

Cable loss: 0.5 dB    External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function


EUT max. output level = 6.52dBm

For RF Exposure, the information is saved with filename: RF exposure.pdf.

The test plots are attached as below.

# INTERTEK TESTING SERVICES


## 802.11b



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES


802.11g



TRF no.: FCC 15C\_TX\_b  
FCC ID: ZVTW4SD00  
Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES


## 802.11 n-HT20



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES

## 802.11 n-HT40



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited  
Model: W4SD

Date of Test: 22 March 2013

### 4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a)(2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 1-5 % of the emission bandwidth and not to exceed 100 KHz according to FCC KDB 558074. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	10.12
2437	10.12
2462	10.12

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	16.44
2437	16.44
2462	16.44

IEEE 802.11n-HT20 (16QAM, 6.5Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	17.72
2437	17.68
2462	17.72

## INTERTEK TESTING SERVICES

---


---

IEEE 802.11n-HT40 (64QAM, 13.5Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2422	36.00
2437	36.00
2452	35.96

The test plots are attached as below.


# INTERTEK TESTING SERVICES

## 802.11b



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1


# INTERTEK TESTING SERVICES



TRF no.: FCC 15C\_TX\_b  
FCC ID: ZVTW4SD00  
Report No.: SZ12080538-1


# INTERTEK TESTING SERVICES

802.11g



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1



# INTERTEK TESTING SERVICES



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1


# INTERTEK TESTING SERVICES

## 802.11 n-HT20



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1


# INTERTEK TESTING SERVICES



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1


## INTERTEK TESTING SERVICES

802.11 n-HT40



TRF no.: FCC 15C\_TX\_b  
FCC ID: ZVTW4SD00  
Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES



TRF no.: FCC 15C\_TX\_b  
FCC ID: ZVTW4SD00  
Report No.: SZ12080538-1

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited  
Model: W4SD

Date of Test: 22 March 2013

### 4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/ 3 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	-5.81
2437	-5.89
2462	-6.18

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	-12.62
2437	-12.83
2462	-12.86

IEEE 802.11n-HT20 (16QAM, 6.5Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	-12.64
2437	-12.72
2462	-12.88

## INTERTEK TESTING SERVICES

---


---

IEEE 802.11n-HT40 (64QAM, 13.5Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2422	-15.32
2437	-15.74
2452	-15.73

The test plots are attached as below.


# INTERTEK TESTING SERVICES

## 802.11b



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1


# INTERTEK TESTING SERVICES



TRF no.: FCC 15C\_TX\_b  
FCC ID: ZVTW4SD00  
Report No.: SZ12080538-1


# INTERTEK TESTING SERVICES

802.11g



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1



# INTERTEK TESTING SERVICES



TRF no.: FCC 15C\_TX\_b  
FCC ID: ZVTW4SD00  
Report No.: SZ12080538-1


# INTERTEK TESTING SERVICES

802.11 n-HT20



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1



# INTERTEK TESTING SERVICES



TRF no.: FCC 15C\_TX\_b  
FCC ID: ZVTW4SD00  
Report No.: SZ12080538-1


# INTERTEK TESTING SERVICES

## 802.11 n-HT40



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1

## INTERTEK TESTING SERVICES



TRF no.: FCC 15C\_TX\_b  
FCC ID: ZVTW4SD00  
Report No.: SZ12080538-1

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited  
Model: W4SD

Date of Test: 22 March 2013

### 4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n-HT20 and 13.5Mbps for 802.11n-HT40.


The test plots showed all spurious emission up to the tenth harmonic was measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

The test plots are attached as below.

# INTERTEK TESTING SERVICES

802.11b

Channel 01 (2412MHz) Reference Level: -5.81dBm




TRF no.: FCC 15C\_TX\_b

FCC ID: ZVTW4SD00

Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES



Channel 06 (2437MHz) Reference Level: -5.89dBm



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES

Channel 11 (2462MHz) Reference Level: -6.18dBm




TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES

802.11g

Channel 01 (2412MHz) Reference Level: -12.62dBm





TRF no.: FCC 15C\_TX\_b

FCC ID: ZVTW4SD00

Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES



Channel 06 (2437MHz) Reference Level: -12.83dBm



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES

Channel 11 (2462MHz) Reference Level: -12.86dBm




TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES

802.11 n-HT20

Channel 01 (2412MHz) Reference Level: -12.64dBm




TRF no.: FCC 15C\_TX\_b

FCC ID: ZVTW4SD00

Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES


Channel 06 (2437MHz) Reference Level: -12.72dBm



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES

Channel 11 (2462MHz) Reference Level: -12.88dBm




TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES

802.11 n-HT40

Channel 03 (2422MHz) Reference Level: -15.32dBm




TRF no.: FCC 15C\_TX\_b

FCC ID: ZVTW4SD00

Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES


Channel 06 (2437MHz) Reference Level: -15.74dBm



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES

Channel 09 (2452MHz) Reference Level: -15.73dBm



TRF no.: FCC 15C\_TX\_b  
 FCC ID: ZVTW4SD00  
 Report No.: SZ12080538-1

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited  
Model: W4SD

Date of Test: 22 March 2013

### 4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

- Not required, since all emissions are more than 20dB below fundamental
- See attached data sheet

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited  
Model: W4SD

Date of Test: 22 March 2013

### 4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited  
Model: W4SD

Date of Test: 22 March 2013

### 4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where      FS = Field Strength in dB $\mu$ V/m  
RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V  
CF = Cable Attenuation Factor in dB  
AF = Antenna Factor in dB  
AG = Amplifier Gain in dB  
PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

#### Example

Assume a receiver reading of 62.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 32 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$\begin{aligned} RA &= 62.0 \text{ dB}\mu\text{V} \\ AF &= 7.4 \text{ dB} \\ CF &= 1.6 \text{ dB} \\ AG &= 29.0 \text{ dB} \\ PD &= 0 \text{ dB} \\ FS &= 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m} \end{aligned}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

## **INTERTEK TESTING SERVICES**

---

Applicant: Kenxen Limited  
Model: W4SD

Date of Test: 22 March 2013

### **4.8 Radiated Spurious Emission**

Worst Case Radiated Spurious Emission (802.11n-HT40) at 2387.800MHz is passed by 0.1 dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited

Date of Test: 22 March 2013

Model: W4SD

Worst Case Operating Mode: 802.11 n-HT20 (TX-Channel 01)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	320.030	43.8	20.0	15.9	39.7	46.0	-6.3
Horizontal	358.830	42.5	20.0	16.1	38.6	46.0	-7.4
Horizontal	480.080	41.6	20.0	18.7	40.3	46.0	-5.7
Vertical	279.290	35.4	20.0	12.7	28.1	46.0	-17.9
Vertical	321.010	33.9	20.0	15.9	29.8	46.0	-16.2
Vertical	959.890	24.1	20.0	24.0	28.1	46.0	-17.9

NOTES: 1. Quasi-Peak detector is used except for others stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. All emissions are below the QP limit.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited

Date of Test: 22 March 2013

Model: W4SD

Mode: 802.11b (TX-Channel 01)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4824.000	52.2	36.1	34.1	50.2	54.0	-3.8
Horizontal	*2388.740	62.9	36.7	27.2	53.4	54.0	-0.6

NOTES:

1. Peak detector is used for the emission measurement (RBW=1MHz, VBW=3MHz for Peak data).
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

---

Applicant: Kenzen Limited

Date of Test: 22 March 2013

Model: W4SD

Mode: 802.11b (TX-Channel 06)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4874.000	51.2	36.1	34.5	49.6	54.0	-4.4
Horizontal	*7311.000	52.3	35.6	37.1	53.8	54.0	-0.2

NOTES:

1. Peak detector is used for the emission measurement (RBW=1MHz, VBW=3MHz for Peak data).
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited

Date of Test: 22 March 2013

Model: W4SD

Mode: 802.11b (TX-Channel 11)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4924.000	50.2	36.1	34.7	48.8	54.0	-5.2
Horizontal	*2483.510	55.9	36.7	27.7	46.9	54.0	-7.1

NOTES: 1. Peak detector is used for the emission measurement (RBW=1MHz, VBW=3MHz for Peak data).

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited

Date of Test: 22 March 2013

Model: W4SD

Mode: 802.11g (TX-Channel 01)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4824.000	51.0	36.1	34.1	49.0	54.0	-5.0
Horizontal	*2389.160	62.7	36.7	27.2	53.2	54.0	-0.8

NOTES: 1. Peak detector is used for the emission measurement (RBW=1MHz, VBW=3MHz for Peak data).

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited

Date of Test: 22 March 2013

Model: W4SD

Mode: 802.11g (TX-Channel 06)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4874.000	50.8	36.1	34.5	49.2	54.0	-4.8
Horizontal	*7311.000	52.0	35.6	37.1	53.5	54.0	-0.5

NOTES: 1. Peak detector is used for the emission measurement (RBW=1MHz, VBW=3MHz for Peak data).

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited

Date of Test: 22 March 2013

Model: W4SD

Mode: 802.11g (TX-Channel 11)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4924.000	49.9	36.1	34.7	48.5	54.0	-5.5
Horizontal	*7386.000	52.2	35.6	37.2	53.8	54.0	-0.2
Horizontal	*2484.060	61.3	36.7	27.7	52.3	54.0	-1.7

NOTES: 1. Peak detector is used for the emission measurement (RBW=1MHz, VBW=3MHz for Peak data).

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited

Date of Test: 22 March 2013

Model: W4SD

Mode: 802.11 n-HT20 (TX-Channel 01)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4824.000	51.0	36.1	34.1	49.0	54.0	-5.0
Horizontal	*2389.720	63.3	36.7	27.2	53.8	54.0	-0.2

NOTES: 1. Peak detector is used for the emission measurement (RBW=1MHz, VBW=3MHz for Peak data).

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited

Date of Test: 22 March 2013

Model: W4SD

Mode: 802.11 n-HT20 (TX-Channel 06)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4874.000	50.5	36.1	34.5	48.9	54.0	-5.1
Horizontal	*7311.000	51.9	35.6	37.1	53.4	54.0	-0.6

NOTES: 1. Peak detector is used for the emission measurement (RBW=1MHz, VBW=3MHz for Peak data).

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited

Date of Test: 22 March 2013

Model: W4SD

Mode: 802.11 n-HT20 (TX-Channel 11)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4924.000	50.1	36.1	34.7	48.7	54.0	-5.3
Horizontal	*7386.000	52.1	35.6	37.2	53.7	54.0	-0.3
Horizontal	*2484.060	62.5	36.7	27.7	53.5	54.0	-0.5

NOTES:

1. Peak detector is used for the emission measurement (RBW=1MHz, VBW=3MHz for Peak data).
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited

Date of Test: 22 March 2013

Model: W4SD

Mode: 802.11 n-HT40 (TX-Channel 03)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4844.000	50.9	36.1	34.6	49.4	54.0	-4.6
Horizontal	*2387.800	63.4	36.7	27.2	53.9	54.0	-0.1

NOTES: 1. Peak detector is used for the emission measurement (RBW=1MHz, VBW=3MHz for Peak data).

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited

Date of Test: 22 March 2013

Model: W4SD

Mode: 802.11 n-HT40 (TX-Channel 06)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4874.000	50.8	36.1	34.5	49.2	54.0	-4.8
Horizontal	*7311.000	52.3	35.6	37.1	53.8	54.0	-0.2

NOTES: 1. Peak detector is used for the emission measurement (RBW=1MHz, VBW=3MHz for Peak data).

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited

Date of Test: 22 March 2013

Model: W4SD

Mode: 802.11 n-HT40 (TX-Channel 09)

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	*4904.000	50.2	36.1	34.8	48.9	54.0	-5.1
Horizontal	*7356.000	51.8	35.6	37.4	53.6	54.0	-0.4
Horizontal	2486.300	62.6	36.7	27.7	53.6	54.0	-0.4

NOTES:

1. Peak detector is used for the emission measurement (RBW=1MHz, VBW=3MHz for Peak data).
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## **INTERTEK TESTING SERVICES**

---

---

### **4.9 Conducted Emission**

Worst Case Live-Conducted emission at 0.516MHz is Passed by 6.1 dB margin

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

# INTERTEK TESTING SERVICES


Applicant: Kenxen Limited

Date of Test: 22 March 2013

Model: W4SD

Worst Case Operating Mode: 802.11 n\_20M (TX-Channel 01)

## Conducted Emission Test - FCC



## Result Table QP

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.150	42.1	L1	9.6	23.9	66.0
0.196	41.4	L1	9.6	22.3	63.7
0.516	47.3	L1	9.6	8.7	56.0
1.652	39.0	L1	9.7	17.0	56.0
5.056	43.5	L1	9.8	16.5	60.0
9.518	44.4	L1	9.9	15.6	60.0

## Result Table AV

Frequency (MHz)	Average (dB $\mu$ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.150	38.3	L1	9.6	17.7	56.0
0.196	37.9	L1	9.6	15.8	53.7
0.516	39.9	L1	9.6	6.1	46.0
1.652	31.3	L1	9.7	14.7	46.0
5.056	36.1	L1	9.8	13.9	50.0
9.518	36.5	L1	9.9	13.5	50.0

TRF no.: FCC 15C\_TX\_b

FCC ID: ZVTW4SD00

Report No.: SZ12080538-1

# INTERTEK TESTING SERVICES


Applicant: Kenxen Limited

Date of Test: 22 March 2013

Model: W4SD

Worst Case Operating Mode: 802.11n\_20M (TX-Channel 01)

## Conducted Emission Test - FCC



## Result Table QP

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.198	38.7	N	9.6	25.0	63.7
0.296	39.3	N	9.6	21.0	60.3
0.535	44.1	N	9.6	11.9	56.0
1.752	36.2	N	9.8	19.8	56.0
4.920	41.3	N	9.9	14.7	56.0
9.304	42.5	N	10.0	17.5	60.0

## Result Table AV

Frequency (MHz)	Average (dB $\mu$ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.198	29.5	N	9.6	24.2	53.7
0.296	29.6	N	9.6	20.7	50.3
0.535	33.0	N	9.6	13.0	46.0
1.752	26.1	N	9.8	19.9	46.0
4.920	32.3	N	9.9	13.7	46.0
9.304	35.2	N	10.0	14.8	50.0

TRF no.: FCC 15C\_TX\_b

FCC ID: ZVTW4SD00

Report No.: SZ12080538-1

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited  
Model: W4SD

Date of Test: 22 March 2013

4.10 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

- [ ] Not required - No digital part
- [ ] Test results are attached
- [ x ] Included in the separated report.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Limited  
Model: W4SD

Date of Test: 22 March 2013

### 4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

## **INTERTEK TESTING SERVICES**

---

---

### **EXHIBIT 5**

### **EQUIPMENT PHOTOGRAPHS**

## INTERTEK TESTING SERVICES

---

---

### 5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.doc & internal photos.pdf.

## **INTERTEK TESTING SERVICES**

---

---

### **EXHIBIT 6**

### **PRODUCT LABELLING**

## INTERTEK TESTING SERVICES

---

---

### 6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

## **INTERTEK TESTING SERVICES**

---

---

### **EXHIBIT 7**

### **TECHNICAL SPECIFICATIONS**

## INTERTEK TESTING SERVICES

---

---

### 7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

## **INTERTEK TESTING SERVICES**

---

---

### **EXHIBIT 8**

### **INSTRUCTION MANUAL**

## INTERTEK TESTING SERVICES

---

---

### 8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

## **INTERTEK TESTING SERVICES**

---

---

### **EXHIBIT 9**

### **CONFIDENTIALITY REQUEST**

## INTERTEK TESTING SERVICES

---

---

### 9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

## **INTERTEK TESTING SERVICES**

---

---

### **EXHIBIT 10**

#### **MISCELLANEOUS INFORMATION**

## INTERTEK TESTING SERVICES

---

### 10.0 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

## **INTERTEK TESTING SERVICES**

---

---

### **EXHIBIT 11**

### **TEST EQUIPMENT LIST**

## INTERTEK TESTING SERVICES

---

### 11.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-03	BiConiLog Antenna	ETS	3142C	00066460	30-Jun-12	30-Jun-13
SZ185-01	EMI Receiver	R&S	ESCI	100547	22-Sep-12	22-Jun-13
SZ061-09	Horn Antenna	ETS	3115	00092346	28-Nov-12	28-Nov-13
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	8-Sep-12	22-Jun-13
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	8-Dec-12	8-Jun-13
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	22-Sep-12	22-Jun-13
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	17-Nov-12	17-May-13
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	3-Dec-12	08-Jun-13
SZ062-02	RF Cable	RADIALL	RG 213U	--	17-Mar-12	17-Sep-13
SZ062-05	RF Cable	RADIALL	0.04-26.5GHz	--	29-Dec-12	29-Jun-13
SZ062-12	RF Cable	RADIALL	0.04-26.5GHz	--	29-Dec-12	29-Jun-13
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	--	11-Jun-12	11-Jun-13
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	5-Nov-12	5-Nov-13
SZ187-01	Two-Line V-Network	R&S	ENV216	100072	5-Nov-12	5-Nov-13
SZ187-02	Two-Line V-Network	R&S	ENV216	100073	5-Nov-12	5-Nov-13
SZ188-03	Shielding Room	ETS	RFD-100	4100	10-Sep-12	10-Sep-13