FCC§1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Report No.: RDG151201005-00A

Applicable Standard

According to subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure										
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time E , H or S (minutes)						
0.3-1.34	614	1.63	*100	30						
1.34-30	824/f	2.19/f	*180/f ²	30						
30-300	27.5	0.073	0.2	30						
300-1,500			f/1500	30						
1,500-100,000			1.0	30						

f = frequency in MHz

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

I	Frequency	Antenna Gain		Max Turn up Power		Evaluation	Power	MPE Limit
	(MHz)	(dBi)	(numeric)	(dBm)	(mW)	Distance (cm)	Density (mW/cm ²)	(mW/cm ²)
	450.0125	8	6.31	51	125893	650	0.15	0.30

Note: The manufacturer does not specify an antenna to be used with this device, but a typical installation has a gain up to 8 dBi.

To comply with FCC RF exposure requirements, a minimum separation distance of 650 cm is required between the antenna and all public persons.

Result: Compliance

FCC Part 90 Page 9 of 24

^{* =} Plane-wave equivalent power density