


12.4mm Overmolded Button Tag



OVERVIEW

Overmolded Button Tag is designed for applications that require a rugged tag in harsh environment. It basically meets all requirements such as heat, pressure and chemical resistance in the applications.



SPECIFICATION

Diameter (±0.2mm)	12.4 mm		
Thickness (±0.4mm)	T 2 mm		
Available Technology	I.CODE SLIX		
Operating Frequency	13.56MHz		
Reading Range	Depending on the reader design and local installation conditions		
Material	PA6		
Operating Temperature	-40~85°C		
Storage Temperature	-40~130°C		
Protection Class	IP68		
Assembly	Overmolding		
Standard Color	Black		
Approx. Weight	0.4 g		
Packaging	1000pcs		
Option	ID Numbering	Printing	Adhesive Back
	• Laser Engraving	• Laser Engraving • Pad Printing	•

WARRANTY

® SAG warrants this product against defects in material and workmanship under normal use and service. The warranty period commences from the date of shipment for a period of one year.

APPLICATION

- Laundry Management
- Garment Tracking
- Textile Rental
- Factory Automation
- Asset Tracking
- Inventory Control



(SAG) Securitag Assembly Group Co., Ltd.			
TEL	+886-4-2492 5298	E-mail	info@sag.com.tw
FAX	+886-4-2492 7388	WEB	www.SAG.com.tw

Ref: TAG-B1-1003