

TEST REPORT

Report No.: HK12050691-1

Zhongshan Longde S&T Technology Co., Ltd.

Application For Certification (Original Grant) (FCC ID: ZWP2011A1)

Transmitter

Prepared and Checked by:	Approved by:
Signed On File	
Wong Cheuk Ho, Herbert Engineer	Chan Chi Hung, Terry Assistant Supervisor Date: May 30, 2012

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

GENERAL INFORMATION

Zhongshan Longde S&T Technology Co., Ltd. BRAND NAME: N/A, MODEL: 2011A

FCC ID: ZWP2011A1

Grantee:	Zhongshan Longde S&T Technology Co., Ltd.	
Grantee Address:	No. 33 Middle Industry AV,	
	Xiaolan, Zhongshan City,	
	GD, China.	
Contact Person:	Ms. Fiona Li	
Tel:	86 760 2382 0470	
Fax:	86 760 2382 5029	
e-mail:	risin@longde.com.cn	
Manufacturer:	Zhongshan Longde S&T Technology Co., Ltd.	
Manufacturer Address:	No. 33 Middle Industry AV,	
	Xiaolan, Zhongshan City,	
	GD, China.	
Brand Name:	N/A	
Model:	2011A	
Type of EUT:	Transmitter	
Description of EUT:	Remote Key Finder TSI	
Serial Number:	N/A	
FCC ID:	ZWP2011A1	
Date of Sample Submitted:	May 11, 2012	
Date of Test:	May 21, 2012	
Report No.:	HK12050691-1	
Report Date:	May 30, 2012	
Environmental Conditions:	Temperature: +10 to 40°C	
	Humidity: 10 to 90%	

Report No.: HK12050691-1 FCC ID: ZWP2011A1

SUMMARY OF TEST RESULT

Zhongshan Longde S&T Technology Co., Ltd. BRAND NAME: N/A, MODEL: 2011A

FCC ID: ZWP2011A1

TEST SPECIFICATION	REFERENCE	RESULTS
Maximum Peak Output Power	15.247(b), (c) / RSS-210 A8.4	N/A
Hopping Channel Carrier Frequencies	15.247(e) / RSS-210 A8.1	N/A
Separation		
20dB Bandwidth of the Hopping Channel	15.247(a) / RSS-210 A8.1	N/A
Number of Hopping Frequencies	15.247(e) / RSS-210 A8.1	N/A
Average Time of Occupancy of	15.247(e) / RSS-210 A8.1	N/A
Hopping Frequency		
Antenna Conducted Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
Radiated Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
RF Exposure Compliance	15.247(i) / RSS-Gen 5.6	N/A
Transmitter Power Line Conducted	15.207 / RSS-Gen 7.2.4	N/A
Emissions		
Transmitter Field Strength	15.227 / RSS-310 3.8	N/A
Transmitter Field Strength	15.229 / RSS-210 A2.7	N/A
Transmitter Field Strength,	15.231(a) / RSS-210 A1.1.1	Pass
Bandwidth and Timing Requirement		
Transmitter Field Strength,	15.231(e) / RSS-210 A1.1.5	N/A
Bandwidth and Timing Requirement		
Transmitter Field Strength and	15.239 / RSS-210 A2.8	N/A
Bandwidth Requirement		
Transmitter Field Strength and	15.249 / RSS-210 A2.9	N/A
Bandwidth Requirement		
Transmitter Field Strength and	15.235 / RSS-310 3.9	N/A
Bandwidth Requirement		
Receiver / Digital Device Radiated	15.109 / RSS-210 2.5	N/A
Emissions		
Digital Device Conducted Emissions	15.107 / ICES-003	N/A

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the pervisions of this section.

2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

Report No.: HK12050691-1

Table of Contents

1.0	General Description	T
1.1	Product Description	1
1.2	Related Submittal(s) Grants	1
1.3	Test Methodology	
1.4	Test Facility	
	· · · · · · · · · · · · · · · · · · ·	
2.0	System Test Configuration	2
2.1	Justification	2
2.2	EUT Exercising Software	
2.3	Special Accessories	
2.4	Equipment Modification	
2.5	Measurement Uncertainty	
2.6	Support Equipment List and Description	
3.0	Emission Results	3
3.1	Field Strength Calculation	
3.2	Radiated Emission Configuration Photograph	
3.3	Radiated Emission Data	
4.0	Equipment Photographs	6
5.0	Product Labelling	6
6.0	Technical Specifications	6
7.0	Instruction Manual	6
8.0	Miscellaneous Information	7
8.1	Measured Bandwidth	
8.2	Discussion of Pulse Desensitization	
8.3	Calculation of Average Factor	
8.4	Emissions Test Procedures	
9.0	Equipment List	9

Report No.: HK12050691-1

1.0 **General Description**

1.1 Product Description

The equipment under test (EUT) is a wireless key finder operating at 315MHz. The EUT is powered by 3.0VDC (2 x 1.5V "AAA" size batteries). The EUT has two buttons. When pressing either button, the EUT will transmit RF signal to the corresponding receiver and thus causing the receiver beeping.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

The Declaration of the Conformity procedure of receiver for this transmitter is being processed as the same time of this application.

1.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

Report No.: HK12050691-1 FCC ID: ZWP2011A1

2.0 **System Test Configuration**

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2003).

The device was powered by 2 x new 1.5V "AAA" size batteries.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

2.4 Equipment Modification

Any modifications installed previous to testing by Zhongshan Longde S&T Technology Co., Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services Hong Kong Ltd.

2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

N/A.

Report No.: HK12050691-1 FCC ID: ZWP2011A1

00 IB. 2WI 201 I/ (I

3.0 **Emission Results**

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - AG - AV

where $FS = Field Strength in dB\mu V/m$

RA = Receiver Amplitude (including preamplifier) in dBµV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB AG = Amplifier Gain in dB AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

FS = RR + LF

where $FS = Field Strength in dB\mu V/m$

 $RR = RA - AG - AV in dB\mu V$

LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

 $RA = 52.0 dB\mu V/m$

AF = 7.4 dB $RR = 18.0 \text{ dB}\mu\text{V}$

CF = 1.6 dB LF = 9.0 dB

AG = 29.0 dBAV = 5.0 dB

FS = RR + LF

 $FS = 18 + 9 = 27 \, dB\mu V/m$

Level in μ V/m = Common Antilogarithm [(27 dB μ V/m)/20] = 22.4 μ V/m

Report No.: HK12050691-1 FCC ID: ZWP2011A1

3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 315.050 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 6.1 dB

Report No.: HK12050691-1 FCC ID: ZWP2011A1

Applicant: Zhongshan Longde S&T Technology Co., Ltd. Date of Test: May 21, 2012

Model: 2011A

Worst-Case Operating Mode: Transmitting

Radiated Emissions
Pursuant to FCC Part 15 Section 15.231(a) Requirement

Table 1

			Pre-	Antenna	Average		Limit at	
Polari-	Frequency	Reading	Amp	factor	Factor	Net at 3m	3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	315.050	74.0	16	23.0	11.5	69.5	75.6	-6.1
V	630.100	35.1	16	29.0	11.5	36.6	55.6	-19.0
V	945.150	28.1	16	33.0	11.5	33.6	55.6	-22.0
V	1260.200	59.4	34	26.1	11.5	40.0	55.6	-15.6
Н	1575.250	60.3	34	27.2	11.5	42.0	54.0	-12.0
Н	1890.300	56.8	34	27.2	11.5	38.5	55.6	-17.1
Н	2205.350	41.7	34	29.4	11.5	25.6	54.0	-28.4
Н	2520.400	54.2	34	30.4	11.5	39.1	55.6	-16.5
V	2835.450	53.9	34	30.4	11.5	38.8	54.0	-15.2
Н	3150.500	60.6	34	31.9	11.5	47.0	55.6	-8.6
Н	3465.550	55.6	34	31.9	11.5	42.0	55.6	-13.6

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

Report No.: HK12050691-1

4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

6.0 <u>Technical Specifications</u>

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

Report No.: HK12050691-1

8.0 **Miscellaneous Information**

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

8.1 Measured Bandwidth

For electronic filing, the plot shows the fundamental emission when modulated is saved with filename: bw.pdf. From the plot, the bandwidth is observed to be 404kHz, at 20dBc where the bandwidth limit is 0.7875MHz.

8.2 Discussion Pulse Desensitivity

Pulse desensitivity is not applicable for this device. The effective period (Teff) is approximately 26.48ms for a digital "1" bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

8.3 Calculation of Average Factor

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 100ms

Effective period of the cycle = $57x240\mu s + 16x800\mu s = 26.48ms$

DC = 26.48 / 100 = 0.2648

Therefore, the averaging factor is found by $20\log 0.2648 = -11.5dB$.

Report No.: HK12050691-1 FCC ID: ZWP2011A1

8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2003. A typical or an unmodulated CW signal at the operating frequency of the EUT has been supplied to the EUT for all measurements. Such a signal is supplied by a signal generator and an antenna in close proximity to the EUT. The signal level is sufficient to stabilize the local oscillator of the EUT.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

Report No.: HK12050691-1 FCC ID: ZWP2011A1

8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 - 2003.

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

9.0 **Equipment List**

1) Radiated Emissions Test

Equipment	EMI Test Receiver	Biconical Antenna	Log Periodic Antenna
Registration No.	EW-2500	EW-2512	EW-0446
Manufacturer	R&S	EMCO	EMCO
Model No.	ESCI	3104C	3146
Calibration Date	Feb. 24, 2012	Nov. 15, 2011	Oct. 31, 2011
Calibration Due Date	Feb. 24, 2013	May 15, 2013	Apr. 30, 2013

Equipment	Spectrum Analyzer	Double Ridged Guide Antenna
Registration No.	EW-2188	EW-1133
Manufacturer	AGILENTTECH	EMCO
Model No.	E4407B	3115
Calibration Date	Sep. 26, 2011	Mar. 02, 2011
Calibration Due Date	Sep. 26, 2012	Sep. 02, 2012

2) Bandedge Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-1792
Manufacturer	R&S
Model No.	FSP40
Calibration Date	Sep. 28, 2011
Calibration Due Date	Sep. 28, 2012

Report No.: HK12050691-1