



Delivering information

Wireless RF Repeater

ISL024DB1R **User's Guide**

This document contains information about the hardware interface between ISL024DB1R transceiver and Receiver. Information includes the theory of operation, specifications, interface definitions, configuration information and mechanical drawings

Proprietary Material

The information and descriptions contained herein are the property of ISL. Such information and descriptions may not be copied or reproduced by any means, or disseminated or distributed without the express prior written permission of ISL.

This document is for information purposes only and is subject to change without notice.

Statement of Limited Warranty

ISL warrants equipment of its manufacture, and bearing its identification to be free from defects in workmanship and material for a period of 12 months for electronics and 12 months for mechanical parts and Temperature probes from date of delivery from the factory or authorised distributor under normal use and service and otherwise when such equipment is used in accordance with instructions furnished by ISL and for the purposes disclosed in writing at the time of purchase, if any. ISL liability under this warranty shall be limited to replacement or repair of any defective equipment or part which, having been returned to ISL, has been inspected and determined by ISL to be defective, excluding battery cells.

THIS WARRANTY IS IN LIEU OF ANY OTHER WARRANTY, EITHER EXPRESS OR IMPLIED, AS TO DESCRIPTION, QUALITY, AND MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR USE, OR ANY OTHER MATTER.

Revision History

Issue	Date	Author	Comments
0-1	09/09/2011	Vahid Tambe	Initial Release
0-2	29/09/2011	Rob Jevans	Removed antenna references

Operation is subject to the following two conditions: this device may not cause harmful interference, and this device must accept any interference received, including interference that may cause undesired operation.

Caution: any changes or modifications not expressly approved by the Manufacturer could void the user's authority to operate the equipment.

Contents

1. Safety Information	5
DECLARATION OF CONFORMITY	8
2. ISL024DB1R	9
3 Theory of operation.....	10
4. Installing the ISL024DB1R Repeater	12

1. Safety Information

FCC WARNING

This equipment generates or uses radio frequency energy. Changes or modifications to this equipment may cause harmful interference unless the modifications are expressly approved in the instruction manual. The user could lose the authority to operate this equipment if an unauthorized change or modification is made

Agency Identification Numbers

Part #	FCC	
ISL024DB1R	ZWZISL024DB1R	

Approved Antenna List

The ISL024DB1 has been designed with an internal PCB antenna only.

Caution: Any changes or modifications not expressly approved by Invisible Systems could void the user's authority to operate the equipment.

FCC REQUIREMENTS

NOTE: This device complies with Part 15 of the FCC Rules.

Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment generates, uses, and can radiate radio frequency energy. If not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does not cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Re-orient or relocate the receiving antenna
- Increase the separation between the equipment and the receiver
- Connect the equipment to an outlet on a circuit that is different from that to which the receiver is connected.

Replacing battery

!CAUTION:

RISK OF EXPLOSION IF BATTERY IS REPLACED BY AN INCORRECT TYPE.
DISPOSE OF USED BATTERIES ACCORDING TO THE INSTRUCTIONS

WARNING!

Only qualified service personnel may install this equipment. The instructions in this manual are intended for use by qualified service personnel only.

Only qualified persons should service the system.

The installation and service of this hardware is to be performed only by service personnel having appropriate training and experience necessary to be aware of hazards to which they are exposed in performing a task and of measures to minimize the danger to themselves or other persons. Electrical shock hazards from the telecommunication network and AC mains are possible with this equipment. To minimize risk to service personnel and users, the system must be connected to an outlet with a third-wire Earth.

Service personnel must be alert to the possibility of high leakage currents becoming available on metal system surfaces during power line fault events near network lines.

These leakage currents normally safely flow to Protective Earth via the power cord.

Therefore, it is mandatory that connection to an earthed outlet is performed first and removed last when cabling to the unit. Specifically, operations requiring the unit to be powered down must have the network connections (exchange lines) removed first.

Intrinsic safety

Do not install the unit in conditions where there is a danger of electrically ignited explosions.

Exposure to sunlight, heat and moisture

Do not expose the unit to direct sunlight for long periods. Keep away from excessive heat and moisture.

Spare parts and accessories

Use only approved spare parts and accessories. The operation of non-approved parts cannot be guaranteed and may even cause damage.



DECLARATION OF CONFORMITY

Measurement Standard Applied

ANSI C63.10:2009

Manufacturer:

Invisible Systems Ltd
9 Beetham Rd
Milnthorpe
Cumbria
LA7 7QL
U.K

Product Description

925.78MHz Transceiver
designed for low cost solution
for wireless application

Product Model

ISL024DB1R

Part Number

250001R

Test Laboratories



Unit E
South Orbital Trading Park
Hedon Road
Hull
HU9 1NJ
UK
T 01482 801801
F 01482 801806

STANDARDS TO WHICH CONFORMITY IS DECLARED

Part 15 Specific conditions for 900MHz

Title 47 CFR 15.209, 15.249 (a),(e), 15.215, 15.109, 15.203

I the undersigned, hereby declare that the equipment specified above conforms to the specified Directive and Standards.

Signature

Date

Print Name

Title

2. ISL024DB1R

The ISL024DB1R repeater is designed for use with the ISL024DB1 transceiver system to extend the range of the transmitter from the receiver. The ISL024DB1R incorporates intelligent messages so that the receiver may receive messages from either the receiver and/or repeater directly without conflict. This further enhances the flexibility of the ISL024DB1 with minimal user input.

To determine whether you actually need a repeater, if you have a major obstruction(s) or already know that you need to employ multiple chains in your network, then you will need a solution to extend your data transmission range.

The repeater connection includes the following:

- Power supply connection **Note:** The power supply for the repeater is to be ordered separately.



3 Theory of operation


3.1 Repeater networks

Though there is no functionality for a transmitter to automatically forward a message along to another radio, repeater networks can be setup to provide for additional coverage.

This example of a repeater network would still be useful for a point-to-multipoint network where some of the transmitters are not in range of the primary access point.

In this network topology an ISL024DB1R is setup to act as the primary access point.

To cover additional areas, a repeater consisting of two ISL024DB1R can be added to the network.



Limitations:

There are some limitations to this setup.

- The addition of the repeaters requires additional radios which increases the cost of the systems.
- The repeater setup must be powered sufficiently.

- The antennas of the transmitter and the receiver in the repeater should be positioned to minimize interference. For best performance the antennas should be placed more than 10ft from each other.
- There is some additional latency associated with the repeater; this latency is between 200 and 400ms typically

4. Installing the ISL024DB1R Repeater

Before beginning the installation, determine the position of the repeater for best coverage.

The coverage depends on the construction of the building, architecture, and the choice of building materials.

Environmental requirements

- Avoid installing repeaters on large concrete or marble columns because these columns affect radio coverage. If possible, place the base station a minimum of one meter/3.3 feet from these types of columns.
- Do not install a repeater with the antenna housings near metal objects. Be careful not to damage existing wiring or panels.
- Do not position repeaters in ducts, plenums or hollow spaces used to transport environmental air except where the duct, plenum or hollow space is created by a suspended ceiling having lay-in panels.
- Keep the repeater away from steel constructions.
- Do not position repeaters directly on metallic surfaces. If possible, place the receiver a minimum of one meter/3.3 feet from these types of surfaces.
- Only position repeaters where the signal is needed.
- The installation area must be clean, free of traffic and excess dust, dry, and well ventilated.
- The installation area must be within the temperature ranges of 10°C and 40°C/50°F and 104°F.
- The installation area must be between 20% and 80% non-condensing relative humidity.

Note The repeater does not add channels; it only adds additional coverage area.

For best RF coverage, the repeater must be mounted vertically on walls. The antennas must always be kept perpendicular to the floor.

Caution The repeater must not be installed at any angle other than vertical. If the repeater is placed upside-down, the coverage area of the repeater is decreased by 40 - 50% and it might not transmit or receive effectively.

Powering the ISL024DB1R Repeater

The power supply for the repeater is 3.6VDC, 300mA

Appropriate RF safety/installation information

The repeater is intended to be installed by authorised personal. The repeater shall be installed in accordance with FCC rules.

TABLE 2: ISL024DB1R DETAILED SPECIFICATIONS

INTERFACES	
RF Connector	None internal PCB antenna.
OPERATIONAL	
Network Topologies	Point-to-Point, Point-to-Multi Point
Security	N/A
Frequency Band	925.78MHz
RF Data rate	2400 kbps
RF Technology	Narrowband
Output Power	1mW
Maximum radiated power (EIRP)	19.7mV/m measured at 3 meter
Range Line of sight	Outdoor: up to 300m Indoor: up to 30m
Sensitivity	-115dBm at 2400kbps RF rate
ELECTRICAL/ENVIRONMENTAL	
Supply voltage	+3.3 v DC
Current consumption	35mA
Temperature (Operating)	-30°C to 75°C
Temperature (storage)	-50°C to 85°C
PHYSICAL	
Dimensions	35x50mm
Weight	8g
CERTIFICATIONS	
FCC	FCC ID: ZWZISL024DB1R
CE	ANSI C63.10:2009
ROHS	yes