



FCC - TEST REPORT

Report Number : **709502404488-00B** Date of Issue: February 18, 2025

Model : CM-07

Product Type : Tubular Motor

Applicant : Coulisse B.V.

Address : Vonderweg 48, 7468 DC Enter, THE NETHERLANDS

Production Facility : Ningbo Dooya Mechanic & Electronic Technology Co., Ltd.

Address : No.168 Shengguang Road, Luotuo, Zhenhai 315202 Ningbo,
: Zhejiang province People's Republic of China

Test Result : **Positive** **Negative**

Total pages including Appendices : 24



TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.



1 Table of Contents

1	Table of Contents.....	2
2	Report Modification Record.....	3
3	Details about the Test Laboratory	3
4	Description of the Equipment Under Test.....	4
5	Summary of Test Standards.....	6
6	Summary of Test Results	7
7	General Remarks.....	8
8	Systems test configuration	9
9	Test Setups.....	10
10	Test Methodology	12
10.1	Conducted Emission	12
10.2	Radiated Emission	15
10.3	20dB Bandwidth Measurement	19
10.4	Deactivation Time	20
11	Test Equipment List	21
12	System Measurement Uncertainty	22
13	Photographs of Test Set-ups	23
14	Photographs of EUT	24



2 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
709502404488-00B	First Issue	02/18/2025

3 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
No.16 Lane, 1951 Du Hui Road,
Shanghai 201108,
P.R. China

Telephone: +86 21 6141 0123

Fax: +86 21 6140 8600

FCC Registration No.: 820234

FCC Designation Number: CN1183

ISED CAB identifier: CN0101

IC Registration No.: 31668



4 Description of the Equipment Under Test

Product: Tubular Motor
 Model no.: CM-07
 FCC ID: ZY4CM07B1
 IC: NA
 Options and accessories: NA
 Rating: 12V DC
 RF Transmission Frequency: SRD transceiver: 433.92MHz;
 2.4GHz BLE: 2402~2480 MHz
 No. of Operated Channel: SRD transceiver: 1;
 2.4GHz BLE: 40
 Modulation: SRD transceiver: FSK;
 2.4GHz BLE: GFSK
 Channel list: SRD transceiver: 433.92MHz;
 2.4GHz BLE:

Bluetooth Low Energy							
Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Antenna Type: SRD transceiver: Line Antenna;
 2.4GHz BLE: Line Antenna
 Antenna Gain: 2.4GHz BLE: 2.2dBi



Description of the EUT: The Equipment Under Test (EUT) is a Tubular Motor with BLE function and SRD function (transceiver). We tested it and listed the worst data in this report.

Test sample no.: SHA-882436-2

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment, antenna gain or any information supplied.



5 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2023 Edition	RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to ANSI C63.10-2020.



6 Summary of Test Results

Technical Requirements				
FCC Part 15 Subpart C				
Test Condition		Pages	Test Site	Test Result
§15.207	Conducted emission AC power port	11-13	Shield room	Pass
§15.205, §15.209, 15.35 (c)§15.231(b)	The Field strength of Emissions	14-17	3m chamber	Pass
§15.231(c)	20dB Bandwidth Measurement	18	Shield room	Pass
§15.231(a)(1)	Deactivation Time	19	Shield room	Pass
§15.203	Antenna requirement	See Note 2		Pass

Remark

Note 1: N/A – Not Applicable. Conducted emission is not apply for battery operated device.

Note 2: The EUT uses a Line Antenna. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.



7 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: ZY4CM07B1 complies with Section 15.207, 15.205, 15.209, 15.231 of the FCC Part 15, Subpart C Rules.

This report is only for the 433.92MHz test report, for the 2.4GHz BLE test report please refer to 709502404488-00C.

We tested it and listed the worst data in this report.

SUMMARY:

All tests according to the regulations cited on page 5 were

- Performed

- **Not** Performed

The Equipment Under Test

- **Fulfills** the general approval requirements.

- **Does not** fulfill the general approval requirements.

Sample Received Date: January 7, 2025

Testing Start Date: January 11, 2025

Testing End Date: February 11, 2025

-TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:



Hui TONG
EMC Section Manager

Wenqiang LU
EMC Project Engineer

Chengjie GUO
EMC Test Engineer




8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
AC/DC Adapter	XP Power	VEC65US12	--


9 Test Setups

8.1 AC Power Line Conducted Emission test setups




8.2 Radiated test setups


9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:



Above 1GHz Test Setup:



8.3 Conducted RF test setups





10 Test Methodology

10.1 Conducted Emission

Test Method

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both sides of AC line were checked for maximum conducted interference.
6. The frequency range from 150 kHz to 30 MHz was searched.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

Limit

According to §15.207, conducted emissions limit as below:


Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

*Decreasing linearly with logarithm of the frequency.



Conducted Emission Test 0.15MHz – 30MHz

Product Type : Tubular Motor
 M/N : CM-07
 Operating Condition : Mode: Tx 433.92MHz
 Test Specification : L-line
 Comment : AC 120V/60Hz (by adaptor)



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.150000	37.89	---	66.00	28.11	1000.0	9.000	L1	19.5
0.298500	---	19.24	50.28	31.04	1000.0	9.000	L1	19.5
0.609000	37.11	---	56.00	18.89	1000.0	9.000	L1	19.5
0.618000	---	28.70	46.00	17.30	1000.0	9.000	L1	19.5
0.951000	27.46	---	56.00	28.54	1000.0	9.000	L1	19.5
0.991500	---	20.00	46.00	26.00	1000.0	9.000	L1	19.5
3.511500	---	19.19	46.00	26.81	1000.0	9.000	L1	19.6
3.529500	25.72	---	56.00	30.28	1000.0	9.000	L1	19.5
12.304500	23.96	---	60.00	36.04	1000.0	9.000	L1	19.8
12.394500	---	17.89	50.00	32.11	1000.0	9.000	L1	19.8
12.921000	27.51	---	60.00	32.49	1000.0	9.000	L1	19.8
13.011000	---	19.72	50.00	30.28	1000.0	9.000	L1	19.8

Remark:


Measure Level (dBuV/m) = Reading Level (dBuV) + Correction Factor (dB)

Correction Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

(The Reading Level is recorded by software which is not shown in the sheet)



Product Type : Tubular Motor
 M/N : CM-07
 Operating Condition : Mode: Tx 433.92MHz
 Test Specification : N-line
 Comment : AC 120V/60Hz (by adaptor)



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.168000	34.90	---	65.06	30.16	1000.0	9.000	N	19.5
0.276000	---	20.52	50.94	30.42	1000.0	9.000	N	19.4
0.609000	---	29.36	46.00	16.64	1000.0	9.000	N	19.5
0.609000	37.00	---	56.00	19.00	1000.0	9.000	N	19.5
0.964500	28.34	---	56.00	27.66	1000.0	9.000	N	19.5
0.987000	---	20.04	46.00	25.96	1000.0	9.000	N	19.5
2.971500	25.91	---	56.00	30.09	1000.0	9.000	N	19.5
3.529500	---	19.15	46.00	26.85	1000.0	9.000	N	19.5
12.381000	---	20.16	50.00	29.84	1000.0	9.000	N	19.8
12.390000	27.84	---	60.00	32.16	1000.0	9.000	N	19.8
12.957000	29.39	---	60.00	30.61	1000.0	9.000	N	19.8
23.982000	---	24.55	50.00	25.45	1000.0	9.000	N	20.6

Remark:

Measure Level (dBuV/m) = Reading Level (dBuV) + Correction Factor (dB)

Correction Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

(The Reading Level is recorded by software which is not shown in the sheet)



10.2 Radiated Emission

Test Method

- 1: The EUT was place on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2: The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
- 3: The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4: For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5: Use the following spectrum analyzer settings According to C63.10:
 - 9kHz -150kHz
RBW = 200Hz, VBW = 1kHz for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.
 - 150kHz - 30MHz
RBW = 10 kHz, VBW = 30 kHz for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.
 - 30MHz - 1GHz
RBW = 100 kHz, VBW = 300 kHz for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.
 - For Above 1GHz
RBW = 1MHz, VBW \geq 3RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.



Limit

1. FCC Limit: In addition to the provisions of § 15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field Strength of Fundamental (Microvolts /meter)	Field Strength of spurious emissions ((Microvolts /meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	1,250 to 3,750 *	125 to 375 *
174-260	3,750	375
260-470	3,750 to 12, 500*	375 to 1,250*
Above 470	12,500	1,250

*Linear interpolation with frequency

(a) The above field strength limits are specified at a distance of 3 meters. The tighter limits apply at the band edges.

(b) Intentional radiators operating under the provisions of this section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector. The specific method of measurement employed shall be specified in the application for equipment authorization. If average emission measurements are employed, the provisions in § 15.35 for averaging pulsed emissions and for limiting peak emissions apply. Further, compliance with the provisions of § 15.205 shall be demonstrated using the measurement instrumentation specified in that section.

(c) The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in § 15.209, whichever limit permits a higher field strength.

Limits for 15.209 Radiated emission limits

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3



Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.


Radiated Emission								
Value	Emissions Frequency MHz	E-Field Polarity	PK Emission dB μ V/m	Average Factor dB	AV Emission dB μ V/m	Limit dB μ V/m	Margin	Emission Type
Below 1GHz								
PK	433.92	H	89.70	/	/	100.83	11.13	Fundamental
AV	433.92	H	85.13	-23.15	61.98	80.83	18.85	Fundamental
PK	433.92	V	84.60	/	/	100.83	16.23	Fundamental
AV	433.92	V	81.78	-23.15	58.63	80.83	22.2	Fundamental
PK	867.789	H	40.23	/	/	80.83	40.6	Spurious
AV	867.789	H	40.65	-23.15	17.5	60.83	43.33	Spurious
PK	867.789	V	39.42	/	/	80.83	41.41	Spurious
AV	867.789	V	40.65	-23.15	17.5	60.83	43.33	Spurious
Above 1GHz								
PK	1301.933	H	32.33	/	/	74	41.67	Spurious
AV	1301.933	H	30.89	-23.15	7.74	54	46.26	Spurious
PK	1301.933	V	37.41	/	/	74	36.59	Spurious
AV	1301.933	V	30.54	-23.15	7.39	54	46.61	Spurious

Remark:

- 1: AV Emission Level= PK Emission Level+20log (duty cycle)
- 2: Data of measurement within this frequency range shown "/" in the table above means the reading of emissions are attenuated more than 20db below the permissible limits or the field strength is too small to be measured..
- 3: "*" means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.
- 4: Corrected Amplitude = Read level + Corrector factor
 - Above 1GHz: Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain
 - Below 1GHz: Corrector factor = Antenna Factor + Cable Loss
5. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz)
6. Corrected Reading = Original Receiver Reading + Correct Factor
7. Only the worst data listed in this report

Duty Cycle = 6.957ms/100 (ms) =6.957%

Duty Cycle Factor =20log (Duty Cycle) =-23.15



Date: 11.FEB.2025 08:35:48

10.3 20dB Bandwidth Measurement

Test Method

1. The EUT was placed on 0.8m height table, the RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
Use the following test receiver settings:
RBW = 1% to 5% of the OBW, VBW \geq 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth. Record the results.


Limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900MHz. For devices operating above 900MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20dB down from the modulated carrier.

The limit for the EUT = 0.25% * 433.92 MHz = 1084.8 kHz

Test Result

Channel	20dB Bandwidth (KHz)	Limit (KHz)	Result
1	82.092KHz	\leq 1084.8	Pass





10.4 Deactivation Time

Test Method

1. The EUT was placed on 0.8m height table, the RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT in transmitting mode.
3. Set center frequency of spectrum analyzer=operating frequency.
4. Set the spectrum analyzer as $RBW \geq OBW$, $VBW \geq RBW$, Span=0Hz, detector=peak.
5. Repeat above procedures until all frequency measured was complete.

Limit


According to FCC Part 15.231 (a), the transmitter shall be complied the following requirements:
 (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

(2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.

(3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour.

Test Result

Channel	Frequency	Deactivation Time	Limit	Result
1	433.92MHz	408.7ms	≤5s	Pass





11 Test Equipment List

List of Test Instruments

Test Site1

RF Conductive Test

Description	Manufacturer	Model no.	Equipment ID.	Calibration Date	Calibration Due
Signal and spectrum analyzer	R&S	FSV40	S1503003-YQ-EMC	2024-8-01	2025-7-31

Conducted Emission

Description	Model no.	Manufacturer	Equipment ID.	Calibration Date	Calibration Due
EMI test receiver	ESR3	R&S	S1503001-YQ-EMC	2024-8-01	2025-7-31
2-Line V-network	ENV216	R & S	S1503103-YQ-EMC	2024-8-01	2025-7-31

Radiated Emission Test

USED	Equipment Name	Model	Manufacturer	Equipment ID.	Calibration Date	Calibration Due
<input checked="" type="checkbox"/>	EMI test receiver	ESR3	R&S	S1503109-YQ-EMC	2024-8-01	2025-7-31
<input checked="" type="checkbox"/>	Trilog super broadband test antenna	SCHWARZBECK	VULB9168	S1808296-YQ-EMC	2024-8-30	2025-8-29
<input checked="" type="checkbox"/>	Double-ridged waveguide horn antenna	HF907	R&S	S1503009-YQ-EMC	2024-4-14	2025-4-13
<input checked="" type="checkbox"/>	Pre-amplifier	HPAP-9K0130	Shenzhen HzEMC	S2110423b-YQ-EMC	2024-8-01	2025-7-31
<input checked="" type="checkbox"/>	Signal and spectrum analyzer	FSV40	R&S	S1503003-YQ-EMC	2024-8-01	2025-7-31
<input checked="" type="checkbox"/>	Loop antenna	HFH2-Z2	R&S	S1503013-YQ-EMC	2024-6-26	2025-6-25

Measurement Software Information

Test Item	Software	Manufacturer	Version
RE	EMC 32	Rohde & Schwarz	V10.50.40
CE	EMC 32	Rohde & Schwarz	V9.15.03



12 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty

Items	Extended Uncertainty
Conducted Disturbance at Mains Terminals	150kHz to 30MHz, LISN, 3.16dB
Radiated Disturbance	30MHz to 1GHz, 5.03dB (Horizontal) 5.12dB (Vertical) 1GHz to 18GHz, 5.49dB 18GHz to 40GHz, 5.63dB
Carrier power conducted measurement	50MHz~18GHz, 1.238dB
Spurious Emission Conducted Measurement	9kHz ~40GHz, 1.224dB

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2023, clause 4.3.3.



13 Photographs of Test Set-ups

Refer to the < Test Setup photos >.



14 Photographs of EUT

Refer to the < External Photos > & < Internal Photos >.

THE END