



## FCC TEST REPORT

Report Number : **709502409685-00C** Date of Issue: December 23, 2024

Model : CMD-03, CM-45

Product Type : Tubular motor

Applicant : Coulisse B.V.

Address : Vonderweg 48, 7468 DC Enter, THE NETHERLANDS

Manufacturer : Coulisse B.V.

Address : Vonderweg 48, 7468 DC Enter, THE NETHERLANDS

Test Result :  **Positive**  **Negative**

Total pages including Appendices : 23



TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.  
dc



## 1 Table of Contents

1	Table of Contents.....	2
2	Report Modification Record .....	3
3	Details about the Test Laboratory .....	3
4	Description of the Equipment Under Test .....	4
5	Summary of Test Standards .....	5
6	Summary of Test Results .....	6
7	General Remarks.....	7
8	Systems test configuration .....	8
9	Test Setups.....	9
10	Test Methodology .....	11
10.1	Conducted Emission.....	11
10.2	Radiated Emission.....	16
10.3	20 Bandwidth Measurement.....	20
10.4	Deactivation Time.....	21
11	Test Equipment List.....	22
12	System Measurement Uncertainty .....	23



## 2 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
709502409685-00C	First Issue	12/23/2024

## 3 Details about the Test Laboratory

### Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch  
No.16 Lane, 1951 Du Hui Road,  
Shanghai 201108,  
P.R. China

Telephone: +86 21 6141 0123

Fax: +86 21 6140 8600

FCC Registration No.: 820234

FCC Designation Number: CN1183

ISED CAB identifier: CN0101

IC Registration No.: 31668



## 4 Description of the Equipment Under Test

Product: Tubular motor  
 Model no.: CMD-03, CM-45  
 FCC ID: ZY4CMD03B1  
 Options and accessories: NA  
 Rating: Input USB-C 5V  
 RF Transmission Frequency: 433.92MHz  
 Frequency: 2402~2480 MHz (BLE5.0)

No. of Operated Channel:

Bluetooth Low Energy							
Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Modulation: 2.4GHz BLE: GFSK; 433.92MHz: 2GFSK  
 Hardware Version: B1  
 Software Version: B1  
 Antenna Type: 2.4GHz BLE: Line antenna; 433.92MHz: Line antenna  
 Antenna Gain: 2.4GHz BLE:2.2 dBi  
 Description of the EUT: The Equipment Under Test (EUT) is a Tubular motor which supports 433.92MHz transceiver and support 2.4GHz BLE. We tested it and listed the worst data in this report.  
 Test sample no.: SHA-866063-3

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.



## 5 Summary of Test Standards

<b>Test Standards</b>	
FCC Part 15 Subpart C	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to ANSI C63.10-2020.



## 6 Summary of Test Results

Technical Requirements				
FCC Part 15 Subpart C				
Test Condition		Pages	Test Site	Test Result
§15.207	Conducted emission AC power port	11-15	Shield room	Pass
§15.205, §15.209, 15.35 (c)§15.231(b)	The Field strength of Emissions	16-19	3m chamber	Pass
§15.231(c)	Bandwidth Measurement	20	Shield room	Pass
§15.231(a)(2)	Deactivation Time	21	Shield room	Pass
§15.203	Antenna requirement	--	See Note 1	Pass

Note 1: The EUT uses line antenna. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.



## 7 General Remarks

### Remarks

This submittal(s) (test report) is intended for FCC ID: ZY4CMD03B1, complies with Section 15.207, 15.205, 15.209, 15.231 of the FCC Part 15, Subpart C Rules.

According to client's declaration, schematics, PCB layout, critical components and mechanical construction of two models are the same. Differences between two models are the model name and outside view. Model CMD-03 was chosen to perform the full test items.

This report is only for 433.92MHz.

### SUMMARY:

All tests according to the regulations cited on page 5 were

- Performed

- **Not** Performed

### The Equipment Under Test

- **Fulfills** the general approval requirements.

- **Does not** fulfill the general approval requirements.


Sample Received Date: November 12, 2024

Testing Start Date: November 14, 2024

Testing End Date: December 2, 2024

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:




Prepared by:



Tested by:



Hui TONG  
EMC Section Manager

Jiaxi XU  
EMC Project Engineer

Chengjie GUO  
EMC Test Engineer




## 8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
AC/DC adapter	MLF	MLF-A260502000UU	--


## 9 Test Setups

### 9.1 AC Power Line Conducted Emission test setups




### 9.2 Radiated test setups


9kHz ~ 30MHz Test Setup:



## 30MHz ~ 1GHz Test- Setup



## 1GHz ~ 18GHz Test Setup:





## 10 Test Methodology

### 10.1 Conducted Emission

#### Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

#### Limit

Frequency MHz	QP Limit dB $\mu$ V	AV Limit dB $\mu$ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency



## Conducted Emission

# 150k-30MHz Conducted Emission Test


## EUT Information

EUT Name:	Tubular motor
Model:	CMD-03
Client:	Coulisse B.V
Op Cond:	Power on and charging mode, 433.92MHz transmitting.
Operator:	Guo Chengjie
Test Spec:	FCC part 15.207(a)
Comment:	Phase L
Sample No:	SHA-866063-3

## Scan Setup: Voltage with 2-Line-LISN pre [EMI conducted]

Hardware Setup: Voltage with 2-Line-LISN  
 Receiver: [ESR 3]  
 Level Unit: dBuV

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
9 kHz - 150 kHz	100 Hz	PK+	200 Hz	0.02 s	0 dB
150 kHz - 30 MHz	4.5 kHz	PK+; AVG	9 kHz	0.01 s	0 dB





## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.240000	32.41	---	62.10	29.69	1000.0	9.000	L1	19.5
0.325500	---	26.27	49.57	23.30	1000.0	9.000	L1	19.5
0.528000	---	39.75	46.00	6.25	1000.0	9.000	L1	19.5
0.528000	41.02	---	56.00	14.98	1000.0	9.000	L1	19.5
1.590000	---	38.59	46.00	7.41	1000.0	9.000	L1	19.5
1.644000	40.52	---	56.00	15.48	1000.0	9.000	L1	19.5
2.332500	37.09	---	56.00	18.91	1000.0	9.000	L1	19.5
3.129000	---	33.08	46.00	12.92	1000.0	9.000	L1	19.5
5.671500	35.84	---	60.00	24.16	1000.0	9.000	L1	19.6
5.676000	---	28.51	50.00	21.49	1000.0	9.000	L1	19.6
17.263500	25.27	---	60.00	34.73	1000.0	9.000	L1	20.1
17.731500	---	18.73	50.00	31.27	1000.0	9.000	L1	20.2

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator



# 150k-30MHz Conducted Emission Test


## EUT Information

EUT Name: Tubular motor  
 Model: CMD-03  
 Client: Coulisse B.V  
 Op Cond: Power on and charging mode, 433.92MHz transmitting.  
 Operator: Guo Chengjie  
 Test Spec: FCC part 15.207(a)  
 Comment: Phase N  
 Sample No: SHA-866063-3

## Scan Setup: Voltage with 2-Line-LISN pre [EMI conducted]

Hardware Setup: Voltage with 2-Line-LISN  
 Receiver: [ESR 3]  
 Level Unit: dBuV

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
9 kHz - 150 kHz	100 Hz	PK+	200 Hz	0.02 s	0 dB
150 kHz - 30 MHz	4.5 kHz	PK+; AVG	9 kHz	0.01 s	0 dB





## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.330000	---	18.93	49.45	30.52	1000.0	9.000	N	19.4
0.339000	29.76	---	59.23	29.47	1000.0	9.000	N	19.4
0.532500	---	29.51	46.00	16.49	1000.0	9.000	N	19.5
0.537000	31.51	---	56.00	24.49	1000.0	9.000	N	19.5
1.644000	---	29.87	46.00	16.13	1000.0	9.000	N	19.5
1.648500	36.44	---	56.00	19.56	1000.0	9.000	N	19.5
3.142500	---	13.31	46.00	32.69	1000.0	9.000	N	19.5
3.196500	27.74	---	56.00	28.26	1000.0	9.000	N	19.5
5.703000	---	10.47	50.00	39.53	1000.0	9.000	N	19.6
5.757000	18.38	---	60.00	41.62	1000.0	9.000	N	19.6
17.898000	26.12	---	60.00	33.88	1000.0	9.000	N	20.1
19.333500	---	12.47	50.00	37.53	1000.0	9.000	N	20.2

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

## 10.2 Radiated Emission

### Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10:

For Above 1GHz

Span = wide enough to capture the peak level of the in-band emission and all spurious  
 RBW = 1MHz, VBW $\geq$ 3RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious  
 RBW = 100 KHz, VBW $\geq$ 3RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

### Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (duty cycle  $\geq$ 98%) for peak detection at frequency above 1GHz
4. If the emission is pulsed (duty cycle <98%), modify the unit for continuous operation: use the settings shown above, then correct the reading by subcontracting the peak to average duty cycle correction factor  $20\log$  (duty cycle),, derived from the appropriate duty cycle calculation.



## Limit

According to §15.231 (b), the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field Strength of Fundamental (Microvolts /meter @3m)	Field Strength of spurious emissions ((Microvolts /meter @3m)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	1,250 to 3,370 *	125 to 3750 *
174-260	3,750	375
260-470 √	3,750 to 12, 500*	375 to 1,250*
Above 470	12,500	1,250

## Limits for 15.209 Radiated emission limits; general requirements

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Frequency	Limit at 3m (dBuV/m)
0.009 MHz – 0.490 MHz	128.5 to 93.8 <sup>1</sup>
0.490 MHz – 1.705 MHz	73.8 to 63 <sup>1</sup>
1.705 MHz – 30 MHz	69.5 <sup>1</sup>
30 MHz – 88 MHz	40.0 <sup>1</sup>
88 MHz – 216 MHz	43.5 <sup>1</sup>
216 MHz – 960 MHz	46.0 <sup>1</sup>
Above 960 MHz	54.0 <sup>1</sup>
Above 1000 MHz	54.0 <sup>2</sup>
Above 1000 MHz	74.0 <sup>3</sup>

<sup>1</sup>Limit is with detector with bandwidths as defined in CISPR-16-1-1 except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz where an Average detector is used.

<sup>2</sup>Limit is with 1 MHz measurement bandwidth and using an Average detector.

<sup>3</sup>Limit is with 1 MHz measurement bandwidth and using a Peak detector.

## Spurious radiated emissions for transmitter

Radiated Emission									
Value	Emissions	E-Field	PK	Corr.	Average	AV	Limit	Margin	Emission Type
	Frequency	Polarity	Emission	Factor	Factor	Emission	dB $\mu$ V/m		
	MHz		dB $\mu$ V/m	dB	dB	dB $\mu$ V/m			
Below 1GHz									
PK	433.92	H	82.36	25.70	0.00	/	100.80	18.44	Fundamental
AV	433.92	H	82.36	/	-23.15	59.21	80.80	21.59	Fundamental
PK	433.92	V	74.15	25.70	0.00	/	100.80	26.65	Fundamental
AV	433.92	V	74.15	/	-23.15	51.00	80.80	29.80	Fundamental
PK	867.84	H	43.88	33.20	0.00	/	80.80	36.92	Spurious
AV	867.84	H	43.88	/	-23.15	20.73	60.80	40.07	Spurious
PK	867.84	V	38.21	33.20	0.00	/	80.80	42.59	Spurious
AV	867.84	V	38.21	/	-23.15	15.06	60.80	45.74	Spurious
Above 1GHz									
PK	1600.00	H	34.16	-14.00	0.00	/	74.00	39.84	Restricted band*
AV	1600.00	H	34.16	/	-23.15	11.01	54.00	42.99	Restricted band*
PK	3425.50	H	40.40	-6.50	0.00	/	80.80	40.40	Spurious
AV	3425.50	H	40.40	/	-23.15	17.25	60.80	43.55	Spurious
PK	1552.20	V	34.91	-14.20	0.00	/	74.00	39.09	Restricted band*
AV	1552.20	V	34.55	/	-23.15	11.40	54.00	42.60	Restricted band*
PK	2034.50	V	37.07	-11.50	0.00	/	80.80	43.73	Spurious
AV	2034.50	V	37.07	/	-23.15	13.92	60.80	46.88	Spurious

Remark:

1: AV Emission Level= PK Emission Level+20log(dutycycle)

2: Data of measurement within this frequency range shown “/” in the table above means the reading of emissions are attenuated more than 20db below the permissible limits or the field strength is too small to be measured.

3: “\*\*” means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.

4: Level= Reading Level + Correction Factor

Correction Factor = Antenna Factor + Cable Loss- Amplifier Gain


(The Reading Level is recorded by software which is not shown in the sheet)

Duty Cycle =6.957(ms)/100(ms) =6.957%


Duty Cycle Factor =20log (Duty Cycle) =-23.15



## Duty Cycle



Date: 20.NOV.2024 08:57:07



Date: 20.NOV.2024 08:55:33

## 10.3 20 Bandwidth Measurement

### Test Method

1. Set to the maximum power setting and enable the EUT transmit continuously.
2. Use the following test receiver settings:  
Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel  
RBW = 1% to 5% of the 20dB bandwidth of the emission being measured,  $VBW \geq RBW$ ,  
Sweep = auto, Detector function = peak, Trace = max hold
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth. Record the results.
4. Repeat above procedures until all frequencies measured were complete.


### Limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900MHz. For devices operating above 900MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20dB down from the modulated carrier.

The limit for the EUT =  $0.25\% * 433.92 \text{ MHz} = 1084 \text{ kHz}$

### Test Result

Channel	20dB Bandwidth (KHz)	Limit (KHz)
1	82.442	$\leq 1084.8$



Date: 20.NOV.2024 08:53:18



## 10.4 Deactivation Time

### Test Method

1. Set to the maximum power setting and enable the EUT in transmitting mode.
2. Set center frequency of spectrum analyzer=operating frequency.
3. Set the spectrum analyzer as RBW=120 KHz, VBW=1MHz, Span=0Hz.
4. Repeat above procedures until all frequency measured was complete.

### Limit


According to FCC Part 15.231 (a), the transmitter shall be complied the following requirements:  
 (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

(2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.

(3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour.

### Test Result

Channel	Frequency	Deactivation Time	Limit	Result
1	433.92MHz	391.3ms	≤5S	Pass



Date: 20.NOV.2024 08:46:49

## 11 Test Equipment List

### List of Test Instruments

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
RE	EMI Test Receiver	Rohde & Schwarz	ESR3	101906	2024-8-1	2025-7-31
	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2024-8-1	2025-7-31
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9168	961	2024-8-30	2025-8-29
	Horn Antenna	Rohde & Schwarz	HF907	102393	2024-4-14	2025-4-13
	Pre-amplifier	Shenzhen HzEMC	HPA-081843	HYPAA23026	2024-4-16	2025-4-15
	Loop antenna	Rohde & Schwarz	HFH2-Z2	100443	2024-6-26	2025-6-25
	Double Ridged Horn Antenna	ETS-Lindgren	3116C	00246076	2023-7-7	2026-7-6
	3m Semi-anechoic chamber	TDK	9X6X6	----	2024-5-8	2027-5-7
CE	EMI Test Receiver	Rohde & Schwarz	ESR3	101907	2024-8-1	2025-7-31
	LISN	Rohde & Schwarz	ENV216	101924	2024-8-1	2025-7-31

### Measurement Software Information

Test Item	Software	Manufacturer	Version
RE	EMC 32	Rohde & Schwarz	V10.50.40
CE	EMC 32	Rohde & Schwarz	V9.15.03

## 12 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Items	Extended Uncertainty
Conducted Disturbance	9kHz to 30MHz, 3.16dB (AMN)
Radiated Disturbance	9kHz to 30MHz, 3.52dB 30MHz to 1GHz, 5.03dB (Horizontal) 5.12dB (Vertical) 1GHz to 18GHz, 5.49dB 18GHz to 40GHz, 5.63dB

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2023, clause 4.3.3.

-----End of Test Report-----