



FCC PART 15B, CLASS B

MEASUREMENT AND TEST REPORT

For

Nexpro International Limitada

San Jose-Goicoechea, Guadalupe, Barrio Tournon, frente Al Hotel Villas Tournon,

Oficinas Del Bufete Facio Y Canas, Costa Rica

FCC ID: ZYPE580

Report Type: Original Report	Product Type: GSM Mobile Phone
Test Engineer: <u>Eros Du</u>	
Report Number: <u>RDG110916007-00</u>	
Report Date: <u>2011-10-20</u>	
Reviewed By: <u>EMC Engineer</u>	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk “★” (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION.....	.3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)3
OBJECTIVE3
RELATED SUBMITTAL(S)/GRANT(S).....	.3
TEST FACILITY3
SYSTEM TEST CONFIGURATION.....	4
DESCRIPTION OF TEST CONFIGURATION4
EUT EXERCISE SOFTWARE4
EQUIPMENT MODIFICATIONS4
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS4
EXTERNAL I/O CABLE.....	.4
CONFIGURATION OF TEST SETUP5
BLOCK DIAGRAM OF TEST SETUP6
SUMMARY OF TEST RESULTS	7
FCC §15.107 – AC LINE CONDUCTED EMISSIONS	8
MEASUREMENT UNCERTAINTY8
EUT SETUP8
EMI TEST RECEIVER SETUP.....	.9
TEST EQUIPMENT LIST AND DETAILS.....	.9
TEST PROCEDURE9
TEST RESULTS SUMMARY9
TEST DATA9
FCC §15.109 - RADIATED EMISSIONS	14
MEASUREMENT UNCERTAINTY14
EUT SETUP14
EMI TEST RECEIVER SETUP.....	.15
TEST PROCEDURE15
TEST EQUIPMENT LIST AND DETAILS.....	.15
CORRECTED AMPLITUDE & MARGIN CALCULATION15
TEST RESULTS SUMMARY15
TEST DATA16

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Nexpro International Limitada*'s product, model number: *E580 (FCC ID: ZYPE580)* (the "EUT") in this report was a *GSM Mobile Phone*, which was measured approximately: 7.0 cm (L) x 7.0 cm (W) x 1.8 cm (H), rated input voltage: DC 3.7V battery or DC 5.2 V from adapter for charging.

Adaptor information: ADAPTADOR ca/cc
ENTRADA: 100-240Vca 50/60 Hz 120mA
SALIDA: 5.2Vcc 500mA

** All measurement and test data in this report was gathered from production sample serial number: 1108066 (Assigned by BACL, Shenzhen). The EUT was received on 2011-09-16.*

Objective

This report is prepared on behalf of *Nexpro International Limitada* in accordance with Part 2, Subpart J, Part 15- Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15B, Class B.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS, Part 22H&24E PCE submissions with FCC ID: ZYPE580

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical mode which is provided by manufacturer.

EUT Exercise Software

No exercise software

Equipment Modifications

No modification was made to the EUT tested.

Local Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Laptop	D600	85RF831
HP	Laser Jet5L	C3941A	JPTVOB2337
SAST	Modem	AEM-2100	0293

External I/O Cable


Cable Description	Length (m)	From/Port	To
Shielded Detachable Printer Cable	1.8	Parallel Port/Host	Printer
Shielded Detachable Serial Cable	1.8	Serial Port/Host	Modem
Shielded Detachable USB Cable	0.85	EUT	Laptop

Configuration of Test Setup

For downloading mode




For Charging&media playing mode




Block Diagram of Test Setup

For downloading mode



For Charging&media playing mode



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	AC Line Conducted Emissions	Compliance
§15.109	Radiated Emissions	Compliance


FCC §15.107 – AC LINE CONDUCTED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is ± 2.4 dB.(k=2, 95% level of confidence)

EUT Setup



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMIN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.107 Class B limits.

The spacing between the peripherals was 10 cm.

The adapter of laptop was connected to a 120 VAC/60 Hz power source for downloading mode.

The adapter was connected to a 120 VAC/60 Hz power source for charging & media playing mode.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	830245/006	2011-03-03	2012-03-02
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2011-03-09	2012-03-08

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

During the conducted emission test, for downloading mode, the adapter of laptop was connected to the outlet of the first LISN and the other relevant support equipments were connected to the outlet of the second LISN. For charging&media playing mode, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.107, with the worst margin reading of:

8.75 dB at 8.845 MHz in the Line conducted mode for Downloading mode

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	48 %
ATM Pressure:	100.0 kPa

The testing was performed by Eros Du on 2011-10-10.

Test Mode: Downloading

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (PK/QP/Ave.)
8.845	41.25	10.10	50.00	8.75	Ave.
1.610	36.61	10.10	46.00	9.39	Ave.
0.805	32.96	10.10	46.00	13.04	Ave.
1.610	42.79	10.10	56.00	13.21	QP
8.845	41.32	10.10	60.00	18.68	QP
0.805	33.60	10.10	56.00	22.40	QP
14.770	27.25	10.10	50.00	22.75	Ave.
14.815	29.89	10.10	60.00	30.11	QP
0.540	15.38	10.10	46.00	30.62	Ave.
0.350	25.09	10.10	60.29	35.20	QP
0.350	12.76	10.10	50.29	37.53	Ave.
0.540	17.75	10.10	56.00	38.25	QP


AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (PK/QP/Ave.)
8.845	38.79	10.10	50.00	11.21	Ave.
1.610	34.26	10.10	46.00	11.74	Ave.
1.205	33.41	10.10	46.00	12.59	Ave.
0.200	40.33	10.10	54.57	14.24	Ave.
1.610	39.86	10.10	56.00	16.14	QP
4.825	29.72	10.10	46.00	16.28	Ave.
8.845	38.58	10.10	60.00	21.42	QP
1.205	33.33	10.10	56.00	22.67	QP
0.200	40.91	10.10	64.57	23.66	QP
4.825	30.73	10.10	56.00	25.27	QP
14.865	23.32	10.10	50.00	26.68	Ave.
14.745	28.91	10.10	60.00	31.09	QP


Test Mode: Charging & media playing

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (PK/QP/Ave.)
0.400	29.04	10.10	48.86	19.82	Ave.
0.400	35.05	10.10	58.86	23.81	QP
3.200	18.58	10.10	46.00	27.42	Ave.
3.205	24.55	10.10	56.00	31.45	QP
2.180	13.15	10.10	46.00	32.85	Ave.
0.880	12.41	10.10	46.00	33.59	Ave.
5.310	13.99	10.10	50.00	36.01	Ave.
0.880	18.79	10.10	56.00	37.21	QP
2.180	18.17	10.10	56.00	37.83	QP
5.335	19.71	10.10	60.00	40.29	QP
28.585	9.19	10.10	50.00	40.81	Ave.
28.585	13.47	10.10	60.00	46.53	QP

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (PK/QP/Ave.)
0.405	32.61	10.10	48.71	16.10	Ave.
0.405	37.37	10.10	58.71	21.34	QP
9.980	26.45	10.10	50.00	23.55	Ave.
4.905	22.12	10.10	46.00	23.88	Ave.
4.930	26.98	10.10	56.00	29.02	QP
1.610	15.99	10.10	46.00	30.01	Ave.
7.015	18.67	10.10	50.00	31.33	Ave.
1.610	24.30	10.10	56.00	31.70	QP
7.000	21.75	10.10	60.00	38.25	QP
9.980	17.40	10.10	60.00	42.60	QP
27.690	7.22	10.10	50.00	42.78	Ave.
27.635	11.12	10.10	60.00	48.88	QP


FCC §15.109 - RADIATED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is ± 4.0 dB. ($k=2$, 95% level of confidence)

EUT Setup



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter of laptop was connected to a 120 VAC/60 Hz power source for downloading mode.

The adapter was connected to a 120 VAC/60 Hz power source for charging&media playing mode.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 1000 MHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency	RB/W	VB/W	IF B/W	Detection
30 MHz-1 GHz	100 kHz	300 kHz	120 kHz	Quasi-peak

Test Procedure

During the radiated emissions test, for downloading mode, the adapter of laptop and all the other relevant equipments were connected to AC floor outlet. For charging&media playing mode, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detection mode from 30 MHz to 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447E	1937A01046	2011-08-02	2012-08-02
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2011-07-05	2012-07-04

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp (Shenzhen). attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109 Class B, with the worst margin reading of:

3.2 dB at 40.795250 MHz in the **Vertical** polarization for charging&media playing mode

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	48 %
ATM Pressure:	100.0 kPa

The testing was performed by Eros Du on 2011-10-09.

Test Mode: Downloading


Auto Test(FCC 15 Class B)



Frequency (MHz)	Corrected Amplitude (dB μ V/m)	Test Antenna		Turntable Position (degree)	Correction Factor (dB)	Limit (dB μ V/m)	Margin (dB)
		Height (cm)	Polarity (H/V)				
54.660500	34.4	102.0	V	183.0	-18.0	40.0	5.6
142.871750	28.2	101.0	V	146.0	-13.4	43.5	15.3
48.995750	23.9	137.0	V	162.0	-16.9	40.0	16.1
86.275750	23.3	159.0	V	164.0	-17.8	40.0	16.7
151.929750	21.8	102.0	V	146.0	-14.1	43.5	21.7
566.380750	23.0	139.0	H	237.0	-7.2	46.0	23.0

Test Mode: Charging & media playing

Auto Test(FCC 15 Class B)



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Test Antenna		Turntable Position (degree)	Correction Factor (dB)	Limit (dBμV/m)	Margin (dB)
		Height (cm)	Polarity (H/V)				
40.795250	36.8	101.0	V	215.0	-12.6	40.0	3.2*
42.111000	34.8	101.0	V	212.0	-13.4	40.0	5.2
31.369750	24.8	102.0	V	179.0	-6.4	40.0	15.2
50.635750	21.3	102.0	V	149.0	-17.4	40.0	18.7
904.621500	22.6	192.0	V	168.0	-0.7	46.0	23.4
814.425250	20.5	203.0	V	233.0	-1.6	46.0	25.5

*Within measurement uncertainty!

***** END OF REPORT *****