

Date: 2018-06-28

Report Number: 60.790.18.021.01

Model No.: PX102 FCC ID: ZZNPX102

Radiofrequency radiation exposure evaluation

According to KDB 447498 D01v06 section 4.3.1, For frequencies between 100 MHz to 6GHz and test separation distances ≤ 50 mm, the Numeric threshold is determined as:

Step a)

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR

>> The fundamental frequency of the EUT is 2402-2480MHz, the test separation distance is ≤ 50mm.

(Manufacturer specified the separation distance is: 20mm)

Step a)

- >> Numeric threshold (2402MHz), mW / 20mm * $\sqrt{2.402}$ GHz ≤ 3.0 Numeric threshold (2402MHz) ≤ 38.713 mW
- >> Numeric threshold (2440MHz), mW / 20mm * $\sqrt{2.440}$ GHz ≤ 3.0 Numeric threshold (2440MHz) ≤ 38.411 mW
- >> Numeric threshold (2480MHz), mW / 20mm * $\sqrt{2.480}$ GHz ≤ 3.0 Numeric threshold (2480MHz) ≤ 38.100 mW
- >> The power of EUT measured (2402MHz) is: 1.69dBm = 1.476mW The power of EUT measured (2440MHz) is: 1.05dBm = 1.273mW The power of EUT measured (2480MHz) is: 0.27dBm = 1.064mW

Which is smaller than the Numeric threshold.

Therefore, the device is exempt from stand-alone SAR test requirements.

Page 1 of 1
TÜV SÜD Certification and Testing (China) Co., Ltd.
Shenzhen Branch Building 12&13, Zhiheng Wisdomland Business Park, Nantou Checkpoint Road 2, Nanshan District, 518052 Shenzhen, CHINA