



FCC PART 22H, PART 24E TEST REPORT

For

CDM MIAMI INC

1825 NW 112th AVE, UNIT 158, MIAMI, FL 33172

FCC ID: ZZRTM0723

Report Type: Product Type:
Original Report GSM Mobile Phone

Test Engineer: Tiger Ye

Report Number: RSZ120605001-00C

Report Date: 2012-06-18

Alvin Huang

Reviewed By: RF Leader

Test Laboratory: Bay Area Compliance Laboratories Corp. (Shenzhen)

6/F, the 3rd Phase of WanLi Industrial Building

Tiger He

ShiHua Road, FuTian Free Trade Zone

Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008

www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "★" (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	
EQUIPMENT MODIFICATIONS	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	7
FCC §1.1307 & §2.1093 - RF EXPOSURE	8
APPLICABLE STANDARD	
TEST RESULT	
FCC §2.1047 - MODULATION CHARACTERISTIC	9
FCC § 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER	10
APPLICABLE STANDARD	
Test Procedure	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §2.1049, §22.917, §22.905 & §24.238 - BANDWIDTH	
APPLICABLE STANDARD	
Test Procedure	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	
APPLICABLE STANDARD	
Test Procedure	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS	21
APPLICABLE STANDARD	21
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	22
FCC §22.917(A) & §24.238(A) - BAND EDGES	23
APPLICABLE STANDARD	
Test Procedure	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY	27
APPLICABLE STANDARD	
Test Procedure	27

Report No.: RSZ120605001-00C

Bay Ar	ea Com	pliance	Laborator	ies Corr	. (Shenzhen
--------	--------	---------	-----------	----------	-------------

PRODUCT SIMILAR	RITY DECLARATION LETT	ER	30
TEST DATA			28
TEST EQUIPMENT LIS	ST AND DETAILS		28

Report No.: RSZ120605001-00C

FCC Part 22H/24E Page 3 of 30

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *CDM MIAMI INC*'s product, model number: *FIESTA (FCC ID: ZZRTM0723)* or the "EUT" in this report was a *GSM Mobile Phone*, which was measured approximately: 11.2 cm (L) x 5.8 cm (W) x 1.2 cm (H), rated input voltage: DC 3.7 V Li-ion battery.

Report No.: RSZ120605001-00C

Frequency Range:

Cellular Band: 824-849 MHz (Tx), 869-894 MHz (Rx) PCS Band: 1850-1910 MHz (Tx), 1930-1990 MHz (Rx)

Bluetooth: 2402-2480 MHz (Tx/ Rx)

Modulation Mode: GMSK (Cellular/PCS); GFSK, π/4-DQPSK, 8DPSK (Bluetooth)

Transmitter Output Power:

Cellular Band: 31.83 dBm (Conducted Power) PCS Band: 29.38 dBm (Conducted Power) Bluetooth: -0.6 dBm (Conducted power)

Note: The product, model FIESTA, N700, LUMINUM, N800, they are electrically identical, only different in model No. and appearance color. Model FIESTA was selected for full testing, which was explained for details in the attached declaration letter.

* All measurement and test data in this report was gathered from production sample serial number: 1206013 (Assigned by BACL, Shenzhen). The EUT was received on 2012-06-05.

Objective

This test report is prepared on behalf of *CDM MIAMI INC* in accordance with Part 2-Subpart J, Part 22-Subpart H, and Part 24-Subpart E of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS and Part 15B JBP submissions with FCC ID: ZZRTM0723.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2-Subpart J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-D, ANSI C63.4-2009.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FCC Part 22H/24E Page 4 of 30

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Report No.: RSZ120605001-00C

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at http://ts.nist.gov/Standards/scopes/2007070.htm

FCC Part 22H/24E Page 5 of 30

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-D.


The GSM/PCS item test was performed with the EUT operating at normal mode.

The GPRS item test was performed with the EUT operating at testing mode.

Equipment Modifications

No modification was made to the EUT.

Block Diagram of Test Setup



Report No.: RSZ120605001-00C

FCC Part 22H/24E Page 6 of 30

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliance*
\$2.1046; \$ 22.913 (a); \$ 24.232 (c)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238	Occupied Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053 § 22.917 (a); § 24.238 (a)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a)	Out of band emission, Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Report No.: RSZ120605001-00C

Note: * Please refer to SAR report released by BACL, report number: RSZ120605001-20.

FCC Part 22H/24E Page 7 of 30

FCC §1.1307 & §2.1093 - RF EXPOSURE

Report No.: RSZ120605001-00C

Applicable Standard

FCC§1.1307 and §2.1093.

Test Result

Compliance, please refer to the SAR report: RSZ120605001-20.

FCC Part 22H/24E Page 8 of 30

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC $\S 2.1047(d)$, Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

Report No.: RSZ120605001-00C

FCC Part 22H/24E Page 9 of 30

FCC § 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.


Report No.: RSZ120605001-00C

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.



Radiated method:

TIA 603-D section 2.2.17

Test Equipment List and Details

Manufacturer	Description Model		Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2012-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2012-11-27
HP	Synthesized Sweeper	8341B	2624A00116	2012-04-11	2013-04-10
COM POWER	Dipole Antenna	AD-100	041000	2011-09-25	2012-09-25
A.H. System	Horn Antenna	SAS-200/571	135	2012-02-11	2013-02-10
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2012-04-11	2013-04-10

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

FCC Part 22H/24E Page 10 of 30

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Tiger Ye on 2012-06-10.

Conducted Power

Cellular Band (Part 22H)

Report No.: RSZ120605001-00C

Mode	Channel	Channel Frequency (MHz)		Limit (dBm)
	128	824.2	31.50	38.45
GSM	190	836.6	31.76	38.45
	251	848.8	31.83	38.45

Mode	Frequency		Limit			
Mioue	(MHz)	Slot 1	Slot 2	Slot 3	Slot 4	(dBm)
	824.2	31.50	31.44	Not s	38.45	
GPRS	836.6	31.72	31.70	Not supported		38.45
	848.8	31.81	31.74	Not s	supported	38.45

PCS Band (Part 24E)

Mode	Channel	Channel Frequency (MHz)		Limit (dBm)
	512	1850.2	29.14	33
GSM	661	1880.0	29.29	33
	810	1909.8	29.38	33

Mode	Frequency		Limit			
Mode	(MHz)	Slot 1	Slot 2	Slot 3	Slot 4	(dBm)
	1850.2	29.07	28.46	Not s	Not supported	
GPRS	1880.0	29.27	28.85	Not s	supported	33
	1909.8	29.35	28.95	Not s	supported	33

FCC Part 22H/24E Page 11 of 30

Radiated Power

ERP & EIRP

ERP for Cellular Band (Part 22H)

Report No.: RSZ120605001-00C

Indic	cated	Table	Test Antenna		Substituted			Antenna	Cable	Absolute	Part 22H
Frequency (MHz)	S.A. Reading (dBµV)	Angle Degree	Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)	Gain Correction (dBd)	Loss (dB)	Level (dBm)	Limit (dBm)
	High Channel										
848.8	98.54	79	1.9	Н	848.8	27.5	Н	0.00	0.68	26.82	38.45
848.8	103.11	112	1.6	V	848.8	32.1	V	0.00	0.68	31.42	38.45

EIRP for PCS Band (Part 24E)

Indic	cated	Table	Test Antenna		Substituted			Antenna	Cable	Absolute	Part 24E	
Frequency (MHz)	S.A. Reading (dBµV)	Angle Degree	Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)	Gain Correction (dBi)	Loss (dB)	Level (dBm)	Limit (dBm)	
	High Channel											
1909.8	117.51	341	2.3	Н	1909.8	17.0	Н	9.40	1.03	25.37	33	
1909.8	115.84	48	1.9	V	1909.8	20.4	V	9.40	1.03	28.77	33	

FCC Part 22H/24E Page 12 of 30

FCC §2.1049, §22.917, §22.905 & §24.238 - BANDWIDTH

Applicable Standard


FCC §2.1049, §22.917, §22.905 and §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 3 kHz (Cellular /PCS) and the 26 dB & 99% bandwidth was recorded.

Report No.: RSZ120605001-00C



Test Equipment List and Details

Manufacturer	Description	Description Model Serial Number		Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2012-04-11	2013-04-10

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56%
ATM Pressure:	100.0kPa

The testing was performed by Tiger Ye on 2012-05-21.

FCC Part 22H/24E Page 13 of 30

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following tables and plots.

GMSK Modulation:

Cellular Band (Part 22H)

Report No.: RSZ120605001-00C

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
190	836.6	242.5	316.6

PCS Band (Part 24E)


Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
661	1880.0	246.5	314.6

FCC Part 22H/24E Page 14 of 30


Cellular Band (Part 22H)

99% Occupied Bandwidth

Report No.: RSZ120605001-00C



26 dB Bandwidth




FCC Part 22H/24E Page 15 of 30


PCS Band (Part 24E)

99% Occupied Bandwidth

Report No.: RSZ120605001-00C



26 dB Bandwidth



FCC Part 22H/24E Page 16 of 30

FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Report No.: RSZ120605001-00C


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

Manufacturer	Description Model		Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2012-04-11	2013-04-10
Wainwright Germany	Band Reject Filter	WRCG1850/1910- 1835/1925-40/8SS	22	2012-02-28	2013-02-28
Wainwright Germany	Band Reject Filter	WRCG823/850- 813/860-40/8SS	7	2012-02-28	2013-02-28
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa


The testing was performed by Tiger Ye on 2012-05-21.

Please refer to the following plots.

FCC Part 22H/24E Page 17 of 30


Cellular Band (Part 22H)

30 MHz - 1 GHz - Middle Channel



Report No.: RSZ120605001-00C

1 GHz – 10 GHz - Middle Channel




FCC Part 22H/24E Page 18 of 30


PCS Band (Part 24E)

30 MHz – 1 GHz - Middle Channel

Report No.: RSZ120605001-00C




1 GHz - 2 GHz - Middle Channel



FCC Part 22H/24E Page 19 of 30

2 GHz - 10 GHz - Middle Channel

Report No.: RSZ120605001-00C



FCC Part 22H/24E Page 20 of 30

FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

Report No.: RSZ120605001-00C

Applicable Standard

FCC § 2.1053, §22.917 and § 24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in $dB = 10 \lg (TXpwr in Watts/0.001) - the absolute level$

Spurious attenuation limit in $dB = 43 + 10 \text{ Log}_{10}$ (power out in Watts)

Test Equipment List and Details

Manufacturer	Description	Description Model Serial Number		Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2012-11-30
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2012-11-27
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23
SUPER ULTRA	Amplifier	ZVA-213+	N/A	2011-11-24	2012-11-23
НР	Amplifier	HP8447D	2944A09795	2011-11-24	2012-11-23
HP	Synthesized Sweeper	8341B	2624A00116	2012-04-11	2013-04-10
COM POWER	Dipole Antenna	AD-100	041000	2011-09-25	2012-09-25
A.H. System	Horn Antenna	SAS-200/571	135	2012-02-11	2013-02-10
Electro-Mechanics	Horn Antenna	3116	9510-2270	2011-10-14	2012-10-13
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2012-04-11	2013-04-10

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

FCC Part 22H/24E Page 21 of 30

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Tiger Ye on 2012-05-21.

Test mode: Transmitting (worst case)

30 MHz ~ **10 GHz**:

Cellular Band (Part 22H)

Report No.: RSZ120605001-00C

Indica	ted	Table	Test A	ntenna		Substitu	ted		Absolute		
Frequency (MHz)	S.A. Reading (dBµV)	Angle Degree	Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dB)	Cable Loss (dB)	Level (dBm)	Limit (dBm)	Margin (dB)
	Middle Channel										
417.6	35.6	240	2.8	Н	417.6	-59.7	0	0.41	-60.11	-13	47.11
417.6	34.3	58	1.7	V	417.6	-60.5	0	0.41	-60.91	-13	47.91
1673.2	69.18	57	2.1	Н	1673.2	-33.9	9.0	0.97	-25.87	-13	12.87
1673.2	71.61	114	1.6	V	1673.2	-28.8	9.0	0.97	-20.77	-13	7.77
2509.8	54.74	241	1.8	Н	2509.8	-46.0	10.2	1.46	-37.26	-13	24.26
2509.8	54.05	123	1.7	V	2509.8	-42.3	10.2	1.46	-33.56	-13	20.56
3346.4	56.91	347	2.3	Н	3346.4	-37.5	11.5	2.08	-28.08	-13	15.08
3346.4	51.16	25	1.9	V	3346.4	-42.4	11.5	2.08	-32.98	-13	19.98

30 MHz ~ 20 GHz:

PCS Band (Part 24E)

Indica	ted	Table	Test A	ntenna		Substitu	ted		Absolute		
Frequency (MHz)	S.A. Reading (dBµV)	Angle	Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dB)	Cable Loss (dB)	Level (dBm)	Limit (dBm)	Margin (dB)
	Middle Channel										
520.3	36.8	240	2.8	Н	520.3	-58.5	0	0.45	-58.95	-13	45.95
520.3	35.6	58	1.7	V	520.3	-59.2	0	0.45	-59.65	-13	46.65
3760	71.04	52	2.1	Н	3760	-25.9	12.0	2.96	-16.86	-13	3.86
3760	66.22	147	1.9	V	3760	-29.9	12.0	2.96	-20.86	-13	7.86
5640	51.15	236	1.8	Н	5640	-41.2	12.4	3.94	-32.74	-13	19.74
5640	48.08	138	1.6	V	5640	-43.1	12.4	3.94	-34.64	-13	21.64
7520	46.62	69	2.1	Н	7520	-41.6	10.5	3.07	-34.17	-13	21.17
7520	43.21	185	1.9	V	7520	-46.2	10.5	3.07	-38.77	-13	25.77

FCC Part 22H/24E Page 22 of 30

FCC §22.917(a) & §24.238(a) - BAND EDGES

Applicable Standard

According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.


Report No.: RSZ120605001-00C

According to \$24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency, RBW set to 3 kHz.



Test Equipment List and Details

Manufacturer	Description	ription Model Serial Number		Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2012-04-11	2013-04-10

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Tiger Ye on 2012-05-21.

FCC Part 22H/24E Page 23 of 30

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following tables and plots.

Cellular Band (Part 22H)

Report No.: RSZ120605001-00C

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.977	-19.30	<-13
849.022	-18.83	<-13


PCS Band (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.981	-26.32	<-13
1910.022	-24.72	<-13


FCC Part 22H/24E Page 24 of 30

Cellular Band, Left Band Edge

Report No.: RSZ120605001-00C




Cellular Band, Right Band Edge




FCC Part 22H/24E Page 25 of 30

PCS Band, Left Band Edge

Report No.: RSZ120605001-00C



PCS Band, Right Band Edge



FCC Part 22H/24E Page 26 of 30

FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055 (a), § 2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobil	ile Services
--	--------------

Report No.: RSZ120605001-00C

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



FCC Part 22H/24E Page 27 of 30

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2011-11-24	2012-11-23
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2012-04-11	2013-04-10

Report No.: RSZ120605001-00C

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Tiger Ye on 2012-05-21.

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following tables.

Cellular Band (Part 22H)

Middle Channel, f ₀ =836.6 MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30		10	0.011953	2.5
-20		12	0.014344	2.5
-10		15	0.01793	2.5
0		9	0.010758	2.5
10	3.7	14	0.016734	2.5
20		16	0.019125	2.5
30		8	0.009563	2.5
40		15	0.017930	2.5
50		12	0.014344	2.5
25	V _{max.} = 4.2	13	0.015539	2.5
25	V _{min.} = 3.5	11	0.013148	2.5

FCC Part 22H/24E Page 28 of 30

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

PCS Band (Part 24E)

Report No.: RSZ120605001-00C

Middle Channel, f _o =1880.0 MHz				
Temperature (℃)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30		14	0.007447	Pass
-20		15	0.007979	Pass
-10		16	0.008511	Pass
0		18	0.009574	Pass
10	3.7	20	0.010638	Pass
20		14	0.007447	Pass
30		12	0.006383	Pass
40		10	0.005319	Pass
50		15	0.007979	Pass
25	V _{max.} = 4.2	9	0.004787	Pass
25	V _{min.} = 3.5	8	0.004255	Pass

FCC Part 22H/24E Page 29 of 30

PRODUCT SIMILARITY DECLARATION LETTER



CDM MIAMI INC 1825 NW 112TH AVE., UNIT 158, MIAMI FL, 33172

TEL: 305 477 6433 FAX: 305 477 6432

2012-6-18

Product Similarity Declaration

To Whom It May Concern,

We, CDM MIAMI INC. hereby declare that our GSM Mobile Phone, Trade Mark: FUN, Model Number: N700, LUMINUM, N800 are electrically identical with the FIESTA that was certified by BACL. They are just different in model number and appearance design in terms of housing colors due to marketing purposes.

Report No.: RSZ120605001-00C

Please contact me if you have any question.

Signature: Dennis Tang

DENNIS TANG
Marketing Director

***** END OF REPORT *****

FCC Part 22H/24E Page 30 of 30