

RF EXPOSURE EVALUATION

EUT Specification

EUT	GSM Cell Phone
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input checked="" type="checkbox"/> Others(Bluetooth: 2.402GHz ~ 2.480GHz)
Device category	<input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	3.02dBm (2.01mW) for Bluetooth 7.87dBm (6.12mW) for WIFI (Max. AVG output power)
Antenna gain	2.3 dBi
Evaluation applied	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

Standard Requirement

Portable Device

According to §15.247(i) and §1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v05, section 4.3.1.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16}$ where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Measurement Result

Channel	Channel Frequency (MHz)	Max Output Peak power (dBm)	Max Output Peak power (mW)	Calculation Value ^(Note 1)	Threshold Value
Bluetooth (GFSK)					
Low	2402	2.24	1.68	0.521	3.0
Middle	2441	2.56	1.80	0.563	3.0
High	2480	3.02	2.01	0.633	3.0
Bluetooth (π4/-DQPSK)					
Low	2402	0.15	1.04	0.322	3.0
Middle	2441	1.09	1.29	0.403	3.0
High	2480	1.05	1.27	0.400	3.0
Bluetooth (8DPSK)					
Low	2402	0.17	1.04	0.322	3.0
Middle	2441	0.57	1.14	0.356	3.0
High	2480	1.07	1.28	0.403	3.0

Note 1: Calculation Value =[(max. power of channel, mW)/(min.

test separation distance, mm)] • [√ f(GHz)].

For example: $1.80/5^* \sqrt{2.441}=0.563 \leq 3.0$

Note 2: The maximum peak output power (turn-up power) in low channel of BT is 3.5dBm(2.24mw), the calculation value= $2.24/5^* \sqrt{2.402}=0.694 \leq 3.0$

The maximum peak output power (turn-up power) in middle channel of BT is 3.5dBm(2.24mw), the calculation value= $2.24/5^* \sqrt{2.441}=0.700 \leq 3.0$

The maximum peak output power (turn-up power) in high channel of BT is 3.5dBm(2.24mw), the calculation value= $2.24/5^* \sqrt{2.480}=0.706 \leq 3.0$

Channel	Channel Frequency (MHz)	Max Output Peak power (dBm)	Max Output AVG power (mW)	Calculation Value ^(Note 1)	Threshold Value
WIFI (802.11b)					
Low	2412	6.38	4.35	1.320	3.0
Middle	2437	6.06	4.04	1.261	3.0
High	2462	4.40	2.75	0.863	3.0
WIFI (802.11g)					
Low	2412	7.87	6.12	1.901	3.0
Middle	2437	6.36	4.33	1.352	3.0
High	2462	5.59	3.62	1.136	3.0
WIFI [802.11n(HT20)]					
Low	2412	5.48	3.53	1.097	3.0
Middle	2437	4.08	2.56	0.799	3.0
High	2462	3.27	2.12	0.665	3.0

Note 1: Calculation Value =[(max. power of channel, mW)/(min.

test separation distance, mm)] • [√ f(GHz)].

For example: $6.12/5 * \sqrt{2.412} = 1.901 \leq 3.0$

Note 2: The maximum average output power (turn-up power) in low channel of WIFI is 8.0dBm(6.31mw), the calculation value= $6.31/5 * \sqrt{2.412} = 1.960 \leq 3.0$

The maximum average output power (turn-up power) in middle channel of WIFI is 8.0dBm(6.31mw), the calculation value= $6.31/5 * \sqrt{2.437} = 1.970 \leq 3.0$

The maximum average output power (turn-up power) in high channel of WIFI is 8.0dBm(6.31mw), the calculation value= $6.31/5 * \sqrt{2.462} = 1.980 \leq 3.0$

According to KDB447498 D01 v05, threshold at which no SAR required is ≤ 3.0 for 1-g SAR, separation distance is 5mm, and no simultaneous SAR measurement is required.

Sincerely,



(signature)

Dennis Tang
 Marketing Director
 Tel: 305-477-6433 Fax: 305-717-2453
 E-mail: Dennistech@126.com
 Address: 3100 NW 72nd Ave., Unit 118, Miami FL 33122