

RF EXPOSURE COMPLIANCE REQUIREMENT

1.1.Rules Part No.

15.247(b)

1.2.Limit

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1). (b)(2). and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

1.3.Test Procedure

EUT RF Exposure

(1) BLUETOOTH MODE

The Max Conducted Peak Output Power is **0.75dBm(1.189mW)** in lowest channel (2.402GHz);

The best case gain of the antenna is 1dBi(1.26 numeric).

According to the formula. calculate the EIRP test result:

$$\text{EIRP} = P \times G = 1.189\text{mW} \times 1.26 = 1.498\text{mW} \quad ①$$

SAR requirement:

$$② \quad S = 60 / f(\text{GHz}) = 60/2.402 = 24.98\text{mW} \quad ②;$$

$$① < ②.$$

So the SAR report is not required.

(2) WIFI MODE

The Max Conducted Peak Output Power is **11.24dBm(13.305mW)** in lowest channel (2.412GHz);

The best case gain of the antenna is 1dBi(1.26 numeric).

According to the formula. calculate the EIRP test result:

$$\text{EIRP} = P \times G = 13.305\text{mW} \times 1.26 = 16.764\text{mW} \quad ①$$

SAR requirement:

$$② \quad S = 60 / f(\text{GHz}) = 60/2.412 = 24.87\text{mW} \quad ②;$$

$$① < ②.$$

So the SAR report is not required.