



## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,  
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM170500530002  
Page: 1 of 104

# TEST REPORT

**Application No.:** SZEM1705005300CR  
**Applicant:** Camino International Limited  
**Address of Applicant:** FLAT A, 3/F, INTERNATIONAL INDUSTRIAL BUILDING 501-503 CASTLE PEAK ROAD, Chueng Sha Wan, Kowlong, Hong Kong  
**Manufacturer:** Camino International Limited  
**Address of Manufacturer:** FLAT A, 3/F, INTERNATIONAL INDUSTRIAL BUILDING 501-503 CASTLE PEAK ROAD, Chueng Sha Wan, Kowlong, Hong Kong  
**Equipment Under Test (EUT):**  
**EUT Name:** Optimus Prime Bluetooth Speaker  
**Model No.:** 761602  
**Trade mark:** Hasbro  
**FCC ID:** ZZX602  
**Standards:** 47 CFR Part 15, Subpart C 15.247  
**Date of Receipt:** 2017-06-07  
**Date of Test:** 2017-06-15 to 2017-06-22  
**Date of Issue:** 2017-06-29

<b>Test Result :</b>	Pass*
----------------------	-------

\* In the configuration tested, the EUT complied with the standards specified above.



Jack Zhang  
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

<b>Revision Record</b>				
<b>Version</b>	<b>Chapter</b>	<b>Date</b>	<b>Modifier</b>	<b>Remark</b>
01		2017-06-29		Original

<b>Authorized for issue by:</b>			
			
	<b>Peter Geng /Project Engineer</b>		
			
	<b>Eric Fu /Reviewer</b>		

## 2 Test Summary

<b>Radio Spectrum Technical Requirement</b>				
<b>Item</b>	<b>Standard</b>	<b>Method</b>	<b>Requirement</b>	<b>Result</b>
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)	Pass

<b>Radio Spectrum Matter Part</b>				
<b>Item</b>	<b>Standard</b>	<b>Method</b>	<b>Requirement</b>	<b>Result</b>
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(1)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

### 3 Contents

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 TEST SUMMARY .....</b>	<b>3</b>
<b>3 CONTENTS .....</b>	<b>4</b>
<b>4 GENERAL INFORMATION.....</b>	<b>6</b>
4.1 DETAILS OF E.U.T .....	6
4.2 DESCRIPTION OF SUPPORT UNITS .....	6
4.3 MEASUREMENT UNCERTAINTY .....	7
4.4 TEST LOCATION .....	8
4.5 TEST FACILITY .....	8
4.6 DEVIATION FROM STANDARDS.....	8
4.7 ABNORMALITIES FROM STANDARD CONDITIONS .....	8
<b>5 EQUIPMENT LIST .....</b>	<b>9</b>
<b>6 RADIO SPECTRUM TECHNICAL REQUIREMENT.....</b>	<b>12</b>
6.1 ANTENNA REQUIREMENT .....	12
6.1.1 <i>Test Requirement:</i> .....	12
6.1.2 <i>Conclusion</i> .....	12
6.2 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM HOPPING SEQUENCE.....	13
6.2.1 <i>Test Requirement:</i> .....	13
6.2.2 <i>Conclusion</i> .....	13
<b>7 RADIO SPECTRUM MATTER TEST RESULTS .....</b>	<b>14</b>
7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) .....	14
7.1.1 <i>E.U.T. Operation</i> .....	15
7.1.2 <i>Test Setup Diagram</i> .....	15
7.1.3 <i>Measurement Procedure and Data</i> .....	15
7.2 CONDUCTED PEAK OUTPUT POWER.....	20
7.2.1 <i>E.U.T. Operation</i> .....	21
7.2.2 <i>Test Setup Diagram</i> .....	21
7.2.3 <i>Measurement Procedure and Data</i> .....	21
7.3 20dB BANDWIDTH.....	22
7.3.1 <i>E.U.T. Operation</i> .....	22
7.3.2 <i>Test Setup Diagram</i> .....	22
7.3.3 <i>Measurement Procedure and Data</i> .....	22
7.4 CARRIER FREQUENCIES SEPARATION .....	23
7.4.1 <i>E.U.T. Operation</i> .....	23
7.4.2 <i>Test Setup Diagram</i> .....	23
7.4.3 <i>Measurement Procedure and Data</i> .....	23
7.5 HOPPING CHANNEL NUMBER .....	24
7.5.1 <i>E.U.T. Operation</i> .....	24
7.5.2 <i>Test Setup Diagram</i> .....	24
7.5.3 <i>Measurement Procedure and Data</i> .....	24
7.6 DWELL TIME .....	25
7.6.1 <i>E.U.T. Operation</i> .....	25
7.6.2 <i>Test Setup Diagram</i> .....	25
7.6.3 <i>Measurement Procedure and Data</i> .....	25

7.7	CONDUCTED BAND EDGES MEASUREMENT .....	26
7.7.1	<i>E.U.T. Operation</i> .....	26
7.7.2	<i>Test Setup Diagram</i> .....	26
7.7.3	<i>Measurement Procedure and Data</i> .....	26
7.8	CONDUCTED SPURIOUS EMISSIONS.....	27
7.8.1	<i>E.U.T. Operation</i> .....	27
7.8.2	<i>Test Setup Diagram</i> .....	27
7.8.3	<i>Measurement Procedure and Data</i> .....	27
7.9	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS .....	28
7.9.1	<i>E.U.T. Operation</i> .....	28
7.9.2	<i>Test Setup Diagram</i> .....	28
7.9.3	<i>Measurement Procedure and Data</i> .....	29
7.10	RADIATED SPURIOUS EMISSIONS.....	34
7.10.1	<i>E.U.T. Operation</i> .....	35
7.10.2	<i>Test Setup Diagram</i> .....	35
7.10.3	<i>Measurement Procedure and Data</i> .....	36
<b>8</b>	<b>PHOTOGRAPHS .....</b>	<b>49</b>
8.1	CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) TEST SETUP.....	49
8.2	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS TEST SETUP .....	49
8.3	RADIATED SPURIOUS EMISSIONS TEST SETUP.....	50
8.4	EUT CONSTRUCTIONAL DETAILS .....	50
<b>9</b>	<b>APPENDIX.....</b>	<b>51</b>
9.1	APPENDIX 15.247 .....	51-104

## **4 General Information**

### **4.1 Details of E.U.T.**

Power supply: #1 adapter  
SWITCH MODE POWER SUPPLY  
MODEL: AS360-150-AD240  
INPUT: AC 100-240V, 50/60Hz  
OUTPUT: DC 15V, 2.4A

#2 adapter  
SWITCH MODE POWER SUPPLY  
MODEL: AS360-150-AA240  
INPUT: AC 100-240V, 50/60Hz  
OUTPUT: DC 15V, 2.4A

remark: both adapter were involved in the test (Conducted Emissions at AC Power Line (150kHz-30MHz) and Radiated Spurious Emissions below 1GHz), the one (#1) is detachable and the other one (#2) is not

Operation Frequency: 2402MHz~2480MHz  
Bluetooth Version: 4.0 Dual mode  
Modulation Type: This is for classic mode.  
Number of Channel: 79  
Antenna Type: PIFA  
Antenna Gain: 0dBi

### **4.2 Description of Support Units**

The EUT was tested as an independently unit

### 4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10-8
2	Duty cycle	0.37%
3	Occupied Bandwidth	3%
4	RF conducted power	0.75dB
5	RF power density	2.84dB
6	Conducted Spurious emissions	0.75dB
7	RF Radiated power	4.5dB (below 1GHz) 4.8dB (above 1GHz)
8	Radiated Spurious emission test	4.5dB (30MHz-1GHz) 4.8dB (1GHz-18GHz)
9	Temperature test	1 °C
10	Humidity test	3%
11	Supply voltages	1.5%
12	Time	3%

#### **4.4 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.  
518057.

Tel: +86 755 2601 2053      Fax: +86 755 2671 0594

No tests were sub-contracted.

#### **4.5 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

#### **4.6 Deviation from Standards**

None

#### **4.7 Abnormalities from Standard Conditions**

None

## 5 Equipment List

<b>Conducted Emissions at AC Power Line (150kHz-30MHz)</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2017-05-10	2018-05-10
LISN	Rohde & Schwarz	ENV216	SEM007-01	2016-10-09	2017-10-09
LISN	ETS-LINDGREN	3816/2	SEM007-02	2017-04-14	2018-04-13
8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	2016-09-28	2017-09-28
4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	2016-09-28	2017-09-28
2 Line ISN	Fischer Custom	FCC-TLISN-T2-02	EMC0122	2016-09-28	2017-09-28

<b>Conducted Peak Output Power</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

<b>20dB Bandwidth</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

<b>Carrier Frequencies Separation</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

**Hopping Channel Number**

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

**Dwell Time**

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

**Conducted Band Edges Measurement**

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

**Conducted Spurious Emissions**

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

**General used equipment**

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2016-10-12	2017-10-12
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2017-04-18	2018-04-18

**RE in Chamber**

Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2017-05-10	2018-05-10
EMI Test Receiver (9k-7GHz)	Rohde & Schwarz	ESR	SEM004-03	2017-04-14	2018-04-13
Trilog-Broadband Antenna (30M-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016-06-29	2019-06-29
Pre-amplifier (9kHz-1GHz)	Sonoma Instrument Co	310N	SEM005-04	2017-06-05	2018-06-04
.Loop Antenna (9kHz-30MHz)	ETS-Lindgren	6502	SEM003-08	2015-08-14	2018-08-14

**RE in Chamber**

Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2017-05-10	2018-05-10
EXA Signal Analyzer (10Hz-26.5GHz)	Agilent Technologies Inc	N9010A	SEM004-09	2017-06-05	2018-06-04
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2014-11-01	2017-11-01
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-13
Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2016-10-09	2017-10-09
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2016-10-09	2017-10-09
Band filter	N/A	N/A	N/A	N/A	N/A

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(c)

#### 6.1.2 Conclusion

Standard Requirment:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.



## **6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence**

### **6.2.1 Test Requirement:**

47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)

### **6.2.2 Conclusion**

Standard Requirment:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1):

According to Technical Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- > Number of shift register stages: 9
- > Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- > Longest sequence of zeros: 8 (non-inverted signal)

Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

Each frequency used equally on the average by each transmitter.

According to Technical Specification, the receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g):

According to Technical Specification, the system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h):

According to Technical specification, the system incorporates with an adaptive system to detect other user within the spectrum band so that it individ

## **7 Radio Spectrum Matter Test Results**

### **7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)**

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


\*Decreases with the logarithm of the frequency.

### 7.1.1 E.U.T. Operation

## Operating Environment:

Temperature: 24 °C      Humidity: 54 % RH      Atmospheric Pressure: 1005 mbar  
Test mode b:TX\_non-Hop mode\_Keep the EUT in continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.1.2 Test Setup Diagram




### 7.1.3 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50µH + 50hm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

#1 adapter

Mode:b; Line:Live Line



Site : Shielding Room


Condition : CE LINE

Job NO : 05300CR

Mode : b

	Freq	Cable	LISN	Read	Limit	Over	Remark
		Loss	Factor	Level	Level	Line	
	MHz	dB	dB	dBuV	dBuV	dBuV	
1 @	0.15240	0.02	9.64	42.78	52.44	55.87	-3.43 Peak
2 @	0.16854	0.02	9.64	42.27	51.93	55.03	-3.10 Peak
3	0.20723	0.02	9.64	39.18	48.84	53.32	-4.48 Peak
4	0.22556	0.02	9.64	37.85	47.51	52.61	-5.10 Peak
5	0.34463	0.02	9.64	35.71	45.37	49.09	-3.73 Peak
6	3.454	0.02	9.70	31.83	41.56	46.00	-4.44 Peak

Mode:b; Line:Live Line




Site : Shielding Room  
Condition : CE LINE  
Job NO : 05300CR  
Mode : b

	Freq	Cable	LISN	Read	Limit	Over	Remark
		Loss	Factor	Level			
	MHz	dB	dB	dBuV	dBuV	dBuV	dB
1	0.15080	0.02	9.64	43.18	52.84	55.96	-3.12 Peak
2	0.15567	0.02	9.64	42.58	52.24	55.69	-3.45 Peak
3	0.17399	0.02	9.64	40.86	50.52	54.77	-4.24 Peak
4	0.20505	0.02	9.64	38.80	48.46	53.40	-4.95 Peak
5	0.31999	0.02	9.64	36.09	45.75	49.71	-3.96 Peak
6	3.190	0.02	9.69	27.96	37.68	46.00	-8.32 Peak

#2 adapter

Mode:b; Line:Neutral Line



Site : Shielding Room


Condition : CE NEUTRAL

Job NO : 05300CR

Mode : b

	Freq	Cable	LISN	Read	Limit	Over	Remark
		Loss	Factor	Level			
	MHz	dB	dB	dBuV	dBuV	dBuV	dB
1 @	0.15816	0.02	9.64	42.36	52.02	55.56	-3.54 Peak
2	0.17215	0.02	9.63	41.27	50.92	54.86	-3.93 Peak
3	0.19344	0.02	9.63	38.27	47.92	53.89	-5.97 Peak
4	0.20075	0.02	9.63	37.91	47.56	53.58	-6.02 Peak
5 @	0.34281	0.02	9.63	36.19	45.84	49.13	-3.29 Peak
6	3.156	0.03	9.67	30.78	40.48	46.00	-5.52 Peak

Mode:b; Line:Neutral Line



Site : Shielding Room  
 Condition : CE NEUTRAL  
 Job NO : 05300CR  
 Mode : b

	Freq	Cable	LISN	Read	Limit	Over	Remark
		Loss	Factor	Level	Level	Line	
	MHz	dB	dB	dBuV	dBuV	dBuV	
1 @	0.15403	0.02	9.64	42.66	52.32	55.78	-3.46 Peak
2	0.16241	0.02	9.63	41.94	51.60	55.34	-3.74 Peak
3	0.18838	0.02	9.63	40.34	49.99	54.11	-4.11 Peak
4	0.25078	0.02	9.63	37.24	46.89	51.73	-4.84 Peak
5	0.30834	0.02	9.63	36.29	45.94	50.02	-4.08 Peak
6	2.487	0.03	9.66	31.95	41.64	46.00	-4.36 Peak

## 7.2 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(1)

Test Method: ANSI C63.10 (2013) Section 7.8.5


Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

**7.2.1 E.U.T. Operation**

Operating Environment:

Temperature: 25 °C      Humidity: 55 % RH      Atmospheric Pressure: 1005 mbar  
Test mode b:TX\_non-Hop mode\_Keep the EUT in continuously transmitting mode with GFSK modulation, π/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

**7.2.2 Test Setup Diagram****7.2.3 Measurement Procedure and Data**

The detailed test data see: Appendix 15.247

### 7.3 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247(a)(1)

Test Method: ANSI C63.10 (2013) Section 7.8.7


#### 7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode b:TX\_non-Hop mode\_Keep the EUT in continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

#### 7.3.2 Test Setup Diagram



#### 7.3.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.4 Carrier Frequencies Separation


Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)  
Test Method: ANSI C63.10 (2013) Section 7.8.2  
Limit: 2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W

### 7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C      Humidity: 55 % RH      Atmospheric Pressure: 1005 mbar  
Test mode a:TX\_Hop mode\_Keep the EUT in frequency hopping mode with GFSK modulation, π/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.4.2 Test Setup Diagram



### 7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.5 Hopping Channel Number

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(iii)

Test Method: ANSI C63.10 (2013) Section 7.8.3

Limit:

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth $\geq$ 250kHz
2400-2483.5	15
5725-5850	75


### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX\_Hop mode\_Keep the EUT in frequency hopping mode with GFSK modulation, π/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.5.2 Test Setup Diagram



### 7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.6 Dwell Time

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(iii)

Test Method: ANSI C63.10 (2013) Section 7.8.4

Limit:

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period


### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX\_Hop mode\_Keep the EUT in frequency hopping mode with GFSK modulation, π/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.6.2 Test Setup Diagram



### 7.6.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.7 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 7.8.6


### 7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode b:TX\_non-Hop mode\_Keep the EUT in continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.7.2 Test Setup Diagram



### 7.7.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.8 Conducted Spurious Emissions

Test Requirement	47 CFR Part 15, Subpart C 15.247(d)
Test Method:	ANSI C63.10 (2013) Section 7.8.8
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.


### 7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C      Humidity: 55 % RH      Atmospheric Pressure: 1005 mbar

Test mode b:TX\_non-Hop mode\_Keep the EUT in continuously transmitting mode with GFSK modulation, π/4DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.8.2 Test Setup Diagram



### 7.8.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.9 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m


### 7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C Humidity: 54 % RH Atmospheric Pressure: 1005 mbar

Test mode b:TX\_non-Hop mode\_Keep the EUT in continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.


### 7.9.2 Test Setup Diagram



### **7.9.3 Measurement Procedure and Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Mode:b; Polarization:Horizontal; Modulation Type:GFSK; Channel:Low




Condition: 3m HORIZONTAL

Job No: : 05300CR

Mode: : 2402 Band edge  
: BT

		Cable Freq	Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Level	Over Line Limit	Over Line Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2362.072	5.32	28.99	37.96	46.61	42.96	74.00	-31.04	peak	
2	2390.000	5.34	29.08	37.96	43.90	40.36	74.00	-33.64	peak	
3	pp 2402.148	5.35	29.11	37.96	97.04	93.54	74.00	19.54	peak	

Mode:b; Polarization:Vertical; Modulation Type:GFSK; Channel:Low




Condition: 3m VERTICAL

Job No: : 05300CR

Mode: : 2402 Band edge  
: BT

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2384.399	5.33	29.06	37.96	46.47	42.90	74.00	-31.10	peak
2	2390.000	5.34	29.08	37.96	44.23	40.69	74.00	-33.31	peak
3 pp	2402.148	5.35	29.11	37.96	95.85	92.35	74.00	18.35	peak

Mode:b; Polarization:Horizontal; Modulation Type:GFSK; Channel:High




Condition: 3m HORIZONTAL

Job No: : 05300CR

Mode: : 2480 Band edge  
: BT

		Cable Freq	Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp	2479.731	5.41	29.34	37.95	99.35	96.15	74.00	22.15	peak
2		2483.500	5.41	29.35	37.95	51.04	47.85	74.00	-26.15	peak
3		2483.971	5.41	29.35	37.95	53.79	50.60	74.00	-23.40	Peak

Mode:b; Polarization:Vertical; Modulation Type:GFSK; Channel:High



**7.10 Radiated Spurious Emissions**

Test Requirement 47 CFR Part 15, Subpart C 15.205 &amp; 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Measurement Distance: 10m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### 7.10.1 E.U.T. Operation

Operating Environment:

Temperature: 24 °C      Humidity: 54 % RH      Atmospheric Pressure: 1005 mbar  
 Test mode b:TX\_non-Hop mode\_Keep the EUT in continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.10.2 Test Setup Diagram




### **7.10.3 Measurement Procedure and Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

**Radiated Emission below 1GHz****#1 adapter**

Mode:b; Polarization:Horizontal




Condition: 10m HORIZONTAL

Job No. : 05300CR

Test Mode: b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	39.99	7.08	13.32	32.99	26.59	14.00	29.50	-15.50
2	149.49	7.46	13.38	32.74	26.71	14.81	33.10	-18.29
3	199.99	7.34	9.29	32.70	36.47	20.40	33.10	-12.70
4	312.18	8.13	13.01	32.60	31.79	20.33	35.60	-15.27
5	560.69	8.97	17.92	32.60	29.84	24.13	35.60	-11.47
6 pp	818.83	9.79	21.37	32.58	27.64	26.22	35.60	-9.38

Mode:b; Polarization:Vertical



Condition: 10m VERTICAL

Job No. : 05300CR

Test Mode: b

	Freq	Cable	Ant	Preamp	Read	Limit	Over	Limit
		Loss	Factor	Factor	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp	50.59	6.19	12.73	33.00	37.71	23.63	29.50
2		109.80	7.48	10.35	32.79	34.38	19.42	33.10
3		129.92	7.47	12.03	32.76	34.81	21.55	33.10
4		383.93	8.41	14.56	32.60	27.93	18.30	35.60
5		647.39	9.29	19.50	32.60	27.93	24.12	35.60
6		929.01	10.10	22.59	32.50	27.10	27.29	35.60
								-8.31

**Below 1GHz**

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

$L_3$ : Level @ 3m distance. Unit: uV/m;

$L_{10}$ : Level @ 10m distance. Unit: uV/m;

$D_3$ : 3m distance. Unit: m


$D_{10}$ : 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
50.59	23.63	15.19	50.63	34.09	40.00	-5.91	V
109.80	19.42	9.35	31.18	29.88	43.50	-13.62	V
129.92	21.55	11.95	39.85	32.01	43.50	-11.49	V
383.93	18.30	8.22	27.41	28.76	46.00	-17.24	V
647.39	24.12	16.07	53.56	34.58	46.00	-11.42	V
929.01	27.29	23.15	77.16	37.75	46.00	-8.25	V
39.99	14.00	5.01	16.71	24.46	40.00	-15.54	H
149.49	14.81	5.50	18.34	25.27	43.50	-18.23	H
199.99	20.40	10.47	34.90	30.86	43.50	-12.64	H
312.18	20.33	10.39	34.62	30.79	46.00	-15.21	H
560.69	24.13	16.09	53.63	34.59	46.00	-11.41	H
818.83	26.22	20.46	68.21	36.68	46.00	-9.32	H

**#2 adapter**

Mode:b; Polarization:Horizontal




Condition: 10m HORIZONTAL

Job No. : 05300CR

Test Mode: b

Freq	Cable	Ant	Preamp	Read	Limit	Over	dB
	Loss	Factor	Factor	Level	Level	Line	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	
1	35.38	6.99	12.69	32.98	26.37	13.07	29.50 -16.43
2	60.28	6.35	11.94	32.95	26.68	12.02	29.50 -17.48
3	160.35	7.46	13.36	32.73	26.92	15.01	33.10 -18.09
4	308.91	8.11	12.92	32.60	28.01	16.44	35.60 -19.16
5	560.69	8.97	17.92	32.60	32.22	26.51	35.60 -9.09
6 pp	804.60	9.78	21.26	32.60	28.84	27.28	35.60 -8.32

Mode:b; Polarization:Vertical



Condition: 10m VERTICAL

Job No. : 05300CR

Test Mode: b

	Freq	Cable	Ant	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	32.63	6.98	12.56	32.97	30.72	17.29	29.50	-12.21
2	63.31	6.65	11.33	32.93	32.66	17.71	29.50	-11.79
3 pp	175.04	7.37	11.65	32.72	36.40	22.70	33.10	-10.40
4	289.00	8.01	12.39	32.61	33.18	20.97	35.60	-14.63
5	566.62	8.98	18.03	32.60	27.84	22.25	35.60	-13.35
6	975.75	10.22	22.81	32.50	26.55	27.08	43.50	-16.42

**Below 1GHz**

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

$L_3$ : Level @ 3m distance. Unit:  $\mu$ V/m;

$L_{10}$ : Level @ 10m distance. Unit:  $\mu$ V/m;

$D_3$ : 3m distance. Unit: m


$D_{10}$ : 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m ( $\mu$ V/m)	Level @ 3m ( $\mu$ V/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
32.63	17.29	7.32	24.40	27.75	40.00	-12.25	V
63.31	17.71	7.68	25.61	28.17	40.00	-11.83	V
175.04	22.70	13.65	45.49	33.16	43.50	-10.34	V
289.00	20.97	11.18	37.27	31.43	46.00	-14.57	V
566.62	22.25	12.96	43.19	32.71	46.00	-13.29	V
975.75	27.08	22.59	75.31	37.54	54.00	-16.46	V
35.38	13.07	4.50	15.01	23.53	40.00	-16.47	H
60.28	12.02	3.99	13.30	22.48	40.00	-17.52	H
160.35	15.01	5.63	18.77	25.47	43.50	-18.03	H
308.91	16.44	6.64	22.12	26.90	46.00	-19.10	H
560.69	26.51	21.16	70.53	36.97	46.00	-9.03	H
804.60	27.28	23.12	77.07	37.74	46.00	-8.26	H

**Transmitter Emission above 1GHz**

Mode:b; Polarization:Horizontal; Modulation Type:GFSK; Channel:Low




Condition: 3m HORIZONTAL

Job No: : 05300CR

Mode: : 2402 TX RSE  
: BT

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit		Over Line	Over Limit	Remark
					dBuV	dBuV/m			
1 1335.141	4.27	25.11	38.07	45.98	37.29	74.00	-36.71	peak	
2 4157.664	6.89	33.60	38.08	44.47	46.88	74.00	-27.12	peak	
3 pp 4804.000	7.73	34.16	38.40	47.15	50.64	54.00	-3.36	Average	
4 pk 4804.000	7.73	34.16	38.40	57.61	61.10	74.00	-12.90	Peak	
5 7206.000	9.65	36.42	37.11	42.95	51.91	74.00	-22.09	peak	
6 9608.000	11.06	37.52	35.10	38.40	51.88	74.00	-22.12	peak	
7 14873.890	14.82	41.08	38.91	35.41	52.40	74.00	-21.60	peak	

Mode:b; Polarization:Vertical; Modulation Type:GFSK; Channel:Low




Condition: 3m VERTICAL

Job No: : 05300CR

Mode: : 2402 TX RSE  
: BT

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit		Over Line	Over Limit	Remark
					dB	dB/m			
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1 1335.141	4.27	25.11	38.07	49.03	40.34	74.00	-33.66	peak	
2 4367.058	7.13	33.60	38.18	44.61	47.16	74.00	-26.84	peak	
3 pp 4804.000	7.73	34.16	38.40	46.64	50.13	54.00	-3.87	Average	
4 pk 4804.000	7.73	34.16	38.40	58.24	61.73	74.00	-12.27	Peak	
5 7206.000	9.65	36.42	37.11	42.56	51.52	74.00	-22.48	peak	
6 9608.000	11.06	37.52	35.10	37.64	51.12	74.00	-22.88	peak	
7 14830.960	14.81	41.00	38.92	34.75	51.64	74.00	-22.36	peak	

Mode:b; Polarization:Horizontal; Modulation Type:GFSK; Channel:middle




Condition: 3m HORIZONTAL

Job No: : 05300CR

Mode: : 2441 TX RSE  
: BT

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit		Over Line	Over Limit	Remark
					dB	dB/m			
MHz									
1	1335.141	4.27	25.11	38.07	45.59	36.90	74.00	-37.10	peak
2	4367.058	7.13	33.60	38.18	44.13	46.68	74.00	-27.32	peak
3	pp 4882.000	7.84	34.30	38.44	46.35	50.05	54.00	-3.95	Average
4	pk 4882.000	7.84	34.30	38.44	59.00	62.70	74.00	-11.30	peak
5	7323.000	9.73	36.37	37.01	41.87	50.96	74.00	-23.04	peak
6	9764.000	11.21	37.55	35.02	38.17	51.91	74.00	-22.09	peak
7	14873.890	14.82	41.08	38.91	35.94	52.93	74.00	-21.07	peak

Mode:b; Polarization:Vertical; Modulation Type:GFSK; Channel:middle




Condition: 3m VERTICAL

Job No: : 05300CR

Mode: : 2441 TX RSE  
: BT

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over	
							dB	dB
1 1335.141	4.27	25.11	38.07	45.20	36.51	74.00	-37.49	peak
2 4392.376	7.16	33.60	38.20	44.92	47.48	74.00	-26.52	peak
3 pp 4882.000	7.84	34.30	38.44	46.58	50.28	54.00	-3.72	Average
4 pk 4882.000	7.84	34.30	38.44	56.58	60.28	74.00	-13.72	peak
5 7323.000	9.73	36.37	37.01	40.89	49.98	74.00	-24.02	peak
6 9764.000	11.21	37.55	35.02	37.46	51.20	74.00	-22.80	peak
7 15003.420	14.85	41.30	38.90	32.81	50.06	74.00	-23.94	peak

Mode:b; Polarization:Horizontal; Modulation Type:GFSK; Channel:High




Condition: 3m HORIZONTAL

Job No: : 05300CR

Mode: : 2480 TX RSE  
: BT

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit		Over Line	Over Limit	Remark
					dB	dB/m			
MHz									
1	1597.181	4.59	26.24	38.04	43.77	36.56	74.00	-37.44	peak
2	4291.977	7.05	33.60	38.15	44.05	46.55	74.00	-27.45	peak
3 pp	4960.000	7.95	34.43	38.48	46.45	50.35	54.00	-3.65	Average
4 pk	4960.000	7.95	34.43	38.48	57.45	61.35	74.00	-12.65	peak
5	7440.000	9.81	36.32	36.90	41.61	50.84	74.00	-23.16	peak
6	9920.000	11.36	37.58	34.94	36.82	50.82	74.00	-23.18	peak
7	14788.150	14.80	40.92	38.92	34.40	51.20	74.00	-22.80	peak

Mode:b; Polarization:Vertical; Modulation Type:GFSK; Channel:High



Condition: 3m VERTICAL


Job No: : 05300CR

Mode: : 2480 TX RSE  
: BT


Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over	
							dB	dB
1 1308.399	4.23	24.99	38.07	44.96	36.11	74.00	-37.89	peak
2 4341.886	7.10	33.60	38.17	43.65	46.18	74.00	-27.82	peak
3 pp 4960.000	7.95	34.43	38.48	46.10	50.00	54.00	-4.00	Average
4 pk 4960.000	7.95	34.43	38.48	57.10	61.00	74.00	-13.00	peak
5 7440.000	9.81	36.32	36.90	41.22	50.45	74.00	-23.55	peak
6 9920.000	11.36	37.58	34.94	38.07	52.07	74.00	-21.93	peak
7 14830.960	14.81	41.00	38.92	34.93	51.82	74.00	-22.18	peak

## 8 Photographs

### 8.1 Conducted Emissions at AC Power Line (150kHz-30MHz) Test Setup



### 8.2 Radiated Emissions which fall in the restricted bands Test Setup



### 8.3 Radiated Spurious Emissions Test Setup



### 8.4 EUT Constructional Details


Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1705005300CR.


## 9 Appendix


### 9.1 Appendix 15.247


#### 1.20 dB Bandwidth


Test Mode	Test Channel	Ant	EBW[MHz]	Limit[MHz]	Verdict
DH5	2402	Ant1	0.952	---	PASS
DH5	2441	Ant1	0.946	---	PASS
DH5	2480	Ant1	0.946	---	PASS
2DH5	2402	Ant1	1.260	---	PASS
2DH5	2441	Ant1	1.260	---	PASS
2DH5	2480	Ant1	1.260	---	PASS
3DH5	2402	Ant1	1.262	---	PASS
3DH5	2441	Ant1	1.256	---	PASS
3DH5	2480	Ant1	1.256	---	PASS














**2.Conducted Peak Output Power**


Test Mode	Test Channel	Ant	Power[dBm]	Limit[dBm]	Verdict
DH5	2402	Ant1	3.51	<20.97	PASS
DH5	2441	Ant1	4.16	<20.97	PASS
DH5	2480	Ant1	4.03	<20.97	PASS
2DH5	2402	Ant1	3.29	<20.97	PASS
2DH5	2441	Ant1	4.87	<20.97	PASS
2DH5	2480	Ant1	4.54	<20.97	PASS
3DH5	2402	Ant1	3.89	<20.97	PASS
3DH5	2441	Ant1	3.96	<20.97	PASS
3DH5	2480	Ant1	4.87	<20.97	PASS









Conducted Peak Output Power\_3DH5\_2402\_ANT1




## Conducted Peak Output Power\_3DH5\_2441\_ANT1






**3.Carrier Frequency Separation**


Test Mode	Test Channel	Ant	Result[MHz]	Limit[MHz]	Verdict
DH5	2441	Ant1	0.981	$\geq 0.635$ (2/3 20 dB bandwidth)	PASS
2DH5	2441	Ant1	1.002	$\geq 0.840$ (2/3 20 dB bandwidth)	PASS
3DH5	2441	Ant1	1.005	$\geq 0.841$ (2/3 20 dB bandwidth)	PASS








**4.Dwell Time**


Test Mode	Test Channel	Ant	Burst Width[ms/hop/ch]	Total Hops[hop*ch]	Dwell Time[s]	Limit[s]	Verdict
DH1	2402	Ant1	0.39	320	0.125	<0.4	PASS
DH3	2402	Ant1	1.65	160	0.264	<0.4	PASS
DH5	2402	Ant1	2.9	110	0.319	<0.4	PASS
2DH1	2402	Ant1	0.4	310	0.124	<0.4	PASS
2DH3	2402	Ant1	1.66	160	0.266	<0.4	PASS
2DH5	2402	Ant1	2.9	100	0.29	<0.4	PASS
3DH1	2402	Ant1	0.4	320	0.128	<0.4	PASS
3DH3	2402	Ant1	1.66	160	0.266	<0.4	PASS
3DH5	2402	Ant1	2.9	110	0.319	<0.4	PASS


























**5.Hopping Channel Number**


Test Mode	Test Channel	Ant	Number of Hopping Channel[N]	Limit[N]	Verdict
DH5	2402	Ant1	79	>=15	PASS
2DH5	2402	Ant1	79	>=15	PASS
3DH5	2402	Ant1	79	>=15	PASS








**6.Band-edge for RF Conducted Emissions**


Test Mode	Test Channel	Ant	Hopping	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit[dBm ]	Verdict
DH5	2402	Ant1	On	3.300	-52.895	<-16.7	PASS
DH5	2402	Ant1	Off	2.930	-58.841	<-17.07	PASS
DH5	2480	Ant1	On	3.630	-53.587	<-16.37	PASS
DH5	2480	Ant1	Off	3.160	-55.950	<-16.84	PASS
2DH5	2402	Ant1	On	0.750	-54.817	<-19.25	PASS
2DH5	2402	Ant1	Off	1.160	-59.972	<-18.84	PASS
2DH5	2480	Ant1	On	1.750	-55.456	<-18.25	PASS
2DH5	2480	Ant1	Off	1.980	-58.066	<-18.02	PASS
3DH5	2402	Ant1	On	0.060	-54.571	<-19.94	PASS
3DH5	2402	Ant1	Off	1.380	-61.793	<-18.62	PASS
3DH5	2480	Ant1	On	1.730	-55.333	<-18.27	PASS
3DH5	2480	Ant1	Off	2.050	-56.008	<-17.95	PASS

















**7.RF Conducted Spurious Emissions**


Test Mode	Test Channel	Ant	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
DH5	2402	Ant1	30	10000	1000	3000	2.89	-42.350	<-17.11	PASS
DH5	2402	Ant1	10000	25000	1000	3000	2.89	-63.540	<-17.11	PASS
DH5	2441	Ant1	30	10000	1000	3000	3.51	-42.930	<-16.49	PASS
DH5	2441	Ant1	10000	25000	1000	3000	3.51	-62.660	<-16.49	PASS
DH5	2480	Ant1	30	10000	1000	3000	3.3	-44.550	<-16.7	PASS
DH5	2480	Ant1	10000	25000	1000	3000	3.3	-63.550	<-16.7	PASS
2DH5	2402	Ant1	30	10000	1000	3000	1.22	-45.100	<-18.78	PASS
2DH5	2402	Ant1	10000	25000	1000	3000	1.22	-64.310	<-18.78	PASS
2DH5	2441	Ant1	30	10000	1000	3000	2.99	-44.720	<-17.01	PASS
2DH5	2441	Ant1	10000	25000	1000	3000	2.99	-65.010	<-17.01	PASS
2DH5	2480	Ant1	30	10000	1000	3000	1.6	-45.360	<-18.4	PASS
2DH5	2480	Ant1	10000	25000	1000	3000	1.6	-64.240	<-18.4	PASS
3DH5	2402	Ant1	30	10000	1000	3000	1.26	-44.910	<-18.74	PASS
3DH5	2402	Ant1	10000	25000	1000	3000	1.26	-64.920	<-18.74	PASS
3DH5	2441	Ant1	30	10000	1000	3000	1.2	-45.470	<-18.8	PASS
3DH5	2441	Ant1	10000	25000	1000	3000	1.2	-65.250	<-18.8	PASS
3DH5	2480	Ant1	30	10000	1000	3000	2.15	-45.110	<-17.85	PASS
3DH5	2480	Ant1	10000	25000	1000	3000	2.15	-64.900	<-17.85	PASS








RF Conducted Spurious Emissions_DH5_2441_ANT1											
Pref	 * RBW 100 kHz      Marker 1 [T1 ] * VBW 300 kHz      3.51 dBm Ref 10 dBm      SWT 10 ms      2.440900000 GHz * Att 10 dB										
	 1 PK MAXH										
	 10 Offset 0.9 dB D2 -16.49 dBm										
	 Start 2.4 GHz      10 MHz/      Stop 2.5 GHz										
CSE_1	 * RBW 1 MHz      Marker 2 [T1 ] * VBW 3 MHz      -42.93 dBm Ref 10 dBm      SWT 60 ms      4.881651250 GHz * Att 10 dB										
	 1 PK MAXH										
	 10 Offset 0.9 dB D2 -16.49 dBm										
	 Start 30 MHz      997 MHz/      Stop 10 GHz										























RF Conducted Spurious Emissions_3DH5_2402_ANT1	
Pref	<p>Ref 10 dBm * Att 10 dB * RBW 100 kHz Marker 1 [T1] 1.26 dBm  * VBW 300 kHz SWT 10 ms 2.401900000 GHz</p> <p>10 Offset 0.9 dB</p> <p>1 PK MAXH</p> <p>Start 2.4 GHz 10 MHz/ Stop 2.5 GHz</p> <p>A SGL LVL 3DB</p>
CSE_1	<p>Ref 10 dBm * Att 10 dB * RBW 1 MHz Marker 2 [T1] -44.91 dBm  * VBW 3 MHz SWT 60 ms 4.804383750 GHz</p> <p>10 Offset 0.9 dB</p> <p>1 PK MAXH</p> <p>Start 30 MHz 997 MHz/ Stop 10 GHz</p> <p>Marker 1 [T1] 2.58 dBm 2.401613750 GHz</p> <p>A SGL LVL 3DB</p>

