# XTREME TELECOM

# **GSM Mobile Phone**

Model: E71,XTV-71,MTV-71,E71C,HV-71C

3 November, 2011

Report No.: 11070102-FCC-RF-BT

(This report supersedes NONE)



Modifications made to the product: None

Compliance Engineer

# This Test Report is Issued Under the Authority of: | Analy Wang | Peter Cai

This test report may be reproduced in full only.

All Test Data Presented in this report is only applicable to presented Test sample.

Technical Manager

# RF Test Report





Serial#: 11070102-FCC-RF-BT Issue Date: 3 November, 2011 Page: 2 of 53 www.siemic.com.cn

# **Laboratory Introduction**

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to <u>testing</u> and <u>certification</u>, SIEMIC provides initial design reviews and <u>compliance management</u> through out a project. Our extensive experience with <u>China</u>, <u>Asia Pacific</u>, <u>North America</u>, <u>European</u>, <u>and international</u> compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the <u>global markets</u>.

**Accreditations for Conformity Assessment** 

Country/Region	Accreditation Body	Scope			
USA	FCC, A2LA	EMC , RF/Wireless , Telecom			
Canada	IC, A2LA, NIST	EMC, RF/Wireless , Telecom			
Taiwan	BSMI , NCC , NIST	EMC, RF, Telecom , Safety			
Hong Kong	OFTA , NIST	RF/Wireless ,Telecom			
Australia	NATA, NIST	EMC, RF, Telecom, Safety			
Korea	KCC/RRA, NIST	EMI, EMS, RF , Telecom, Safety			
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom			
Mexico	Mexico NOM, COFETEL, Caniety Safety, EMC , RF/Wireless,				
Europe	A2LA, NIST	EMC, RF, Telecom , Safety			

#### **Accreditations for Product Certifications**

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC , RF , Telecom
Canada	IC FCB , NIST	EMC , RF , Telecom
Singapore	iDA, NIST	EMC , RF , Telecom
EU	NB	EMC & R&TTE Directive



Serial#: 11070102-FCC-RF-BT Issue Date: 3 November, 2011 Page: 3 of 53 www.siemic.com.cn

This page has been left blank intentionally.

Serial#: 11070102-FCC-RF-BT Issue Date: 3 November, 2011 Page: 4 of 53 www.siemic.com.cn

# **CONTENTS**

1	EXECUTIVE SUMMARY & EUT INFORMATION	5
2	TECHNICAL DETAILS	6
	MODIFICATION	
	TEST SUMMARY	
	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	
	EX A. TEST INSTRUMENT & METHOD	
	EX B. EUT AND TEST SETUP PHOTOGRAPHS	
	EX C. TEST SETUP AND SUPPORTING EQUIPMENT	
	EX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST	
	EX E. SIEMIC ACCREDITATION CERTIFICATES	
-VININ	EA E. JIEWIO ACCREDITATION CERTIFICATES	. 34



11070102-FCC-RF-BT Serial#: www.siemic.com.cn

#### **Executive Summary & EUT information**

The purpose of this test programme was to demonstrate compliance of the F.CELL,XTREME, MAXCOM, Hi, and model: E71, XTV-71, MTV-71, E71C, HV-71C against the current Stipulated Standards. The GSM Mobile Phone has demonstrated compliance with the FCC 15.247:2010.

#### **EUT Information**

**EUT** 

Description

: GSM Mobile Phone

Model No : E71, XTV-71, MTV-71, E71C, HV-71C

Serial No

Powered by Power Adapter:

Trade Name: JXT Model No.: JY103

Input: 100-240VAC, 50-60Hz, 150mA

**Input Power** Output: DC5V-500mA

> Li-ion Battery: Trade Name: None

Rechargeable Battery: 3.7V

Capacity:1500mAh

Classification

Per Stipulated

: FCC 15.247:2010

**Test Standard** 



Serial#: 11070102-FCC-RF-BT Issue Date: 3 November, 2011 Page: 6 of 53 www.siemic.com.cn

	2 <u>TECHNICAL DETAILS</u>
Purpose	Compliance testing of GSM Mobile Phone model E71, XTV-71, MTV-71, E71C, HV-71C with stipulated standard
Applicant / Client	XTREME TELECOM Room 2202 International Science and Technology Building, Futian District, 3007 Shennan Road,Shenzhen,China
Manufacturer	XTREME TELECOM Room 2202 International Science and Technology Building, Futian District, 3007 Shennan Road,Shenzhen,China
Laboratory performing the tests	SIEMIC Nanjing (China) Laboratories NO.2-1,Longcang Dadao, Yuhua Economic Development Zone, Nanjing, China Tel:+86(25)86730128/86730129 Fax:+86(25)86730127 Email:info@siemic.com
Test report reference number	11070102-FCC-RF-BT
Date EUT received	29 September, 2011
Standard applied	FCC 15.247:2010
Dates of test (from – to)	27October, 2011~3 November,2011
No of Units :	#1
Equipment Category :	Spread Spectrum System/Device
Trade Name :	F.CELL,XTREME, MAXCOM, Hi
Model:	E71, XTV-71, MTV-71, E71C, HV-71C
RF OPERATING FREQUENCY (IES)	Bluetooth: 2402MHz-2480MHz GSM850 TX : 824.2 ~ 848.8 MHz RX :869.2 ~ 893.8 MHz PCS1900 TX : 1850.2 ~ 1909.8 MHz RX :1930.2 ~ 1989.8 MHz
NUMBER OF CHANNELS :	Bluetooth:79 300 (PCS1900) and 125 (PCS850)
MODULATION:	Bluetooth: GFSK GSM / GPRS : GMSK
FCC ID:	ZZZXTV71



Serial#: 11070102-FCC-RF-BT Issue Date: 3 November, 2011 Page: 7 of 53 www.siemic.com.cn

# 3 MODIFICATION

NONE

Serial#: 11070102-FCC-RF-BT Issue Date: 3 November, 2011 Page: 8 of 53 www.siemic.com.cn

# 4 TEST SUMMARY

The product was tested in accordance with the following specifications. All testing has been performed according to below product classification:

#### Spread Spectrum System/Device Test Results Summary

FCC Rules	Description of Test	Result
§15.247 (i), §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

Serial#: 11070102-FCC-RF-BT Issue Date: 3 November, 2011 Page: 9 of 53 www.siemic.com.cn

# 5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

# 5.1 §15.247 (i) and §2.1093 – RF Exposure

#### **Applicable Standard**

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Table 2 - Summary of SAR Evaluation Requirements for a Cell Phone with Multiple Transmitters

	Individual Transmitter	Simultaneous Transmission
Licensed Transmitters	Routine evaluation required	SAR not required: Unlicensed only
Unlicensed Transmitters	When there is no simultaneous transmission — o output ≤ 60/f: SAR not required o output > 60/f: stand-alone SAR required When there is simultaneous transmission — Stand-alone SAR not required when o output ≤ 2·P <sub>Ref</sub> and antenna is ≥ 5.0 cm from other antennas o output ≤ P <sub>Ref</sub> and antenna is ≥ 2.5 cm from other antennas o output ≤ P <sub>Ref</sub> and antenna is < 2.5 cm from other antennas, each with either output power ≤ P <sub>Ref</sub> or 1-g SAR < 1.2 W/kg Otherwise stand-alone SAR is required When stand-alone SAR is required o test SAR on highest output channel for each wireless mode and exposure condition o if SAR for highest output channel is > 50% of SAR limit, evaluate all channels according to normal procedures	o when stand-alone 1-g SAR is not required and antenna is ≥ 5 cm from other antennas  Licensed & Unlicensed  o when the sum of the 1-g SAR is < 1.6 W/kg for all simultaneous transmitting antennas  o when SAR to peak location separation ratio of simultaneous transmitting antenna pair is < 0.3  SAR required:  Licensed & Unlicensed antenna pairs with SAR to peak location separation ratio ≥ 0.3; test is only required for the configuration that results in the highest SAR in stand-alone configuration for each wireless mode and exposure condition  Note: simultaneous transmission exposure conditions for head and body can be different for different style phones; therefore, different test requirements may apply
Jaw, Mouth and Nose	Flat phantom SAR required  o when measurement is required in tight regions of SAM and it is not feasible or the results can be questionable due to probe tilt, calibration, positioning and orientation issues  o position rectangular and clam-shell phones according to flat phantom procedures and conduct SAR measurements for these specific locations	When simultaneous transmission SAR testing is required, contact the FCC Laboratory for interim guidance.



Serial#: 11070102-FCC-RF-BT Issue Date: 3 November, 2011 Page: 10 of 53 www.siemic.com.cn

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

Two antennas are available for the EUT, one is Bluetooth antenna, the other is GSM antenna. The distance between Bluetooth antenna and GSM antenna is less than 2.5cm, but the maximum 1-SAR is 0.421W/kg≤1.2 W/kg.According to KDB 648474. Stand-alone SAR for Bluetooth is not required. So no simultaneous SAR required.

Pacul	4.
Kesiii	ı.

The SAR measurement is exempt.

Serial#: 11070102-FCC-RF-BT Issue Date: 3 November, 2011 Page: 11 of 53 www.siemic.com.cn

#### 5.2 §15.203 - ANTENNA REQUIREMENT

#### Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT has 2 antennas, one is a PIFA antenna for Bluetooth, the gain is 1 dBi; other is a PIFA antenna for GSM/PCS, the gain is 1 dBi for GSM/PCS, which in accordance to section 15.203, please refer to the internal photos..

Result: Compliant.

 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 12 of 53

 www.siemic.com.cn

# 5.3 **§**15.207 (a) - CONDUCTED EMISSIONS

#### Requirement:

	Conducted limit (dBµV)			
Frequency of emission (MHz)	Quasi-peak	Average		
0.15–0.5	66 to 56*	56 to 46*		
0.5–5	56	46		
5–30	60	50		

<sup>\*</sup>Decreases with the logarithm of the frequency.

#### Procedures:


- 1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
- 2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
- 3. <u>Conducted Emissions Measurement Uncertainty</u>

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz - 30MHz (Average & Quasi-peak) is  $\pm 3.5dB$ .

4. Environmental Conditions Temperature 23°C Relative Humidity 50%


Atmospheric Pressure 1019mbar

5. Test date :29 October, 2011 Tested By : Andy Wang



#### Test Data

Frequency (MHz)	Quasi Peak (dBuV)	Limit (dBuV)	Margin (dB)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Factors (dB)
1.526	47.261	56.000	-8.739	39.443	46.000	-6.557	10.181
1.466	46.807	56.000	-9.193	39.659	46.000	-6.341	10.179
1.038	46.677	56.000	-9.323	40.676	46.000	-5.324	10.162
1.590	45.803	56.000	-10.197	36.778	46.000	-9.222	10.184
1.382	45.755	56.000	-10.245	26.535	46.000	-19.465	10.175
1.954	45.584	56.000	-10.416	36.852	46.000	-9.148	10.198



#### Test Data

Frequency (MHz)	Quasi Peak (dBuV)	Limit (dBuV)	Margin (dB)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Factors (dB)
1.530	47.105	56.000	-8.895	38.000	46.000	-8.000	10.181
1.102	46.532	56.000	-9.468	37.626	46.000	-8.374	10.164
1.590	45.692	56.000	-10.308	36.767	46.000	-9.233	10.184
1.966	45.332	56.000	-10.668	33.405	46.000	-12.595	10.199
2.022	45.103	56.000	-10.897	34.347	46.000	-11.653	10.200
0.962	45.053	56.000	-10.947	33.904	46.000	-12.096	10.164

 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 15 of 53

 www.siemic.com.cn

### 5.4 §15.209, §15.205 & §15.247(d) - Spurious Emissions

1. <u>All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.</u>

2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.

3. Radiated Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz & 1GHz above (3m & 10m) is +5.6/-4.5dB.

4. Environmental Conditions Temperature 23°C

Relative Humidity 50% Atmospheric Pressure 1019mbar

5. Test date: 31 October, 2011 Tested By: Andy Wang


Standard Requirement: The emissions from the Low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges.


Test Result: Pass

Serial#: 11070102-FCC-RF-BT Issue Date: 3 November, 2011 Page: 16 of 53 www.siemic.com.cn

#### 30-1000 MHz:

Test Mode: Transmitting





Test Data

Frequency (MHz)	Quasi Peak (dBuV/m)	Azimuth	Polarity(H /V)	Height (cm)	Factors (dB)	Limit (dBuV/m)	Margin (dB)
53.40	28.34	167.00	V	111.00	-36.52	40.00	-11.66
76.94	28.16	89.00	V	101.00	-38.07	40.00	-11.84
80.03	24.75	91.00	V	112.00	-37.50	40.00	-15.25
49.20	27.32	228.00	V	105.00	-34.77	40.00	-12.68
36.38	26.63	203.00	Н	118.00	-26.96	40.00	-13.37
59.15	25.89	103.00	Н	113.00	-37.37	40.00	-14.11

Note: The data which below 20 dB to the limit was not recorded.

 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 17 of 53

 www.siemic.com.cn

#### Above 1 GHz:

Note: Other Bluetooth modes were verified, only the result of worst case basic rate mode was presented.

#### Low Channel (2402 MHz)

Frequency	Substituted level	Detector	Direction	Height	Polarity	Ant.	Cable	Pre- Amp.	Cord.	Limit	Margin
(MHz)	(dBm)	(PK/AV)	(degree)	(m)	(H/V)	Factor	Loss	Gain	Amp.	(dBm)	(dB)
						(dB/m)	(dB)	(dB)	(dBmV/m)		
4804	39.38	AV	160	1.2	V	34.0	2.6	26.79	49.19	54	-4.81
4804	38.43	AV	150	1.2	Н	33.8	2.6	26.79	48.04	54	-5.96
4804	54.25	PK	180	1.1	V	34.0	2.6	26.79	64.06	74	-9.94
4804	53.77	PK	180	1.2	Н	33.8	2.6	26.79	63.38	74	-10.62
1108.39	34.52	AV	12	1.2	V	25.3	1.1	26.51	34.41	54	-19.59
1108.39	33.77	AV	35	1.1	Н	23.8	1.1	26.51	32.16	54	-21.84
1108.39	45.81	PK	80	1.2	V	23.8	1.1	26.51	44.20	74	-29.80
1108.39	46.96	PK	80	1.2	Н	25.3	1.1	26.51	46.85	74	-27.15

#### Middle Channel (2441 MHz)

Frequency	Substituted level	Detector	Direction	Height	Polarity	Ant.	Cable	Pre- Amp.	Cord.	Limit	Margin
(MHz)	(dBm)	(PK/AV)	(degree)	(m)	(H/V)	Factor	Loss	Gain	Amp.	(dBm)	(dB)
						(dB/m)	(dB)	(dB)	(dBmV/m)		
4882	37.12	AV	170	1.1	V	33.6	2.6	26.78	46.54	54	-7.46
4882	38.55	AV	170	1.3	Н	33.8	2.6	26.78	48.17	54	-5.83
4882	51.25	PK	180	1.2	V	33.6	2.6	26.78	60.67	74	-13.33
4882	52.31	PK	180	1.2	Н	33.8	2.6	26.78	61.93	74	-12.07
1414.73	32.45	AV	60	1.1	V	25.1	1.3	26.65	32.20	54	-21.8
1414.73	42.74	AV	60	1.1	Н	25.1	1.3	26.65	42.49	54	-11.51
1414.73	32.34	PK	20	1	V	25.3	1.3	26.65	32.29	74	-41.71
1414.73	42.35	PK	20	1.2	Н	25.3	1.3	26.65	42.30	74	-31.70

#### High Channel (2480 MHz)

Frequency	Substituted level	Detector	Direction	Height	Polarity	Ant.	Cable	Pre- Amp.	Cord.	Limit	Margin
(MHz)	(dBm)	(PK/AV)	(degree)	(m)	(H/V)	Factor	Loss	Gain	Amp.	(dBm)	(dB)
						(dB/m)	(dB)	(dB)	(dBmV/m)		
4960	36.28	AV	20	1.2	V	34.6	2.7	26.75	46.83	54	-7.17
4960	35.37	AV	20	1.1	Н	34.7	2.7	26.75	46.02	54	-7.98
4960	53.45	PK	120	1.2	V	34.6	2.7	26.75	64.00	74	-10.00
4960	51.14	PK	120	1.2	Н	34.7	2.7	26.75	61.79	74	-12.21
1478.15	31.12	AV	85	1.1	V	25.3	1.3	26.65	31.07	54	-22.93
1478.15	30.26	AV	85	1.2	Н	25.5	1.3	26.65	30.41	54	-23.59
1478.15	42.55	PK	130	1.3	V	25.3	1.3	26.65	42.50	74	-31.50
1478.15	42.32	PK	130	1.2	Н	25.5	1.3	26.65	42.47	74	-31.53

 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 18 of 53

 www.siemic.com.cn

#### Spurious emission in restricted band:

Frequency	Substituted level	Detector	Direction	Height	Polarity	Ant.	Cable	Pre- Amp.	Cord.	Limit	Margin
(MHz)	(dBm)	(PK/AV)	(degree)	(m)	(H/V)	Factor	Loss	Gain	Amp.	(dBm)	(dB)
						(dB/m)	(dB)	(dB)	(dBmV/m)		
2398.51	30.34	AV	80	1.1	V	30.1	1.8	26.83	35.41	54	-18.59
2485.24	30.71	AV	120	1.1	V	30.6	1.8	26.83	36.28	54	-17.72
2485.24	31.12	AV	60	1	Н	30.6	1.8	26.83	36.69	54	-17.31
2398.51	31.08	AV	20	1.2	Н	30.1	1.8	26.83	36.15	54	-17.85
2485.24	43.27	PK	10	1.1	V	30.6	1.8	26.83	48.84	74	-25.16
2398.51	42.07	PK	20	1.2	V	30.1	1.8	26.83	47.14	74	-26.86
2485.24	42.61	PK	30	1.2	Н	30.6	1.8	26.83	48.18	74	-25.82
2398.51	43.56	PK	20	1.2	Н	30.1	1.8	26.83	48.63	74	-25.37

 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 19 of 53

 www.siemic.com.cn

#### 5.5 §15.247(a) (1)-CHANNEL Separation Test

1. <u>Conducted Measurement</u>

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyzer was connected to the antenna terminal.

2. Environmental Conditions Temperature 22°C Relative Humidity 50%

Atmospheric Pressure 1019mbar

3. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the

range 30MHz - 40GHz is  $\pm 1.5dB$ .

4. Test date: 31 October, 2011 Tested By: Andy Wang

Requirement(s): According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

#### Procedures:

- 1. Place the EUT on the table and set it in hopping function transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = middle of hopping channel.
- 4. Set the spectrum analyzer as Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span, Video (or Average) Bandwidth (VBW) ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 5. Max hold, mark 2 peaks of hopping channel and record the 2 peaks frequency.


Test Mode: Transmitting

Channel	Channel Frequency (MHz)	Channel Separation (MHz)	Limit (kHz)	Result
Low Channel	2402			
Adjacency Channel	2403	1.004	701.333	<u>PASS</u>
Mid Channel	2441			
Adjacency Channel	2442	1.004	698.667	<u>PASS</u>
High Channel	2480			
Adjacency Channel	2479	1.004	698.667	<u>PASS</u>


Please refer to the following plots.

| Serial#: 11070102-FCC-RF-BT | Issue Date: 3 November, 2011 | Page: 20 of 53 | www.siemic.com.cn

#### **Low Channel**



#### **Middle Channel**




 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 21 of 53

 www.siemic.com.cn

#### **High Channel**



Serial#: 11070102-FCC-RF-BT Issue Date: 3 November, 2011 Page: 22 of 53 www.siemic.com.cn

#### §15.247(a) (1) – 20 dB BANDWIDTH TESTING

1. <u>Conducted Measurement</u>

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyzer was connected to the antenna terminal.

2. Environmental Conditions Temperature 22°C Relative Humidity 50%

Atmospheric Pressure 1019mbar

3. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz - 40GHz is  $\pm 1.5dB$ .

4. Test date: 31 October, 2011 Tested By: Andy Wang

Requirement(s): According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

#### Procedures:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

3.

- 4. Set the spectrum analyzer as Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel, RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 5. Set the measured low, middle and high frequency and test 20dB bandwidth with spectrum analyzer.

Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2402	1.052
Middle	2441	1.048
High	2480	1.048

Please refer to the following plots.


 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011


 Page:
 23 of 53

 www.siemic.com.cn

#### Low Channel



#### **Middle Channel**




 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 24 of 53

 www.siemic.com.cn

#### **High Channel**



 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 25 of 53

 www.siemic.com.cn

# 5.6 §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyzer was connected to the antenna terminal.

2. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz - 40GHz is  $\pm 1.5dB$ .

3. Environmental Conditions

Temperature 22°C Relative Humidity 50% Atmospheric Pressure 1019mbar

4. Test date: 30 October, 2011 Tested By: Andy Wang

#### Standard Requirement:

According to §15.247(a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

#### Procedures:

- 1. Place the EUT on the table and set it in hopping function transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as Start=2400MHz, Stop = 2483.5MHz, Span = the frequency band of operation, RBW  $\geq$ 1% of the span, VBW  $\geq$  RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 4. Count the quantity of peaks to get the number of hopping channels.

Test Result: Compliant.

Please refer to following tables and plots

Test Mode: Transmitting

Frequency Range (MHz)	Number of Hopping Channel	Limit	
2400-2483.5	79	≥ 15	


 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 26 of 53

 www.siemic.com.cn

#### **Number of Hopping Channels**



 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 27 of 53

 www.siemic.com.cn

#### 5.7 §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME)

Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyzer was connected to the antenna terminal.

2. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz - 40GHz is  $\pm 1.5dB$ .

3. Environmental Conditions

Temperature 22°C Relative Humidity 50% Atmospheric Pressure 1019mbar

4. Test date: 30 October, 2011 Tested By: Andy Wang

#### Standard Requirement:

According to §15.247(a)(1)(iii), The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used

#### Procedures:

- 1. Place the EUT on the table and set it in transmitting mode and switch on frequency hopping function.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as Span = zero span, centered on a hopping channel,

RBW=1MHz, VBW ≥ RBW, Sweep = as necessary to capture the entire dwell time per hopping channel, Detector function = peak, Trace = max hold.

4. Calculate the time of occupancy in a period with time occupancy of a burst and quantity of bursts.

Test Result: Compliant.


Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result			
	Low	0.396	0.12672	0.4	Pass			
DH 1	Middle	0.396	0.12672	0.4	Pass			
DH 1	High	0.396	0.12672	0.4	Pass			
	<i>Note:</i> Dwell time=Pulse time (ms) × $(1600 \div 2 \div 79) \times 31.6$ Second							
	Low	1.672	0.26752	0.4	Pass			
DH 3	Middle	1.672	0.26752	0.4	Pass			
DH 3	High	1.664	0.26624	0.4	Pass			
	<i>Note:</i> Dwell time=Pulse time (ms) × $(1600 \div 4 \div 79) \times 31.6$ Second							
	Low	2.944	0.31403	0.4	Pass			
DH 5	Middle	2.944	0.31403	0.4	Pass			
	High	2.960	0.31573	0.4	Pass			
	<i>Note:</i> Dwell	time=Pulse Time (m	$(1600 \div 6 \div 6)$	79) ×31.6 Sec	cond			


Please refer to the following plots.

#### **Low Channel for DH1**




| Serial#: 11070102-FCC-RF-BT | Issue Date: 3 November, 2011 | Page: 29 of 53 | www.siemic.com.cn


#### **Middle Channel for DH1**




#### **High Channel for DH1**



#### **Low Channel for DH3**




#### Middle Channel for DH3




Serial#: 11070102-FCC-RF-B1 Issue Date: 3 November, 2011 Page: 31 of 53 www.siemic.com.cn


#### **High Channel for DH3**




#### **Low Channel for DH5**



#### **Middle Channel for DH5**



#### **High Channel for DH5**



 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 33 of 53

 www.siemic.com.cn

#### 5.8 §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyzer was connected to the antenna terminal.

2. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz, 40GHz is +1.5dB

range 30MHz – 40GHz is ±1.5dB. Environmental Conditions

Temperature 22°C
Relative Humidity 50%
Atmospheric Pressure 1019mbar

4. Test date: 30 October, 2011 Tested By: Andy Wang

#### Standard Requirement:

According to §15.247(b)(2), For frequency hopping systems in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5MHz band: 0.125watts.

#### Procedures:

3.

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel, RBW > the 20 dB bandwidth of the emission being measured, VBW ≥ RBW, Sweep=auto, Detector function=peak, Trace = max hold.
- 4. Then set the EUT to transmit at low, middle and high channel and measure the conducted output power separately.

Test Result: Compliant.

Please refer to following tables and plots



Serial#: 11070102-FCC-RF-BT Issue Date: 3 November, 2011 Page: 34 of 53 www.siemic.com.cn

Test Mode: Transmitting

Channel	Channel frequency (MHz)	Peak output power (dBm)	Power output (mW)	Limit (mW)
Low channel	2402	2.31	1.702	1000
Middle channel	2441	0.90	1.230	1000
High channel	2480	-0.82	0.828	1000

**Note:** The data above was tested in conducted mode.


 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011


 Page:
 35 of 53

 www.siemic.com.cn

#### **Low Channel**




#### **Middle Channel**



Serial#: 11070102-FCC-RF-BT Issue Date: 3 November, 2011 Page: 36 of 53 www.siemic.com.cn

#### **High Channel**



 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 37 of 53

 www.siemic.com.cn

### 5.9 **§**15.247(d) - BAND EDGES TESTING

#### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Result: Compliant

 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 38 of 53

 www.siemic.com.cn


Test Mode: Transmitting

Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)
2399.490	51.28	20
2493.112	51.01	20

Note: The point fall into the strict band was recorded in FCC 15.209, please refer to the restrict band testing.

### Please refer to follow plots:

#### **Band Edge: Left Side**



Date: 30.AUG.2010 11:02:33


 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 39 of 53

 www.siemic.com.cn

### **Band Edge: Right Side**



Date: 30.AUG.2010 10:56:19

 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 40 of 53

 www.siemic.com.cn

# Annex A. TEST INSTRUMENT & METHOD

## Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES

Instrument	Manufacturer	Model	CAL Date	CAL Due Date
Spectrum Analyzer	HP	8563 E	2011.01.10	2012.01.10
EMI Receiver	Rohde & Schwarz	ESPI 3	2011.05.25	2012.05.25
Antenna (30MHz~2GHz)	Sunol Sciences	JB1	2011.10.04	2012.10.04
Horn Antenna (1~18GHz)	A-INFOMW	JXTXLB-10180	2011.10.04	2012.10.04
Horn Antenna (1~18GHz)	N/A	N/A	2011.10.04	2012.10.04
Pre-Amplifier(0.01 ~ 1.3GHz)	HP	8447F	2011.05.25	2012.05.25
Pre-Amplifier(0.1 ~ 18GHz)	MITEQ	AMF-7D- 00101800-30-10P	2011.05.25	2012.05.25
Horn Antenna (18~40GHz)	Com Power	AH-840	2011.05.25	2012.05.25
Microwave Pre-Amp (18~40GHz)	Com Power	PA-840	2011.05.25	2012.05.25

 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011


 Page:
 41 of 53

 <a href="https://www.siemic.com.cn">www.siemic.com.cn</a>

### Annex A.ii. CONDUCTED EMISSIONS TEST DESCRIPTION

#### Test Set-up

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in <u>Annex B</u>.
- 2. The power supply for the EUT was fed through a 50**W**50**m**H EUT LISN, connected to filtered mains.
- The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
- 4. All other supporting equipments were powered separately from another main supply.



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration1.

#### **Test Method**

- 1. The EUT was switched on and allowed to warm up to its normal operating condition.
- 2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
- 3. High peaks, relative to the limit line, were then selected.
- 4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 KHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
- 5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

#### **Description of Conducted Emission Program**

This EMC Measurement software run LabView automation software and offers a common user interface for electromagnetic interference (EMI) measurements. This software is a modern and powerful tool for controlling and monitoring EMI test receivers and EMC test systems. It guarantees reliable collection, evaluation, and documentation of measurement results. Basically, this program will run a pre-scan measurement before it proceeds with the final measurement. The pre-scan routine will run the common scan range from 150 kHz to 30 MHz; the program will first start a peak and average scan on selectable measurement time and step size. After the program complete the pre-scan, this program will perform the Quasi Peak and Average measurement, based on the pre-scan peak data reduction result.

 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 42 of 53

 www.siemic.com.cn

### Sample Calculation Example

At 20 MHz limit = 250 mV = 47.96 dBmV

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver = 40.00 dBmV

(Calibrated for system losses)

Therefore, Q-P margin = 47.96 - 40.00 = 7.96

i.e. 7.96 dB below limit

Serial#: 11070102-FCC-RF-BT Issue Date: 3 November, 2011 Page: 43 of 53 www.siemic.com.cn

### Annex A. iii. RADIATED EMISSIONS TEST DESCRIPTION

#### Limit

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (µV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

#### **EUT Characterisation**

EUT characterisation, over the frequency range from 30MHz to 10<sup>th</sup> Harmonic, was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS).

 Serial#:
 11070102-FCC-RF-BT


 Issue Date:
 3 November, 2011

 Page:
 44 of 53

 www.siemic.com.cn

#### Test Set-up

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
- 2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
- 3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



#### **Test Method**

The following procedure was performed to determine the maximum emission axis of EUT:

- 1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

#### Final Radiated Emission Measurement

- 1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
- 2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
- 3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
- 4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from  $0 \circ to 360 \circ with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.$
- 5. Repeat step 4 until all frequencies need to be measured were complete.
- 6. Repeat step 5 with search antenna in vertical polarized orientations.

 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 45 of 53

 www.siemic.com.cn

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100 kHz	100 kHz
Above 1000	Peak	1 MHz	1 MHz
Above 1000	Average	1 MHz	10 Hz

#### **Description of Radiated Emission Program**

This EMC Measurement software run LabView automation software and offers a common user interface for electromagnetic interference (EMI) measurements. This software is a modern and powerful tool for controlling and monitoring EMI test receivers and EMC test systems. It guarantees reliable collection, evaluation, and documentation of measurement results. Basically, this program will run a pre-scan measurement before it proceeds with the final measurement. The pre-scan routine will run the scan on four different antenna heights, 2 antenna polarity, and 360 degrees table rotation. For example, the program was set to run 30 MHz to 1 GHz scan; the program will first start from a meter antenna height and divide the 30 MHz to 1 GHz into 10 separate parts of maximum hold sweeps. Each parts of maximum hold sweep, the program will collect the data from 0 degree to 360 degrees table rotation. After the program complete the 1m scan, the antenna continues to rise to 2m and continue the scan. The step will repeated for all specified antenna height and polarity. This program will perform the Quasi Peak measurement after the signal maximization process and pre-scan routine. The final measurement will be base on the pre-scan data reduction result.

#### Sample Calculation Example

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

Peak = Reading + Corrected Factor

where

Corr. Factor = Antenna Factor + Cable Factor - Amplifier Gain (if any) And the average value is

Average = Peak Value + Duty Factor or Set RBW = 1MHz, VBW = 10Hz.

Note:

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.



 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 46 of 53

 www.siemic.com.cn

## Annex B. EUT AND TEST SETUP PHOTOGRAPHS

Please see attachment

| Serial#: 11070102-FCC-RF-BT | Issue Date: 3 November, 2011 | Page: 47 of 53 | www.siemic.com.cn

## Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

### **EUT TEST CONDITIONS**

### Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Equipment Description (Including Brand Name)	Model & Serial Number	Cable Description (List Length, Type & Purpose)
N/A	N/A	N/A


 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011


 Page:
 48 of 53

 <a href="https://www.siemic.com.cn">www.siemic.com.cn</a>

## Block Configuration Diagram for Conducted Emissions



## Block Configuration Diagram for Radiated Emissions





 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 50 of 53

 www.siemic.com.cn

## Annex C.ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
Emissions Testing	The EUT was continuously transmitting to stimulate the worst case.



 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 51 of 53

 www.siemic.com.cn

## Annex D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST

Please see attachment

 Serial#:
 11070102-FCC-RF-BT

 Issue Date:
 3 November, 2011

 Page:
 52 of 53

 www.siemic.com.cn

### Annex E. SIEMIC ACCREDITATION CERTIFICATES

SIEMIC ACREDITATION DETAILS: FCC Test Site Registration No. 986914

### FEDERAL COMMUNICATIONS COMMISSION

Laboratory Division 7435 Oakland Mills Road Columbia, MD 21046

April 19, 2011

Registration Number: 986914

SIEMIC Nanjing (China) Laboratories
2-I Longcang Avenue,
Yuhua Economic and Technology Development Park,
Nanjing, 210039
China

Attention: Leslie Bai,

Re: Measurement facility located at 2-1 Longcang Avenue, Nanjing, China

Anechoic chamber (3 meters) and 3&10 meter OATS

Date of Renewal: April 19, 2011

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website <a href="www.fcc.gov">www.fcc.gov</a> under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Phyllis Parrish Industry Analyst

11070102-FCC-RF-BT Serial#: Issue Date: 3 November, 2011 Page:

#### SIEMIC ACREDITATION DETAILS: Industry of Canada Test Site Registration No. 4842B

| Industry Industrie

January 25, 2011

OUR FILE: 46405-4842 Submission No: 145222

#### Siemic Nanjing (China) Laboratories

2-I Longcang Avenue Yuhua Economic & Technology Dev. Park, Nanjing China

Attention: Leslie Bai

Dear Sir/Madame

The Bureau has received your application for the registration of a 3/10m OATS. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought ( Site# 4842B-2 ). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please keep for your records the following information:

- The company address code associated to the site(s) located at the above address is: 4842B

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 or later shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 metre OATS or 3 metre chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to exceed three years. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL;

http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h\_tt00052e.html.

If you have any questions, you may contact the Bureau by e-mail at certification bureau@ic.gc.ca Please reference our file and submission number above for all correspondence.

Yours sincerely.

Dalwinder Gill

Certification and Engineering Burvas 3701 Carling Ave., Building 94

P.O. Box 11490, Station 'El Ottawa, Ontario 8211 882 firmit delwinder gilligie go ca Tel. No. (623) 998-8363

Fax. No. (613) 990-4752